

[www.neidlein.de](http://www.neidlein.de)



# Tools for Clamping between Centers

**process oriented for turning, hard turning, grinding and milling**



# Process oriented clamping solutions

**with maximum torque transmission  
and supreme accuracy**

# NEIDLEIN- SPANNZEUGE GmbH

The company NEIDLEIN is a leading international manufacturer of clamping tools in the metalworking industry. All over the world our products help to optimize production processes and to realize high quality requirements. The customer workpieces to be machined are clamped between centers by our tools, this means that the entire outer contour of the workpieces can be machined efficiently and with high precision. Our clamping tools are used in hard turning, cylindrical grinding, milling and mill-turning processes.

With our dedicated team, we develop and manufacture an extensive portfolio that includes both standard products and customized special solutions. We are certified according to ISO9001 and ISO14001 standards.

A high level of customer satisfaction, employee loyalty and sustainability in all areas are very important to us.





## A leading edge based on direct dialogue

One of the cornerstones of our policy has always been to provide consistent project-based support – you generally have the same contact partner from the initial enquiry right through to conception, design and delivery.

Close networking between design, production and sales means we make decisions fast. This means short delivery times and a high level of service quality – giving you the competitive advantage and leading edge needed for success.



flange adapter ZFE



dead center FNA and changeable center cone



face driver FSB



live center RN



face driver FFBR



carbide center pin DIN 807



face driver FSP



live center RNCS with carbide tip



mandrel ISD

# Content

## **FACE DRIVERS**

with appropriate changable parts and accessories

---

**8**

## **PIPE DRIVERS & DRIVE DOGS**

with appropriate changable parts and accessories

---

**94**

## **MANDRELS**

---

**100**

## **MOUNTING ELEMENTS**

with appropriate accessories

---

**104**

## **LIVE CENTERS & DEAD CENTERS**

with appropriate accessories

---

**114**

## **SPECIAL APPLICATIONS**

---

**162**

## **GENERAL ACCESSORIES, SERVICE & TRAINING**

---

**170**



FSB



FFB



FSP

## FOR TURNING AND HARD TURNING WITH DRIVE PINS



<b>Face Drivers FSB / SB</b>	<b>10</b>
<b>Face Drivers FFB / FFBH</b>	<b>18</b>
Drive pins FSB / SB / FFB / FFBH · chisel SL / SR / NV	24
Drive pins FSB / SB / FFB / FFBH · KV-HS	26
Drive pins FSB / SB / FFB / FFBH · FV diamond	27
Drive pins FSB / SB / FFB / FFBH · chisel carbide	28
Center pins FSB / SB	30
Center pins FFB / FFBH	31
<b>Face Drivers FSBR / SBR</b>	<b>32</b>
Drive pins FSBR / SBR · chisel SL / SR	34
Center pins FSBR / SBR	35

## FOR TURNING, TURN-MILLING AND GRINDING WITH DRIVE DISKS



<b>Face Drivers FSP / FSPB / SP</b>	<b>36</b>
Drive disks FSP / FSPB / SP · chisel NV / SL / SR	42
Center pins FSP / FSPB / SP	45
Changeable parts OX for tensile samples	46
<b>Face Drivers FSPV / FSPBV / SPV</b>	<b>50</b>
Drive disks FSPV / FSPBV / SPV · chisel NV	54
Center pins FSP(V) / FSPB(V) / SP(V)	57

# Face Drivers

with appropriate changable parts and accessories



FFBR



FDNC

## Face Drivers FFP 58

Drive disks FFP · chisel NV / SL / SR 62

Drive disks FFP · KV diamond 65

Center pins FFP 66

## Face Drivers FFPV 68

Drive disks FFPV · chisel NV 72

Center pins FFP(V) 75

## FOR GRINDING WITH DRIVE PINS



### Face Drivers FFBR / FBSR 78

Drive pins FFBR / FBSR · chisel SR · diamond 82

Center pins FFBR / FBSR 83

### Face Drivers FFB / FFBH 84

Center pins FFB / FFBH 87

Drive pins FFB / FFBH · chisel SR · diamond 88

## FOR MILLING WITH DRIVE HEADS



### Face Drivers FDNC 90

Drive heads FDNC 92

Center pins FDNC 93

## Face Drivers FSB / SB



### with drive pins and movable center pin

The entire surface of the workpiece can be tooled and finished by clamping with a maximum of torque transmission. NEIDLEIN face drivers are mechanical clamping systems which are suited **for turning as well as hard turning.**

Face drivers of type FSB / SB are power-operated by the thrust of the tailstock. Workpieces are clamped centrally using a movable center pin. This way different centerings can be adjusted, thus ensuring a constant datum-point at the end face of the workpieces.

#### Type FSB with flange retainer

Type FSB is mounted onto the machine spindle nose using a flange adapter.



#### Type SB with MK- or cylindrical retainer

Type SB with taper shank and extracting nut for fast mounting into the machine spindle.



#### NEIDLEIN face drivers FSB / SB with movable center pins ensure:

- a maximum of torque transmission, thus achieving high metal removing rates
- datum-point at the end face of the workpiece  
stable datum-point in case of different centerings
- extended tool-life of driving devices and cutting tools due to vibration-free running
- run-out deviation in the process 0.015 - 0.02 mm
- clamping force is triggered by tailstock
- fixed center pin/fixed datum-point in clamped state
- compensating driving devices/ideal clamping of the workpiece
- simple handling


## Clamping principle

The center pin located on the side of the tailstock pushes the workpiece against the movable center pin of the face driver. The center pin will draw back until the surface of the workpiece bears against the drive pins. In this state the clamping bolt is clamped over the power flow in order to ensure a fixed datum-point during the entire tooling process.


The drive pins are "floatingly", thus compensating for variations in workpiece, squareness and surface finish. The entire surface of the workpiece can now be finished in one single clamping. Please check page 15 - 16 for metal removing rates to be obtained as well as for the tailstock forces required. Compatible standard drive pins and center pins are listed on page 24 - 31.

We will be glad to design clamping devices suitable for your workpieces.

### Type FSB with flange retainer



## Technical data – type FSB face driver



type	d	d1	center Ø	d2	d3	d5	d6	l1	l2	drive pin	fixing screws		clamping Ø			max. workpiece weight [kg] *	cat. no.
											type	pcs	D1	D2	D3		
<b>FSB</b>																	
<b>01</b>	48	22	0-5	6	160	25	133.4	115	28	3	M12	3	8	11	17	6	<b>730 12</b>
<b>0</b>	48	22	0-3	8	160	25	133.4	115	28	3	M12	3	6	11	19	8	<b>730 01</b>
<b>11</b>	42	6	0-6	6	160	25	133.4	115	28	3	M12	3	11	14	20	12	<b>730 11</b>
<b>1</b>	48	8	0-8	8	160	25	133.4	115	28	3	M12	3	13	18	26	25	<b>730 02</b>
<b>2</b>	70	14	2-14	10	160	25	133.4	115	23	6	M12	3	26	31	36	50	<b>730 03</b>
<b>3</b>	70	18	2-18	10	160	25	133.4	115	33	6	M12	3	34	39	44	90	<b>730 04</b>
<b>35</b>	80	14	2-14	15	160	25	133.4	115	33	6	M12	3	29	39	49	130	<b>730 09</b>
<b>4</b>	90	24	3-24	15	160	32	133.4	115	72	6	M12	3	39	49	59	250	<b>730 05</b>
<b>45</b>	100	28	3-28	15	160	32	133.4	115	72	6	M12	3	49	59	69	350	<b>730 10</b>
<b>5</b>	132	35	6-35	20	160	45	133.4	115	164	6	M12	3	69	84	99	700	<b>730 06</b>
<b>55</b>	182	35	6-35	20	220	45	171.4	115	165	6	M16	3	110	125	140	1500	<b>730 08</b>
<b>6</b>	212	35	6-35	20	250	45	210	115	165	6	M20	3	140	155	170	2100	<b>730 07</b>
<b>7</b>	255	50	25-48	20	290	50	250	132	165	6	M20	6	180	195	210	3300	<b>730 13</b>
<b>75</b>	302	50	25-48	20	348	50	310	132	165	6	M20	6	230	245	260	5000	<b>730 14</b>
<b>8</b>	360	80	30-76	30	440	78	394	190	262	6	M20	6	270	290	310	7000	<b>730 16</b>
<b>85</b>	410	80	30-76	30	490	78	444	190	262	6	M20	6	320	340	360	10000	<b>730 15</b>

\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7

- All face drivers are supplied without drive pins. (drive pins see page 24 - 29)
- Types FSB 01/0 are supplied with center body, all other types without center pin. (center pins see page 30 - 31)
- Mounting elements for face drivers see page 104 - 109.
- For vertical use of the face driver the center pin and drive pins must be secured against falling out. (Special design)


It is the purpose of a flange-adapter to provide stable connection to the machine spindle. We supply these flange adapters for various sizes of spindle noses either in standard size (DIN ISO 702-1 / DIN 55028) or for spindle noses specific to manufacturer of machine-tools. Thus face drivers of type FSB can be used on different machines. Driving devices and center pins can be exchanged front view on the machine without any effort.

Upon request and depending on the tooling direction of the machine the face driver can be equipped optionally with drive pins for counter-clockwise tooling (SR / tooling direction M3), for clockwise tooling (SL / tooling direction M4) or for both tooling directions (NV = bi-directional).

Apart from the clamping diameters listed in the table under D1, D2, D3 we can also supply intermediate dimensions upon request. We can as well make extra-large center pins or mushroom centers appropriate to oversized centerings in workpieces.

## Technical data – type SB face driver

type SB 01/0



type SB	MK	d	d1	center Ø	d2	d3	l1	l2	l3	drive pin	clamping Ø			max. workpiece weight [kg]**	cat. no.
											D1	D2	D3		
01	3	48	22	0-5	6	M28 x 1.5	87	61	14	3	8	11	17	6	<b>720 16</b>
	4	48	22	0-5	6	M35 x 1.5	87	74	16	3	8	11	17	6	<b>720 17</b>
	5	48	22	0-5	6	M48 x 1.5	87	97	19	3	8	11	17	6	<b>720 18</b>
0	3	48	22	0-3	8	M28 x 1.5	87	61	14	3	6	11	19	8	<b>720 01</b>
	4	48	22	0-3	8	M35 x 1.5	87	74	16	3	6	11	19	8	<b>720 02</b>
	5	48	22	0-3	8	M48 x 1.5	87	97	19	3	6	11	19	8	<b>720 03</b>
11	3	42	6	0-6	6	M28 x 1.5	80	61	14	3	11	14	20	12	<b>720 19</b>
	4	42	6	0-6	6	M35 x 1.5	80	74	16	3	11	14	20	12	<b>720 20</b>
	5	42	6	0-6	6	M48 x 1.5	80	97	19	3	11	14	20	12	<b>720 21</b>
1	3	48	8	0-8	8	M28 x 1.5	80	61	14	3	13	18	26	25	<b>720 04</b>
	4	48	8	0-8	8	M35 x 1.5	80	74	16	3	13	18	26	25	<b>720 05</b>
	5	48	8	0-8	8	M48 x 1.5	80	97	19	3	13	18	26	25	<b>720 06</b>
2	4	70	14	2-14	10	M35 x 1.5	80	74	16	6	26	31	36	50	<b>720 07</b>
	5	70	14	2-14	10	M48 x 1.5	80	97	19	6	26	31	36	50	<b>720 08</b>
3	4	70	18	2-18	10	M35 x 1.5	80	74	16	6	34	39	44	90	<b>720 09</b>
	5	70	18	2-18	10	M48 x 1.5	80	97	19	6	34	39	44	90	<b>720 10</b>
4	5	90	24	3-24	15	M48 x 1.5	104	97	19	6	39	49	59	250	<b>720 11</b>
	6	90	24	3-24	15	M70 x 1.5	104	134	20	6	39	49	59	250	<b>720 12</b>
5	6	132	35	6-35	20	M70 x 1.5	135	134	20	6	69	84	99	700	<b>720 13</b>
55	6	182	35	6-35	20	M70 x 1.5	140	134	20	6	110	125	140	1200	<b>720 15</b>
6	6	212	35	6-35	20	M70 x 1.5	140	134	20	6	140	155	170	1600	<b>720 14</b>

\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7

- All face drivers are supplied without drive pins. (drive pins see page 24 - 29)
- Types SB 01/0 are supplied with center body, all other types without center pin. (center pins see page 30 - 31)
- Reducing sleeves for face drivers see page 112 - 113.

Type series SB with MK retainer is embedded directly in the machine spindle and removed by means of an extracting nut. Driving devices and center pins can be exchanged front view on the machine without any effort.


If necessary and depending on the tooling direction of the machine the face driver can be equipped optionally with drive pins for counter-clockwise tooling (SR/tooling direction M3), for

clockwise tooling (SL/tooling direction M4) or for both tooling directions (NV = bi-directional).

Apart from the clamping diameters listed in the table under D1, D2, D3 we also supply intermediate dimensions upon request. We also make extra-large center pins or mushroom centers appropriate to oversized centerings in workpieces.

### Technical data – type SB face driver with cylindrical shank

Type SB 01/0



type SB	cyl.	d	d1	center Ø	d2	d3	l1	l2	drive pin	clamping Ø			max. workpiece weight [kg] *	cat. no.
										D1	D2	D3		
<b>01</b>	<b>25</b>	48	22	0 - 5	6	25	71	90	3	8	11	17	6	<b>725 01</b>
<b>0</b>	<b>25</b>	48	22	0 - 3	8	25	71	90	3	6	11	19	8	<b>725 02</b>
<b>11</b>	<b>25</b>	42	6	0 - 6	6	25	70	90	3	11	14	20	12	<b>725 03</b>
<b>1</b>	<b>32</b>	48	8	0 - 8	8	32	70	90	3	13	18	26	25	<b>725 05</b>
<b>2</b>	<b>32</b>	70	14	2 - 14	10	32	70	90	6	26	31	36	50	<b>725 06</b>
<b>3</b>	<b>32</b>	70	18	2 - 18	10	32	70	90	6	34	39	44	90	<b>725 07</b>
	<b>40</b>	70	18	2 - 18	10	40	70	90	6	34	39	44	90	<b>725 08</b>

\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7

- All face drivers are supplied without drive pins. (drive pins see page 24 - 29)
- Types SB 01/0 are supplied with center body, all other types without center pin. (center pins see page 30 - 31)

Type series SB with cylindrical shank for clamping in a collet or in a chuck. Driving devices and center pins can be exchanged front view on the machine without any effort.


If necessary and depending on the tooling direction of the machine the face driver can be equipped optionally with drive pins for counter-clockwise tooling (SR/tooling direction M3), for clockwise tooling (SL/tooling direction M4) or for both tooling directions (NV = bi-directional).

Apart from the clamping diameters listed in the table under D1, D2, D3 we also supply intermediate dimensions upon request. We also make extra-large center pins or mushroom centers appropriate to oversized centerings in workpieces.

## Face Drivers FSB / SB · Calculations

### tailstock force / maximum chip cross section of metal removing

**PRINCIPLE:** The tailstock force pushes the workpiece against the movable center pin of the face driver. The center pin will draw back until the surface of the workpiece bears against the drive pins.



#### ■ tailstock force $F_R$ :

The force onto the face driver required for metal removing is calculated on the basis of the empirical formula:

$$F_R = [(q_{max} \times 1000 \times \frac{D}{d}) + 1000] \times m$$

$F_R$	[N]	tailstock force
$q_{max}$	[mm <sup>2</sup> ]	maximum of chip cross section for metal removing
$D$	[mm]	cutting diameter
$d$	[mm]	clamping diameter
$m$	[-]	material factor (see adjustment-chart below)

#### ■ maximum chip cross section $q_{max}$ :

At a given tailstock force, maximum chip cross section is calculated as follows:

$$q_{max} = \frac{\frac{F_R}{m} - 1000}{1000 \times \frac{D}{d}}$$

**EXPLANATORY NOTES:** The calculations refer to tooling against the face driver. In case of tooling against tailstock the calculated chip cross section is reduced by approx. 40%. The first chip, however, should always be machined toward the face driver, in order to achieve an ideal penetration of the drive pins. The ratio  $D/d$  should not exceed 2, otherwise it would work inefficiently.

#### Material factor $m$ adjustment chart:

material factor $m$	1.4	1.2	1.1	1.0	0.8
<b>Rm [N/mm<sup>2</sup>]</b>	1000	800	700	600	400
<b>examples</b>	42CrMo4	16MnCr5 25CrMo4	C 15E (Ck 15) C 45E (Ck 45)	S355J0 35S20	S235J0

## Chisel load of drive pins

Keep the chisel load within the following range:  
250 - 350 N per mm chisel length

- **the chisel load is calculated as follows:**

$$BS = \frac{F_R}{n \times s}$$

$$BS = \frac{7200 \text{ N}}{6 \times 4 \text{ mm}} = 300 \frac{\text{N}}{\text{mm}}$$

BS	[N / mm]	chisel load
F <sub>R</sub>	[N]	tailstock force
n	[-]	number of drive pins
s	[mm]	chisel length

**EXEMPLIFICATION:** turning with FSB 3 face driver, 6 drive pins, respective length of chisel 4 mm, tailstock force 7200 N

### CALCULATION EXAMPLE for type FSB / SB

#### Specific data of machine and workpiece:

maximum tailstock force: 10000 N  
material of the workpiece: C15E  
diameter of the workpiece,  
side of face driver: Ø48 mm  
turning diameter: Ø90 mm

#### Selection of face driver:

face driver FSB 3 / clamping Ø 44 mm  
6 drive pins each 4 mm chisel length

- **tailstock force F<sub>R</sub>:**

In order to ensure sufficient entrainment (see chisel load of drive pins) a tailstock force of approx. 7200 N has to be supplied.

$$BS = \frac{F_R}{n \times s}$$

$$F_R = 300 \frac{\text{N}}{\text{mm}} \times 6 \times 4 \text{ mm} = 7200 \text{ N}$$

- **maximum chip cross section q<sub>max</sub>:**


The maximum chip cross section (at the ultimate turning-Ø) is calculated as follows:

$$q_{max} = \frac{\frac{7200 \text{ N}}{1.1} - 1000}{1000 \times \frac{90 \text{ mm}}{44 \text{ mm}}} = 2.71 \text{ mm}^2$$

#### Determination of material factor m:

as per adjustment chart material factor: m (C15E) = 1.1

**EXPLANATORY NOTES:** This calculation refers to tooling against the face driver. The calculated chip cross section refers to the ultimate turning diameter. In case of further tooling towards the axis of rotation of the workpiece, even larger chip cross sections can be achieved (» formula), commensurate with turning diameter.



## Face Drivers FFB / FFBH



### with drive pins and fixed center pin for high true run accuracy

The entire surface of the workpiece can be completely machined with one single clamping and with a maximum of torque transmission. NEIDLEIN face drivers are mechanical clamping systems, suitable **for turning and hard turning** likewise.

Face drivers of type FFB/FFBH are power-operated on the side of the machine spindle as well as the side of the tailstock. The workpieces are clamped centrally by the fixed center pin. This operation results in high true run-out accuracy.

Drive pins of type FFBH are hydraulically activated and compensated, thus achieving excellent true run-out accuracy.

#### Type FFB with flange retainer

Type FFB is mounted onto the machine spindle nose using flange-adapter, adjustable for true run-out.



#### Type FFBH with flange retainer

Type FFBH is mounted onto the machine spindle nose using flange-adapter adjustable for true run-out.



#### NEIDLEIN face drivers FFB / FFBH with fixed center pin ensure:

- maximum of torque transmission, thus achieving a high rate of metal removing
- datum-point location in the center of the workpiece ensures constant measures of length
- extended service life of drive pins and cutting tools due to vibration-free running
- run-out deviation in the process
  - type FFB: 0.005 - 0.01 mm
  - type FFBH: 0.002 - 0.005 mm
- fixed clamping location
- compensating driving devices/ideal clamping of the workpiece
- easy handling


## Clamping principle

The center pin located on the side of the tailstock pushes the workpiece against the fixed center pin of the face driver. The motion of the drive pins against the surface of the workpiece is initiated by the clamping cylinder mounted into the machine. The drive pins are "floatingly" suspended, thus compensating irregularities with regard to possible unevenness of the surface of workpieces. The datum-point of workpieces on the machines is determined by the size of the center hole. The entire surface of the workpiece can now be tooled in one single clamping.


See page 22 - 23 with data for achievable removal of material and the thrust requested. The appropriate standard drive pins and center pins can be found on page 24 - 31.

We will be glad to design clamping devices suitable for your workpieces.

### Type FFB / FFBH with flange retainer



### Technical data – type FFB face drivers



type FFB 01/0

type	d	center Ø	d2	d3	d5	d6	d8	A	l2	drive pin	fixing screw		clamping Ø			max. workpiece weight [kg] *	cat. no.
											type	pcs	D1	D2	D3		
FFB																	
<b>01</b>	60	1 - 5	6	160	18	133.4	3.5	115	38	3	M12	3	8	11	17	6	<b>731 01</b>
<b>0</b>	60	1 - 3	8	160	18	133.4	3	115	38	3	M12	3	6	11	19	8	<b>731 12</b>
<b>11</b>	42	2 - 6.5	6	160	12	133.4	4.25	115	38	3	M12	3	11	14	20	12	<b>731 11</b>
<b>1</b>	48	4 - 8.5	8	160	18	133.4	6.25	115	38	3	M12	3	13	18	26	25	<b>731 02</b>
<b>2</b>	70	4 - 9	10	160	22	133.4	6.5	115	38	3	M12	3	26	31	36	50	<b>731 03</b>
<b>3</b>	70	6 - 11	10	160	22	133.4	8.5	115	38	3	M12	3	34	39	44	90	<b>731 04</b>
<b>35</b>	80	4 - 9	15	160	22	133.4	6.5	115	38	3	M12	3	29	39	49	130	<b>731 13</b>
<b>4</b>	90	10 - 15	15	160	25	133.4	12.5	115	38	5	M12	3	39	49	59	250	<b>731 05</b>
<b>45</b>	100	10 - 15	15	160	25	133.4	12.5	115	54	5	M12	3	49	59	69	400	<b>731 06</b>
<b>5</b>	132	10 - 15	20	160	25	133.4	12.5	115	54	5	M12	3	69	84	99	1000	<b>731 07</b>
<b>55</b>	182	10 - 15	20	220	40	171.4	12.5	155	54	5	M16	3	110	125	140	1600	<b>731 08</b>
<b>6</b>	220	10 - 15	20	250	40	210	12.5	171	54	5	M20	3	140	155	170	2500	<b>731 09</b>

\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7


- All face drivers are supplied without drive pins. (drive pins see page 24 - 29)
- Types FFB 01/0 are supplied with center body, all other types without center pin. (center pin see page 30 - 31)
- The diameter d8 refers to the standard center pins. (see page 30 - 31)
- Further center pins for other center holes upon request.
- Mounting elements for face drivers see page 104 - 109.
- For vertical use of the face driver the center pin and drive pins must be secured against falling out. (Special design)

It is the purpose of an adjustable flange-adapter to provide stable connection to the machine spindle. We supply these flange adapters for various sizes of spindle noses in standard size (DIN ISO 702-1 / DIN 55028) or for spindle noses specific to machine-tool manufacturer. Thus face drivers of type FFB can be used all-purpose on different machines. Driving devices and center pins can be exchanged front view on the machine without any effort.

Upon request and depending on the tooling direction of the machine, the face driver can be equipped optionally with drive pins for counter-clockwise tooling (SR / tooling direction M3), for clockwise tooling (SL / tooling direction M4) or for both tooling directions (NV = bi-directional).

Apart from the clamping diameters enlisted in the table under D1, D2, D3 we can also supply intermediate dimensions upon request. We can as well make extra-large center pins or mushroom centers appropriate to oversized centerings in workpieces.

### Technical data – type FFBH face drivers




type	d	center Ø	d2	d3	SW	d5	d6	d8	A	l2	drive pin	fixing screw		clamping Ø			max. workpiece weight [kg] *	cat. no.
												type	pcs	D1	D2	D3		
<b>FFBH</b>																		
<b>1</b>	70	4 - 8.5	8	160	24	12	133.4	6.25	115	35	3	M12	3	13	18	26	25	<b>631 02</b>
<b>2</b>	70	4 - 9	10	160	24	12	133.4	6.5	115	35	3	M12	3	26	31	36	50	<b>631 03</b>
<b>3</b>	70	6 - 11	10	160	24	12	133.4	8.5	115	35	3	M12	3	34	39	44	90	<b>631 04</b>
<b>4</b>	90	10 - 15	15	160	34	12	133.4	12.5	132	35	5	M12	3	39	49	59	250	<b>631 06</b>
<b>45</b>	100	10 - 15	15	160	34	12	133.4	12.5	132	35	5	M12	3	49	59	69	400	<b>631 07</b>
<b>5</b>	132	10 - 15	20	160	34	12	133.4	12.5	149	35	5	M12	3	69	84	99	1000	<b>631 08</b>

\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7

- All face drivers are supplied without drive pins and without center pins. (changeable parts see page 24 - 31)
- The diameter d8 refers to the standard center pins. (see page 30 - 31)
- Further center pins for other center holes upon request.
- Mounting elements for face drivers see page 104 - 109.
- For vertical use of the face driver the center pin and drive pins must be secured against falling out. (Special design)

### Technical data – type FFBH hydraulic unit



type	SW1	d5	L	d1	SW2	D	cat. no.
<b>FFBH</b>							
<b>1</b>	24	12	70.5	47	41	75	
<b>2</b>	24	12	70.5	47	41	75	<b>631 02 HE</b>
<b>3</b>	24	12	70.5	47	41	75	
<b>4</b>	34	12	70.5	65	59	93	<b>631 06 HE</b>
<b>45</b>	34	12	70.5	65	59	93	
<b>5</b>	34	12	70.5	87	81	131	<b>631 08 HE</b>


The general explanatory notes for this face driver FFBH can be obtained from the sheet "technical data – type FFB". For safe and smooth operation of face driver we recommend exchange of hydraulic unit after 1500 operating hours.

Furthermore, we offer the option for professional maintenance of the exchanged hydraulic units in our production plant.

## Face Drivers FFB / FFBH · Calculations

### force of clamping cylinder / maximum chip cross section

**PRINCIPLE:** The tailstock force pushes the workpiece against the fixed center pin of the face driver. The drive pins are activated by the clamping cylinder mounted into the machine.



#### ■ force of clamping cylinder $F_S$ :

The force onto the face driver required for metal removing is calculated on the basis of the empirical formula:

$$F_S = [(q_{max} \times 1100 \times \frac{D}{d}) + 1300] \times m$$

$F_R$	[N]	tailstock force
$q_{max}$	[mm <sup>2</sup> ]	maximum of chip cross section for metal removing
$D$	[mm]	cutting diameter
$d$	[mm]	clamping diameter
$m$	[-]	material factor (see adjustment-chart below)

#### ■ maximum chip cross section $q_{max}$ :

At a given force of clamping cylinder, the maximum chip cross section is calculated as follows:

$$q_{max} = \frac{F_S - 1300}{1100 \times \frac{D}{d}}$$

#### ■ tailstock force $F_R$ :

In case of tooling against the face driver the tailstock force has to be approx. 20 % more than the force of the clamping cylinder  $F_S$ .

In case of tooling against the tailstock, the tailstock should be approx. 40 - 50 % higher than the force of the clamping cylinder, if not, then the chip cross section should be reduced by approx. 30 %. (as there is an addition of force of clamping cylinder and cutting force).

**EXPLANATORY NOTES:** The first chip, however, should always be machined toward the face driver, in order to achieve an ideal penetration of the drive pins. The ratio  $D/d$  should not exceed 2, otherwise it would work inefficiently.

#### Material factor $m$ adjustment chart:

material factor $m$	1.4	1.2	1.1	1.0	0.8
<b>Rm [N / mm<sup>2</sup>]</b>	1000	800	700	600	400
<b>examples</b>	42CrMo4	16MnCr5	C 15E (Ck 15)	S355J0	S235J0
		25CrMo4	C 45E (Ck 45)	35S20	

## Chisel load of drive pins

Keep the chisel load within the following range:  
250 - 350 N per mm chisel length

- the chisel load is calculated as follows:

$$BS = \frac{F_S}{n \times s}$$

**EXEMPLIFICATION:** turning with FFB 3 face driver, 3 drive pins respective length of chisel 7 mm, force of clamping cylinder 6300 N

$$BS = \frac{4500 \text{ N}}{3 \times 5 \text{ mm}} = 300 \frac{\text{N}}{\text{mm}}$$

BS	[N/mm]	chisel load
F <sub>S</sub>	[N]	force of clamping cylinder
n	[-]	number of drive pins
s	[mm]	chisel length

### CALCULATION EXAMPLE for type FFB / FFBH

#### Specific data of machine and workpiece:

maximum force of clamping cylinder:	12000 N
material of the workpiece:	16MnCr5
diameter of the workpiece,	
side of face driver:	Ø 62 mm
tooling diameter:	Ø 120 mm

#### Selection of face driver:

face driver FFB 4 / clamping Ø 59 mm  
5 drive pins each 7.5 mm chisel length

- force of clamping cylinder F<sub>S</sub>:

In order to ensure sufficient entrainment (see chisel load of drive pins), a clamping cylinder force of approx. 11250 N is needed.

$$BS = \frac{F_S}{n \times s}$$

$$F_S = 300 \frac{\text{N}}{\text{mm}} \times 5 \times 7.5 \text{ mm} = 11250 \text{ N}$$

- maximum chip cross section q<sub>max</sub>:

The maximum chip cross section (at OD-Ø) is calculated as follows:

$$q_{\max} = \frac{\frac{11250 \text{ N}}{1.2} - 1300}{1100 \times \frac{120 \text{ mm}}{59 \text{ mm}}} = 3.61 \text{ mm}^2$$

#### Calculation of material factor m:

as per adjustment chart material factor: m (16MnCr5) = 1.2

**EXPLANATORY NOTES:** The calculated chip cross section refers to the extreme outer tooling diameter. In case of further tooling towards the axis of rotation of the workpiece, even larger chip cross sections can be achieved (» formula), commensurate with turning diameter.




## Drive Pins FSB / SB / FFB(H) · Chisel SL / SR / NV

for torque transmission onto the workpiece  
for soft / green tooling

Type FSB / SB / FFB(H) · chisel SL / SR / NV






view from tailstock onto the face driver



Technical data – type FSB / SB / FFB(H) · chisel SL / SR / NV

types 01, 11, 8 and 85 with chisel SL and SR are double chiselled



**TYPE CHISEL SL**  
for tooling  
direction M4

**TYPE CHISEL SR**  
for tooling  
direction M3

**TYPE CHISEL NV**  
for tooling  
direction M4 and M3

for type FSB / SB / FFB(H)	d2	clamping Ø			chisel length			cat. no.	cat. no.	cat. no.
		D1	D2	D3	l1	l2	l3			
<b>01</b>	6	8			1.5			<b>736 104</b>	<b>736 101</b>	<b>736 107</b>
	6		11			3		<b>736 105</b>	<b>736 102</b>	<b>736 108</b>
	6			17		6		<b>736 106</b>	<b>736 103</b>	<b>736 109</b>
	6			17		3		<b>736 106S</b>	<b>736 103S</b>	<b>736 109S</b>
<b>0</b>	8	6			1.5			<b>736 04</b>	<b>736 01</b>	<b>736 07</b>
	8		11			4		<b>736 05</b>	<b>736 02</b>	<b>736 08</b>
	8			19		8		<b>736 06</b>	<b>736 03</b>	<b>736 09</b>
	8			19		4		<b>736 06S</b>	<b>736 03S</b>	<b>736 09S</b>
<b>1</b>	8	13			1.5			<b>736 13</b>	<b>736 10</b>	<b>736 16</b>
	8		18			4		<b>736 14</b>	<b>736 11</b>	<b>736 17</b>
	8			26		8		<b>736 15</b>	<b>736 12</b>	<b>736 18</b>
	8			26		4		<b>736 15S</b>	<b>736 12S</b>	<b>736 18S</b>

**TYPE CHISEL SL**  
for tooling  
direction M4

**TYPE CHISEL SR**  
for tooling  
direction M3

**TYPE CHISEL NV**  
for tooling  
direction M4 and M3

for type FSB/SB/FFB(H)	d2	clamping Ø			chisel length			cat. no.	cat. no.	cat. no.
		D1	D2	D3	l1	l2	l3			
<b>11</b>	6	11			1.5			<b>736 76</b>	<b>736 73</b>	<b>736 79</b>
	6		14			3		<b>736 77</b>	<b>736 74</b>	<b>736 80</b>
	6			20			6	<b>736 78</b>	<b>736 75</b>	<b>736 81</b>
	6			20			3	<b>736 78S</b>	<b>736 75S</b>	<b>736 81S</b>
<b>2</b>	10	26			5			<b>736 22</b>	<b>736 19</b>	<b>736 25</b>
	10		31			7.5		<b>736 23</b>	<b>736 20</b>	<b>736 26</b>
	10			36			10	<b>736 24</b>	<b>736 21</b>	<b>736 27</b>
	10			36			5	<b>736 24S</b>	<b>736 21S</b>	<b>736 27S</b>
<b>3</b>	10	34			5			<b>736 31</b>	<b>736 28</b>	<b>736 34</b>
	10		39			7.5		<b>736 32</b>	<b>736 29</b>	<b>736 35</b>
	10			44			10	<b>736 33</b>	<b>736 30</b>	<b>736 36</b>
	10			44			5	<b>736 33S</b>	<b>736 30S</b>	<b>736 36S</b>
<b>35</b>	15	29			5			<b>736 85</b>	<b>736 82</b>	<b>736 88</b>
	15		39			5		<b>736 86</b>	<b>736 83</b>	<b>736 89</b>
	15			49			5	<b>736 87</b>	<b>736 84</b>	<b>736 90</b>
	15			49			7.5	<b>736 87S</b>	<b>736 84S</b>	<b>736 90S</b>
<b>4</b>	15	39			5			<b>736 40</b>	<b>736 37</b>	<b>736 43</b>
	15		49			7.5		<b>736 41</b>	<b>736 38</b>	<b>736 44</b>
	15			59			7.5	<b>736 42</b>	<b>736 39</b>	<b>736 45</b>
	15			59			5	<b>736 42S</b>	<b>736 39S</b>	<b>736 45S</b>
<b>45</b>	15	49			5			<b>736 94</b>	<b>736 91</b>	<b>736 97</b>
	15		59			7.5		<b>736 95</b>	<b>736 92</b>	<b>736 98</b>
	15			69			7.5	<b>736 96</b>	<b>736 93</b>	<b>736 99</b>
	15			69			5	<b>736 96S</b>	<b>736 93S</b>	<b>736 99S</b>
<b>5</b>	20	69			5			<b>736 49</b>	<b>736 46</b>	<b>736 52</b>
	20		84			10		<b>736 50</b>	<b>736 47</b>	<b>736 53</b>
	20			99			10	<b>736 51</b>	<b>736 48</b>	<b>736 54</b>
	20			99			7.5	<b>736 51S</b>	<b>736 48S</b>	<b>736 54S</b>
<b>55</b>	20	110			5			<b>736 58</b>	<b>736 55</b>	<b>736 61</b>
	20		125			10		<b>736 59</b>	<b>736 56</b>	<b>736 62</b>
	20			140			10	<b>736 60</b>	<b>736 57</b>	<b>736 63</b>
	20			140			7.5	<b>736 60S</b>	<b>736 57S</b>	<b>736 63S</b>
<b>6</b>	20	140			5			<b>736 67</b>	<b>736 64</b>	<b>736 70</b>
	20		155			10		<b>736 68</b>	<b>736 65</b>	<b>736 71</b>
	20			170			10	<b>736 69</b>	<b>736 66</b>	<b>736 72</b>
	20			170			7.5	<b>736 69S</b>	<b>736 66S</b>	<b>736 72S</b>
<b>7</b>	20	180			5			<b>736 114</b>	<b>736 111</b>	<b>736 117</b>
	20		195			15		<b>736 115</b>	<b>736 112</b>	<b>736 118</b>
	20			210			20	<b>736 116</b>	<b>736 113</b>	<b>736 119</b>
<b>75</b>	20	230			5			<b>736 344</b>	<b>736 341</b>	<b>736 347</b>
	20		245			15		<b>736 345</b>	<b>736 342</b>	<b>736 348</b>
	20			260			20	<b>736 346</b>	<b>736 343</b>	<b>736 349</b>
<b>8</b>	20	270			10			<b>736 373</b>	<b>736 370</b>	<b>736 376</b>
	20		290			20		<b>736 374</b>	<b>736 371</b>	<b>736 377</b>
	20			310			30	<b>736 375</b>	<b>736 372</b>	<b>736 378</b>
<b>85</b>	30	320			10			<b>736 364</b>	<b>736 361</b>	<b>736 367</b>
	30		340			20		<b>736 365</b>	<b>736 362</b>	<b>736 368</b>
	30			360			30	<b>736 366</b>	<b>736 363</b>	<b>736 369</b>

■ Further clamping Ø of drive pins upon request.






## Drive Pins FSB / SB / FFB(H) · KV-HS

**cross serrated and coated for hard turning operation  
for torque transmission onto the workpiece  
for hard tooling**

### Type FSB / SB / FFB(H) · KV-HS



### Technical data – type FSB / SB / FFB(H) · KV-HS



for type FSB/SB/FFB(H)	clamping Ø			chisel length			cat. no.
	D1	D2	D3	l1	l2	l3	
<b>01</b>	8			1.5			<b>736 200</b>
		11			3		<b>736 201</b>
			17			6	<b>736 202</b>
<b>0</b>	6			1.5			<b>736 203</b>
		11			4		<b>736 204</b>
			19			8	<b>736 205</b>
<b>1</b>	13			1.5			<b>736 209</b>
		18			4		<b>736 210</b>
			26			8	<b>736 211</b>
<b>11</b>	11			1.5			<b>736 206</b>
		14			3		<b>736 207</b>
			20			6	<b>736 208</b>
<b>2</b>	26			5			<b>736 212</b>
		31			7.5		<b>736 213</b>
			36			10	<b>736 214</b>
<b>3</b>	34			5			<b>736 215</b>
		39			7.5		<b>736 216</b>
			44			10	<b>736 217</b>
<b>35</b>	29			5			<b>736 218</b>
		39			10		<b>736 219</b>
			49			15	<b>736 220</b>
<b>4</b>	39			5			<b>736 221</b>
		49			10		<b>736 222</b>
			59			15	<b>736 223</b>
<b>45</b>	49			5			<b>736 224</b>
		59			10		<b>736 225</b>
			69			15	<b>736 226</b>
<b>5</b>	69			5			<b>736 227</b>
		84			12.5		<b>736 228</b>
			99			20	<b>736 229</b>
<b>55</b>	110			5			<b>736 230</b>
		125			12.5		<b>736 231</b>
			140			20	<b>736 232</b>
<b>6</b>	140			5			<b>736 233</b>
		155			12.5		<b>736 234</b>
			170			20	<b>736 235</b>

■ Further clamping Ø of drive pins upon request.




# Drive Pins FSB / SB / FFB(H) · FV Diamond




**serrated and diamond embedded**  
**for torque transmission onto the workpiece**  
**for hard tooling**

for higher friction coefficient and higher tool life of drive pin

Type FSB / SB / FFB / FFBH · FV diamond



Technical data – type FSB / SB / FFB / FFBH · FV diamond



for type FSB/SB/FFB(H)	clamping Ø			chisel length			cat. no.
	D1	D2	D3	l1	l2	l3	
<b>01</b>	8			1.5			<b>736 400</b>
		11			3		<b>736 401</b>
			17			6	<b>736 402</b>
<b>0</b>	6			1.5			<b>736 403</b>
		11			4		<b>736 404</b>
			19			8	<b>736 405</b>
<b>1</b>	13			1.5			<b>736 409</b>
		18			4		<b>736 410</b>
			26			8	<b>736 411</b>
<b>11</b>	11			1.5			<b>736 406</b>
		14			3		<b>736 407</b>
			20			6	<b>736 408</b>
<b>2</b>	26			5			<b>736 412</b>
		31			7.5		<b>736 413</b>
			36			10	<b>736 414</b>
<b>3</b>	34			5			<b>736 415</b>
		39			7.5		<b>736 416</b>
			44			10	<b>736 417</b>
<b>35</b>	29			5			<b>736 418</b>
		39			10		<b>736 419</b>
			49			15	<b>736 420</b>
<b>4</b>	39			5			<b>736 421</b>
		49			10		<b>736 422</b>
			59			15	<b>736 423</b>
<b>45</b>	49			5			<b>736 424</b>
		59			10		<b>736 425</b>
			69			15	<b>736 426</b>
<b>5</b>	69			5			<b>736 427</b>
		84			12.5		<b>736 428</b>
			99			20	<b>736 429</b>
<b>55</b>	110			5			<b>736 430</b>
		125			12.5		<b>736 431</b>
			140			20	<b>736 432</b>
<b>6</b>	140			5			<b>736 433</b>
		155			12.5		<b>736 434</b>
			170			20	<b>736 435</b>

■ Further clamping Ø of drive pins upon request.



## Drive Pins FSB / SB / FFB(H) · Chisel Carbide

**full carbide / carbide inserts**  
**for torque transmission onto the workpiece**  
**for tooling of high-tensile-strength materials**

### Type **FSB / SB / FFB(H)** · chisel carbide

model B / SR



#### MODEL A



#### MODEL B



### Technical data – type **FSB / SB / FFB(H)** · chisel carbide

type 01 - 3 made of full carbide, model A

type 35 - 6 with carbide inserts, model B



**MODEL A****TYPE CHISEL SL**for tooling  
direction M4**TYPE CHISEL SR**for tooling  
direction M3**TYPE CHISEL NV**for tooling  
direction M4 and M3

for type FSB / SB / FFB(H)	clamping Ø D3	length l3	cat. no.	cat. no.	cat. no.
<b>01</b>	17	6	<b>736 500</b>	<b>736 518</b>	<b>736 536</b>
<b>0</b>	19	8	<b>736 501</b>	<b>736 519</b>	<b>736 537</b>
<b>1</b>	26	8	<b>736 502</b>	<b>736 520</b>	<b>736 538</b>
<b>11</b>	20	6	<b>736 503</b>	<b>736 521</b>	<b>736 539</b>
<b>2</b>	36	10	<b>736 504</b>	<b>736 522</b>	<b>736 540</b>
<b>3</b>	44	10	<b>736 505</b>	<b>736 523</b>	<b>736 541</b>

**MODEL B**

for type FSB / SB / FFB(H)	clamping Ø D1 D3	length l3	cat. no.	cat. no.
<b>35</b>	34	6	<b>736 506</b>	<b>736 524</b>
	46	6	<b>736 507</b>	<b>736 525</b>
<b>4</b>	44	6	<b>736 508</b>	<b>736 526</b>
	56	6	<b>736 509</b>	<b>736 527</b>
<b>45</b>	54	6	<b>736 510</b>	<b>736 528</b>
	66	6	<b>736 511</b>	<b>736 529</b>
<b>5</b>	75	6	<b>736 512</b>	<b>736 530</b>
	95	6	<b>736 513</b>	<b>736 531</b>
<b>55</b>	116	6	<b>736 514</b>	<b>736 532</b>
	136	6	<b>736 515</b>	<b>736 533</b>
<b>6</b>	146	6	<b>736 516</b>	<b>736 534</b>
	166	6	<b>736 517</b>	<b>736 535</b>

- Drive Pins are supplied with carbide insert.
- Further clamping-Ø of drive pins upon request.

**Changeable inserts for type 35 - 6, model B**

changeable parts	cat. no.
carbide insert	<b>736 550</b>
set screw for fastening of carbide insert	<b>736 551</b>




## Center Pins FSB / SB

for face drivers FSB / SB with movable center pin

### Type FSB / SB · center pin




### Technical data - type FSB / SB · center pin



center body type FSB / SB 01 / 0



center body type FSB / SB 01 / 0



for type FSB / SB	d1	center Ø	d2	l	cat. no.
<b>01</b>	22	0 - 5	6	52	<b>735 101</b>
<b>0</b>	22	0 - 3	8	52	<b>735 01</b>
<b>11</b>	6	0 - 6	-	53	<b>735 11</b>
<b>1</b>	8	0 - 8	-	53	<b>735 02</b>
<b>2</b>	14	2 - 14	-	47	<b>735 03</b>
<b>3</b>	18	2 - 18	-	51	<b>735 04</b>
<b>35</b>	14	2 - 14	-	47	<b>735 09</b>
<b>4</b>	24	3 - 24	-	70	<b>735 05</b>
<b>45</b>	28	3 - 28	-	74	<b>735 10</b>
<b>5</b>	35	6 - 35	-	96	<b>735 06</b>
<b>55</b>	35	6 - 35	-	96	<b>735 08</b>
<b>6</b>	35	6 - 35	-	96	<b>735 07</b>
<b>7</b>	50	25 - 48	-	100	<b>735 301</b>
<b>75</b>	50	25 - 48	-	100	<b>735 401</b>
<b>8</b>	80	30 - 76	-	135	<b>735 601</b>
<b>85</b>	80	30 - 76	-	135	<b>735 501</b>

■ Further center pins for other center holes upon request.

# Center Pins FFB / FFBH


for face drivers FFB / FFBH with fixed center pin

Type FFB / FFBH · tool steel or carbide

Technical data - type FFB / FFBH · tool steel or carbide




**HM** with carbide insert



A overhang dimension of face driver to centre d8 (see page 20 - 21)

center body type FFB / FFBH 01 / 0

center body type FFB / FFBH 01 / 0



**TYPE TOOL STEEL**

**HM TYPE CARBIDE**

for type FFB / FFBH	d1	d2	d4	center Ø	d8	cat. no.
<b>01</b>	5	6	48	1 - 5	3.5	<b>734 01</b>
<b>0</b>	3	8	48	1 - 3	3	<b>734 101</b>
<b>11</b>	7.8	-	6	2 - 6.5	4.25	<b>734 11</b>
<b>1</b>	9.8	-	8	4 - 8.5	6.25	<b>734 02</b>
<b>2</b>	10	-	14	4 - 9	6.5	<b>734 03</b>
<b>3</b>	12	-	18	6 - 11	8.5	<b>734 04</b>
<b>35</b>	10	-	14	4 - 9	6.5	<b>734 12</b>
<b>4</b>	16	-	20	10 - 15	12.5	<b>734 05</b>
<b>45</b>	16	-	28	10 - 15	12.5	<b>734 06</b>
<b>5</b>	16	-	35	10 - 15	12.5	<b>734 07</b>
<b>55</b>	16	-	35	10 - 15	12.5	<b>734 08</b>
<b>6</b>	16	-	35	10 - 15	12.5	<b>734 09</b>

cat. no.
<b>734 43</b>
<b>734 44</b>
<b>734 33</b>
<b>734 34</b>
<b>734 35</b>
<b>734 36</b>
<b>734 37</b>
<b>734 38</b>
<b>734 39</b>
<b>734 40</b>
<b>734 41</b>
<b>734 42</b>

Further center pins for other center holes upon request.



## Face driver FSBR / SBR

### with drive pins and movable center body for soft workpieces with high true running accuracy

The entire surface of the workpiece can be tooled and finished by clamping with a maximum of torque transmission. NEIDLEIN face drivers of type FSBR / SBR are mechanical clamping systems which are suited **for turning (for grinding operation upon request)**.

Face drivers of type FSBR/SBR are power-operated by the thrust of the tailstock. Workpieces are clamped centrally using a movable center body. This way different centerings can be adjusted thus ensuring a constant datum-point at the end face of the workpieces.

#### Type FSBR with flange retainer

Type FSBR is mounted onto the machine spindle nose using a flange adapter.



#### Type SBR with MK- or cylindrical retainer


Type SBR with taper shank and extracting nut for fast mounting into the machine spindle.



#### NEIDLEIN face drivers FSBR / SBR with movable center body ensure:

- run-out deviation in the process 0.01-0.015 mm
- high process reliability at small workpieces
- datum-point at the end face of the workpiece  
stable datum-point in case of different centerings
- secured drive pins and center body
- clamping force is triggered by tailstock
- fixed center pin / fixed datum-point in clamped state
- compensating driving devices / ideal clamping of the workpiece
- simple handling

### Technical data – type FSBR face driver




type FSBR	d	d1	center Ø	d3	d5	d6	l1	l2	drive pin	fixing screw		clamping-Ø			max. workpiece weight [kg] *	cat. no.
										type	pcs	D1	D2	D3		
<b>01</b>	60	32	0 - 5	160	25	133.4	115	80	3	M12	3	7	11	17	8	<b>730 30</b>
<b>0</b>	60	32	0 - 3	160	25	133.4	115	80	3	M12	3	5	9	15	10	<b>730 31</b>

\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7

- All face drivers are supplied without drive pins. (drive pins see page 34)
- The center body is already installed.
- Mounting elements for face drivers see page 104 - 109.

### Technical data – type SBR face driver



type SBR	MK	d	d1	center Ø	d3	l1	l2	l3	l4	drive pin	clamping-Ø			max. workpiece weight [kg] *	cat. no.
											D1	D2	D3		
<b>01</b>	3	60	32	0 - 5	M28 x 1.5	113	61	16	35	3	7	11	17	8	<b>720 30</b>
	4	60	32	0 - 5	M35 x 1.5	104	74	17.5	37	3	7	11	17	8	<b>720 31</b>
	5	60	32	0 - 5	M48 x 1.5	104	97	19.5	37	3	7	11	17	8	<b>720 32</b>
<b>0</b>	3	60	32	0 - 3	M28 x 1.5	113	61	16	35	3	5	9	15	10	<b>720 35</b>
	4	60	32	0 - 3	M35 x 1.5	104	74	17.5	37	3	5	9	15	10	<b>720 36</b>
	5	60	32	0 - 3	M48 x 1.5	104	97	19.5	37	3	5	9	15	10	<b>720 37</b>

\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7

- Face driver with cylindrical shaft upon request.
- All face drivers are supplied without drive pins. (drive pins see page 34)
- The center body is already installed.
- Reducing sleeves for face drivers see page 112 - 113.




## Drive Pins FSBR / SBR · Chisel SL / SR

for torque transmission onto the workpiece for soft / green tooling

For soft workpieces we apply drive pins made of hardened HSS comprising a chisel. They are characterized by high wear-resistance as well as maximum torque transmission.

### Type FSBR / SBR Chisel SL/SR



SL

SR

### Technical data - type FSBR / SBR drive pins

Form A




Form B



Form C



view from tailstock onto the face driver



for type	for clamping	model	l	TYPE CHISEL SL DIRECTION M4 cat. no.	TYPE CHISEL SR DIRECTION M3 cat. no.
FSBR SBR	D3	A	2	<b>736 662</b>	<b>736 665</b>
FSBR SBR	D2	B	2	<b>736 661</b>	<b>736 664</b>
FSBR SBR	D1	C	2	<b>736 660</b>	<b>736 663</b>

- Clamping diameter D1, D2, D3 see page 33.
- Further clamping  $\varnothing$  of drive pins upon request.


## Center body FSBR / SBR

for face drivers FSBR / SBR with movable center pin

### Type FSBR / SBR



### Technical data - type FSBR / SBR center body



for type FSBR / SBR	d1	center Ø	d2	l	cat. no.
<b>01</b>	32	0 - 5	6	72	<b>735 20</b>
<b>0</b>	32	0 - 3	6	72	<b>735 21</b>



## Face Drivers FSP / FSPB / SP

### with drive disk and movable center pin

The entire surface of the workpiece can be tooled and finished by clamping with a maximum of torque transmission.

NEIDLEIN face drivers of type FSP / FSPB / SP with drive disks are mechanical clamping systems which are suited **for soft / green as well as heavy tooling**. In application, they feature maximum flexibility and high robustness.

These face drivers are power-operated by the thrust of the tailstock. Workpieces are clamped centrally using a movable center pin. This way different centerings can be adjusted, thus ensuring a constant datum-point at the face end of the workpiece.

#### Type FSP with flange retainer for screw connection

Type FSP is mounted onto the machine spindle nose using a flange adapter.



#### Type FSPB with flange retainer for jaw clamping

Type FSPB is directly clamped with the chuck using soft jaws.



#### Type SP with MK retainer

Type SP with taper shank and extracting nut for fast mounting into the machine spindle.



**NEIDLEIN face drivers FSP / FSPB / SP ensure:**

- a maximum of torque transmission, thus achieving high metal removing rates
- datum-point at the face end of the workpiece, stable datum-point in case of different centerings
- compensating drive disk for uneven face sides
- high flexibility in the application, wide range of clamping diameters
- fixed center pin in clamped condition  
» fixed clamping point
- run-out deviation in the process 0.015 - 0.02 mm
- adjustable spring force (depending on the weight of the workpiece)
- low setup costs due to fast change of drive disks and center pins
- cost efficient exchange of parts that are in contact with the workpiece (changeable carbide inserts)

**Clamping principle**

The center pin located on the side of the tailstock pushes the workpiece against the movable center pin of the face driver. The center pin will draw back until the surface of the workpiece bears against the drive disk.


In this state the clamping bolt is clamped over the the power flow, in order to ensure a fixed datum-point throughout the entire tooling process.

The drive disk is "floatingly" suspended, thus balancing out possible planarity defects of the contact surface of the workpiece.


The entire surface of the workpiece can now be tooled in one single clamping. See page 40 for data of achievable removal of material and the tailstock thrust requested.

You will find various sizes of face drivers with appropriate standard drive disks and center pins on the following pages.

In case you need special dimensions, we will be glad to design clamping devices suitable for your workpieces.

**Type FSP with flange retainer**

### Technical data – type FSP face driver · for screw connection




l\* lengths of drive disk see page 42 - 43

type	D	D1	d3	d5	d6	l1	l2	fixing screws	max. workpiece weight [kg] *	cat. no.
FSP								type pcs		
<b>1</b>	56	9 - 31	160	26	133.4	67	83	M12 3	25	<b>631 99</b>
<b>3</b>	70	14 - 59	160	26	133.4	67	104	M12 3	90	<b>632 01</b>
<b>4</b>	90	31 - 125	160	35	133.4	70	110	M12 3	250	<b>632 03</b>
<b>55</b>	182	84 - 290	220	45	171.4	76	170	M16 3	1500	<b>632 05</b>

- All face drivers are provided without drive disk and without center pin. (changeable parts see page 42 - 45)
- Mounting elements for face drivers see page 104 - 97.

\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7

### Technical data – type FSPB face driver · for jaw clamping




l\* lengths of drive disk see page 42 - 43

type	D	D1	d3	d5	l1	l2	max. workpiece weight [kg] *	cat. no.
FSPB								
<b>1</b>	56	9 - 31	130	26	73	77	25	<b>632 00</b>
<b>3</b>	70	14 - 59	130	26	73	98	90	<b>632 02</b>
<b>4</b>	90	31 - 125	130	35	76	104	250	<b>632 04</b>

- All face drivers are provided without drive disk and without center pin. (changeable parts see page 42 - 45)

\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7

**Technical data – type SP face driver**

$l^*$  length of drive disk see page 42 - 43

type SP	MK	D	D1	d3	l1	l2	l3	max. workpiece weight [kg] *	cat. no.
<b>1</b>	<b>3</b>	56	9 - 31	M28 x 1.5	60	56	16	25	<b>632 57</b>
	<b>4</b>	56	9 - 31	M35 x 1.5	61	74	18	25	<b>632 58</b>
	<b>5</b>	56	9 - 31	M48 x 1.5	63	97	20	25	<b>632 59</b>
<b>3</b>	<b>4</b>	70	14 - 59	M35 x 1.5	78	74	17.5	90	<b>632 60</b>
	<b>5</b>	70	14 - 59	M48 x 1.5	78	97	19.5	90	<b>632 61</b>
<b>4</b>	<b>5</b>	90	31 - 125	M48 x 1.5	89	97	19.5	250	<b>632 62</b>
	<b>6</b>	90	31 - 125	M70 x 1.5	87	134	22	250	<b>632 63</b>


\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7

- All face drivers are provided without drive disk and without center pin. (changeable parts see page 42 - 45)
- Reducing sleeves for face drivers see page 112 - 113.
- Face driver with cylindrical shank upon request.

## Face Drivers FSP / FSPB / SP · Calculations

### max. chip cross section of metal removing

**PRINCIPLE:** The tailstock force pushes the workpiece against the movable center pin of the face driver. The center pin will draw back until the surface of the workpiece bears against the drive dik.



#### ■ tailstock force $F_R$ :

The force onto the face driver required for metal removing is calculated on the basis of the empirical formula:

$$F_R = [(q_{max} \times 1000 \times \frac{D}{d}) + 1000] \times m$$

$F_R$	[N]	tailstock force
$q_{max}$	[mm <sup>2</sup> ]	maximum of chip cross section for metal removing
D	[mm]	cutting diameter
d	[mm]	clamping diameter
m	[-]	material factor (see adjustment-chart below)
a	[mm]	depth of cut
f	[mm/1]	feed rate

#### NOTE FSPV / FSPBV / SPV:

When using the face driver type SPV/FSPV/FSPBV, the calculated machining chip cross section  $q_{max}$  must be reduced by 20%.

#### ■ maximum chip cross section $q_{max}$ :

At a given tailstock force, maximum chip cross section is calculated as follows:

$$q_{max} = \frac{\frac{F_R}{m} - 1000}{1000 \times \frac{D}{d}}$$

#### ■ depth of cut a:

$$a = \frac{q_{max}}{f}$$

**EXPLANATORY NOTES:** The calculations refer to tooling against the face driver. In case of tooling against tailstock the calculated chip cross section is reduced by approx. 40%. The first chip, however, should always be machined toward the face driver, in order to achieve an ideal penetration of the carbide inserts. The ratio  $D/d$  should not exceed 2, otherwise it would work inefficiently.

#### Material factor m adjustment chart:

material factor m	1.4	1.2	1.1	1.0	0.8
Rm [N / mm <sup>2</sup> ]	1000	800	700	600	400
examples	42CrMo4	16MnCr5 25CrMo4	C 15E (Ck 15) C 45E (Ck 45)	S355J0 35S20	S235J0

## Chisel load of the carbide inserts

Keep the chisel load within the following range:  
250 - 350 N per mm chisel length

### ■ the chisel load is calculated as follows:

$$BS = \frac{F_R}{n \times s}$$

BS [N/mm] chisel load  
F<sub>R</sub> [N] tailstock force

**EXEMPLIFICATION:** turning with FSP 3 facé driver, 5 carbide inserts, respective length of chisel 4 mm, tailstock force 6000 N

$$BS = \frac{6000 \text{ N}}{5 \times 4 \text{ mm}} = 300 \frac{\text{N}}{\text{mm}}$$

n [-] number of carbide inserts  
s [mm] chisel length

### CALCULATION EXAMPLE for type FSP / FSPB / SP

#### Specific data of machine and workpiece:

maximum tailstock force: 6000 N  
material of the workpiece: 16MnCr5  
diameter of the workpiece,  
side of face driver: Ø 30 mm  
turning diameter: Ø 50 mm

#### Selection of face driver:

face driver FSP 3 / clamping Ø 26 mm  
5 carbide inserts, respective length of chisel 4 mm

#### ■ tailstock force F<sub>R</sub>:

In order to ensure sufficient entrainment (see chisel load of carbide inserts) a tailstock force of approx. 6000 N has to be supplied.

$$BS = \frac{F_S}{n \times s}$$

$$F_R = 300 \frac{\text{N}}{\text{mm}} \times 5 \times 4 \text{ mm} = 6000 \text{ N}$$

#### Determination of material factor m:

as per adjustment chart material factor: m (16MnCr5) = 1.2

#### ■ maximum chip cross section q<sub>max</sub>:

The maximum chip cross section (at the ultimate turning-Ø) is calculated as follows:

$$q_{max} = \frac{\frac{6000 \text{ N}}{1.2} - 1000}{1000 \times \frac{50 \text{ mm}}{26 \text{ mm}}} = 2.08 \text{ mm}^2$$

**EXPLANATORY NOTES:** This calculation refers to tooling against the face driver. The calculated chip cross section refers to the ultimate turning diameter. In case of further tooling towards the axis of rotation of the workpiece, even larger chip cross sections can be achieved (» formula), commensurate with turning diameter.




## Drive Disks FSP / FSPB / SP · Chisel NV / SL / SR

**with changeable carbide inserts or made of tool steel  
for torque transmission onto the workpiece  
for the purpose of soft/green tooling**

Type FSP / FSPB / SP · chisel NV / SL / SR




view from tailstock onto the face driver



SL (carbide)




NV (tool steel)



SR (carbide)

Technical data - type FSP / FSPB / SP · chisel NV / SL / SR



**TYPE CHISEL NV**  
for tooling  
direction M4 and M3

for type FSP / FSPB / SP	D1	D2	D3	l	l1	W	number of chisels	S	F <sub>R</sub> (N)	cat. no.
<b>1</b>	9	9	42	32	5	45°	4 (tool steel)	1.5	1800	<b>738 15</b>
	11	11	42	32	5	45°	4 (tool steel)	2.0	2400	<b>738 16</b>
	14	14	42	32	5	35°	4 (tool steel)	2.0	2400	<b>738 17</b>
	18	18	42	32	5	35°	3 (tool steel)	3.0	2700	<b>738 18</b>
	22	22	42	29	5	30°	3 (tool steel)	3.5	3200	<b>738 19</b>
	26	26	42	29	5	30°	3 (tool steel)	4.0	3600	<b>738 20</b>
	31	31	42	29	5	30°	3 (tool steel)	5.0	4500	<b>738 21</b>
<b>3</b>	14	14	60	57	5	35°	6 (tool steel)	2.5	4500	<b>738 02</b>
	18	18	60	57	5	30°	6 (tool steel)	3	5400	<b>738 03</b>

**TYPE CHISEL SL**  
for tooling  
direction M4

**TYPE CHISEL SR**  
for tooling  
direction M3

for type FSP / FSPB / SP	D1	D2	D3	l	l1	W	number of chisels	S	F <sub>R</sub> (N)	cat. no.	cat. no.
<b>3</b>	22	24	60	57	9	30°	5 (carbide)	4	6000	<b>738 04</b>	<b>738 24</b>
	26	28	60	53	9	30°	5 (carbide)	4	6000	<b>738 05</b>	<b>738 25</b>
	31	33	60	48	9	30°	6 (carbide)	4	7200	<b>738 06</b>	<b>738 26</b>
	36	37	60	48	9	30°	5 (carbide)	6	9000	<b>738 07</b>	<b>738 27</b>
	39	40	60	48	9	30°	5 (carbide)	6	9000	<b>738 08</b>	<b>738 28</b>
	44	45	60	48	9	30°	6 (carbide)	6	10800	<b>738 09</b>	<b>738 29</b>
	49	50	60	48	9	30°	6 (carbide)	6	10800	<b>738 10</b>	<b>738 30</b>
59	60	60	48			6 (carbide)	6	10800	<b>738 11</b>	<b>738 31</b>	
<b>4</b>	31	33	75	50	9	45°	6 (carbide)	4	7200	<b>738 40</b>	<b>738 60</b>
	36	38	75	50	9	38°	6 (carbide)	4	7200	<b>738 41</b>	<b>738 61</b>
	39	41	75	45	9	45°	6 (carbide)	4	7200	<b>738 42</b>	<b>738 62</b>
	44	45	75	45	9	38°	6 (carbide)	6	10800	<b>738 43</b>	<b>738 63</b>
	49	50	75	45	9	30°	6 (carbide)	6	10800	<b>738 44</b>	<b>738 64</b>
	59	60	75	45	9	30°	6 (carbide)	6	10800	<b>738 45</b>	<b>738 65</b>
	69	70	75	45	9	30°	6 (carbide)	6	10800	<b>738 46</b>	<b>738 66</b>
	84	85	75	45	-	-	6 (carbide)	6	10800	<b>738 47</b>	<b>738 67</b>
	99	100	75	45	-	-	6 (carbide)	6	10800	<b>738 48</b>	<b>738 68</b>
	110	111	75	45	-	-	7 (carbide)	6	12600	<b>738 49</b>	<b>738 69</b>
125	126	75	45	-	-	7 (carbide)	6	12600	<b>738 50</b>	<b>738 70</b>	
<b>55</b>	84	85	160	69	9	45°	6 (carbide)	6	10800	<b>738 80</b>	<b>739 00</b>
	99	100	160	69	9	38°	6 (carbide)	6	10800	<b>738 81</b>	<b>739 01</b>
	110	111	160	69	9	30°	7 (carbide)	6	12600	<b>738 82</b>	<b>739 02</b>
	125	126	160	69	9	30°	7 (carbide)	6	12600	<b>738 83</b>	<b>739 03</b>
	140	141	160	69	9	30°	8 (carbide)	6	14400	<b>738 84</b>	<b>739 04</b>
	155	156	160	69	9	30°	8 (carbide)	6	14400	<b>738 85</b>	<b>739 05</b>
	170	171	160	69	-	-	8 (carbide)	6	14400	<b>738 86</b>	<b>739 06</b>
	195	196	160	69	-	-	8 (carbide)	6	14400	<b>738 87</b>	<b>739 07</b>
	230	231	160	69	-	-	7 (carbide)	10	21000	<b>738 88</b>	<b>739 08</b>
	260	261	160	69	-	-	8 (carbide)	10	24000	<b>738 89</b>	<b>739 09</b>
290	291	160	69	-	-	8 (carbide)	10	24000	<b>738 90</b>	<b>739 10</b>	

- All drive disks of type carbide will be provided with the respective carbide inserts.
- Additional clamping diameters of drive disks upon request.

## Changeable inserts for drive disks **FSP / FSPB / SP**

### Technical data - changeable inserts · drive disks **FSP / FSPB / SP**



### CARBIDE INSERTS

for type FSP / FSPB / SP	machining direction	S	cat. no.
<b>3</b>	SL/SR	<b>4</b>	<b>736 548</b>
<b>4</b>			
<b>3</b>	SL/SR	<b>6</b>	<b>736 550</b>
<b>4</b>			
<b>55</b>			
<b>55</b>	SL/SR	<b>10</b>	<b>736 552</b>

### SET SCREW



for fixing carbide inserts

for carbide inserts with S =	thread	cat. no.
<b>4</b>	M4	<b>736 549</b>
<b>6</b>	M5	<b>736 551</b>
<b>10</b>	M5	

## Removal lever for drive disks **FSP / FSPB / SP**

In order to easily and quickly change the drive disks, the removal lever shown at right may be used.

### Technical data - removal lever



The removal lever is placed laterally and easily inserted. Thus the drive disk can be loosened through a tilting movement.

for type FSP / FSPB / SP	D1	D2	l1	cat. no.
<b>1</b>	33	60	260	<b>632 19</b>
<b>3</b>	44.5	80	262	<b>632 20</b>
<b>4</b>	58.5	96	272	<b>632 21</b>
<b>55</b>	130.5	190	310	<b>632 22</b>

### INFORMATION FOR CHANGING THE DRIVE DISKS

In order to exclude the risk of injury, we recommend to use suitable gloves for changing drive disks. We can provide a mounting aid upon request.

The drive disks can be pulled off head side. We recommend the use of a removal lever in order to reduce the force required and provide increased safety.


## Center Pins FSP / FSPB / SP

for face drivers **FSP / FSPB / SP** with movable center pin

Type **FSP / FSPB / SP** · center pin



Technical data – type **FSP / FSPB / SP** · center pin



for type FSP / FSPB / SP	d1	center Ø	clamping Ø	d2	l	cat. no.
<b>1</b>	8	2 - 4.5	9	4.5	44.5	<b>735 25</b>
		2 - 5.5	11	5.5	44.5	<b>735 26</b>
		3 - 8	14 - 18	-	49	<b>735 27</b>
		3 - 8	22 - 31	-	46	<b>735 28</b>
<b>3</b>	14	3 - 7	14	7	81.5	<b>735 52</b>
		3 - 10	18	10	84.5	<b>735 53</b>
		3 - 11	22	11	85.5	<b>735 54</b>
		3 - 10	26	-	81	<b>735 55</b>
		3 - 10	31 - 59	-	76	<b>735 56</b>
		7 - 14	31 - 59	-	78.5	<b>735 57</b>
<b>4</b>	20	3 - 13	31 - 36	-	80.5	<b>735 70</b>
		3 - 13	39 - 125	-	75.5	<b>735 71</b>
		10 - 20	39 - 125	-	80	<b>735 72</b>
<b>55</b>	35	10 - 20	84 - 290	28	113	<b>735 80</b>
		18 - 28	84 - 290	-	118	<b>735 81</b>
		25 - 35	84 - 290	-	123	<b>735 82</b>

■ Further center pins for other center holes upon request.

## Changeable Parts OX for Tensile Samples OBXS / OBX / OCX

### in combination with the face driver types **FSP1 / FSPB1 / SP1** (page 36 - 41)

In combination with the face driver types FSP1 / FSPB1 / SP1, the machining of tensile samples can be realized in one clamping operation, by simply mounting an OX retainer, an OX drive disk and an OX center pin.

With different changeable OX retainers, the robust OX drive disks of sizes OBXS, OBX and OCX can be used.

These face drivers are power-operated by the thrust of the tailstock. Workpieces are clamped centrally using a movable center pin.

This way different centerings can be adjusted, thus ensuring a constant datum-point at the face end of the work-piece.

**OX** · retainer




**OX** · drive disk



#### NEIDLEIN face drivers **FSP1 / FSPB1 / SP1** combined with OX changeable parts ensure:

- robust and changeable OX drive disks
- high cutting performance even with low tailstock force
- compensating OX retainer for uneven face sides on the tensile samples
- easy setup of the OX retainer
- easy setup of the OBXS / OBX / OCX drive disks
- wide range of clamping diameters
- run-out deviation in the process 0.02 - 0.1 mm


**Type OBXS / OBX / OCX · tensile samples manufacturing**



## OX retainer

for retaining the drive disks **OBX / OBXS / OCX**

**Technical data – type OBXS / OBX / OCX · retainer**




type	d1	D2	D3	L	cat. no.
<b>OBXS / OBX</b>	12	24	42	28	<b>738 22</b>
<b>OCX</b>	19	34	42	21	<b>738 23</b>


## Drive Disks **OBXS / OBX / OCX**

for torque transmission onto the workpiece when preparing tensile samples

### Technical data - type **OBXS / OBX / OCX** · drive disks



view from tailstock onto the face driver




type	machining direction	D	D4	D1	D2	D3	L	cat. no.
<b>OBXS</b>	SR	24	12	9			7	<b>717 01</b>
		24	12	14			7	<b>717 02</b>
		24	12		19		7	<b>717 03</b>
	SL	24	12	9			7	<b>717 04</b>
		24	12	14			7	<b>717 05</b>
		24	12		19		7	<b>717 06</b>
		24	12	9			7	<b>717 07</b>
	NV	24	12	14			7	<b>717 08</b>
		24	12		19		7	<b>717 09</b>
<b>OBX</b>	SR	24	12	14			7	<b>717 10</b>
		24	12	19			7	<b>717 11</b>
		24	12		24		7	<b>717 12</b>
	SL	24	12	14			7	<b>717 13</b>
		24	12	19			7	<b>717 14</b>
		24	12		24		7	<b>717 15</b>
		24	12	14			7	<b>717 16</b>
	NV	24	12	19			7	<b>717 17</b>
		24	12		24		7	<b>717 18</b>
<b>OCX</b>	SR	34	19	19			9	<b>717 19</b>
		34	19	27			9	<b>717 20</b>
		34	19		34		9	<b>717 21</b>
	SL	34	19	19			9	<b>717 22</b>
		34	19	27			9	<b>717 23</b>
		34	19		34		9	<b>717 24</b>
		34	19	19			9	<b>717 25</b>
	NV	34	19	27			9	<b>717 26</b>
		34	19		34		9	<b>717 27</b>

## Center Pins OX

### Type OX · center pin



### Technical data - type OX · center pin



type	d1	center Ø	d2	l	cat. no.
<b>OBXS</b>	8	2-5	5	48	<b>735 30</b>
<b>OBX</b>	8	2-6	6	49	<b>735 29</b>
<b>OCX</b>	8	2-8	-	46	<b>735 28</b>



## Face Drivers FSPV / FSPBV / SPV

### with drive disk and movable center pin

The entire surface of the workpiece can be tooled and finished by clamping with a maximum of torque transmission.

NEIDLEIN face drivers of type FSPV / FSPBV / SPV with drive disks are mechanical clamping systems for **turn-milling processes**, which are suited for soft / green as well as heavy tooling. In application, they feature maximum flexibility and high robustness.

These face drivers are power-operated by the thrust of the tailstock. Workpieces are clamped centrally using a movable center pin. This way different centerings can be adjusted, thus ensuring a constant datum-point at the face end of the workpiece.

#### Type FSPV with flange retainer

Type FSPV is mounted onto the machine spindle nose using a flange adapter.



#### Type FSPBV with flange retainer for jaw clamping

Type FSPBV is directly clamped with the chuck using soft jaws.



#### Type SPV with taper shank

Type SPV with taper shank and extracting nut for fast mounting into the machine spindle.



**NEIDLEIN face drivers FSPV / FSPBV / SPV ensure:**

- radial, almost backlash-free driving
- datum-point at the face end of the workpiece, stable datum-point in case of different centerings
- compensating drive disk for uneven face sides
- high flexibility in the application, wide range of clamping diameters
- run-out deviation in the process 0.015 - 0.02 mm
- adjustable spring force (depending on the weight of the workpiece)
- low setup costs due to fast change of drive disks and center pins
- cost efficient exchange of parts that are in contact with the workpiece (changeable carbide inserts)
- fixed center pin in clamped condition  
» fixed clamping point

**Clamping principle**

The center pin located on the side of the tailstock pushes the workpiece against the movable center pin of the face driver. The center pin will draw back until the surface of the workpiece bears against the drive disk.


In this state the clamping bolt is clamped over the power flow, in order to ensure a fixed datum-point throughout the entire tooling process.


The drive disk is "floatingly" suspended, thus balancing out possible planarity defects of the contact surface of the workpiece.

The entire surface of the workpiece can now be tooled in one single clamping. See page 41 for data of achievable removal of material and the tailstock thrust requested.

You will find various sizes of face drivers with appropriate standard drive disks and center pins on the following pages.

In case you need special dimensions, we will be glad to design clamping devices suitable for your workpieces.

**Type FSPV with flange retainer**


**Technical data – type FSPV face driver · for screw connection**


l\* lengths of drive disk see on page 54 - 55

type	D	D1	d3	d5	d6	l1	l2	fixing screws	max. workpiece weight [kg] *	cat. no.
FSPV								type pcs		
<b>1</b>	56	9 - 31	160	26	133.4	67	83	M12 3	25	<b>632 09</b>
<b>3</b>	70	14 - 59	160	26	133.4	67	104	M12 3	90	<b>632 11</b>
<b>4</b>	90	31 - 125	160	35	133.4	70	110	M12 3	250	<b>632 13</b>
<b>55</b>	182	84 - 290	220	45	171.4	76	170	M16 3	1500	<b>632 15</b>

■ All face drivers are provided without drive disk and without center pin. (drive disks at page 54 - 55, center pins see page 57)

\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7

**Technical data – type FSPBV face driver · for jaw clamping**



l\* lengths of drive disk see on page 54 - 55

type	D	D1	d3	d5	l1	l2	max. workpiece weight [kg] *	cat. no.
FSPBV								
<b>1</b>	56	9 - 31	130	26	73	77	25	<b>632 10</b>
<b>3</b>	70	14 - 59	130	26	73	98	90	<b>632 12</b>
<b>4</b>	90	31 - 125	130	35	76	104	250	<b>632 14</b>

■ All face drivers are provided without drive disk and without center pin. (drive disks at page 54 - 55, center pins see page 57)

\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7

**Technical data – type SPV face driver**



l\* lengths of drive disk see on page 54 - 55

type SPV	MK	D	D1	d3	l1	l2	l3	max. workpiece weight [kg] *	cat. no.
1	3	56	9 - 31	M28 x 1.5	60	56	16	25	<b>632 70</b>
	4	56	9 - 31	M35 x 1.5	61	74	18	25	<b>632 71</b>
	5	56	9 - 31	M48 x 1.5	63	97	20	25	<b>632 72</b>
3	4	70	14 - 59	M35 x 1.5	125	106	17.5	90	<b>632 65</b>
	5	70	14 - 59	M48 x 1.5	125	129	19.5	90	<b>632 66</b>
4	5	90	31 - 125	M48 x 1.5	134	132	19.5	250	<b>632 67</b>
	6	90	31 - 125	M70 x 1.5	134	169	22	250	<b>632 68</b>

- All face drivers are provided without drive disk and without center pin. (drive disks on page 54 - 55, center pins see page 57)
- Reducing sleeves for face drivers see page 112 - 113.

\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7




## Drive disks FSPV / FSPBV / SPV · Chisel NV

**with changeable carbide inserts or made of tool steel  
for torque transmission onto the workpiece  
for the purpose of soft / green tooling**

Type FSPV / FSPBV / SPV · Chisel NV



view from tailstock onto the face driver




NV (tool steel)

D1 = 9 - 31 · type 1  
D1 = 14 - 18 · type 3



NV (carbide)

### Technical data - type FSPV / FSPBV / SPV · chisel NV



**TYPE CHISEL NV**for tooling direction M4 and M3  
(tool steel)

for type FSPV / FSPBV / SPV	D1	D2	D3	l	l1	W	number of chisels	S	F <sub>R</sub> (N)	cat. no.
<b>1</b>	9	9	42	32	5	45°	4 (tool steel)	1.5	1800	<b>739 80</b>
	11	11	42	32	5	45°	4 (tool steel)	2.0	2400	<b>739 81</b>
	14	14	42	32	5	35°	4 (tool steel)	2.0	2400	<b>739 82</b>
	18	18	42	32	5	35°	3 (tool steel)	3.0	2700	<b>739 83</b>
	22	22	42	29	5	30°	3 (tool steel)	3.5	3200	<b>739 84</b>
	26	26	42	29	5	30°	3 (tool steel)	4.0	3600	<b>739 85</b>
	31	31	42	29	5	30°	3 (tool steel)	5.0	4500	<b>739 86</b>
<b>3</b>	14	14	60	57	5	35°	6 (tool steel)	2.5	4500	<b>739 22</b>
	18	18	60	57	5	30°	6 (tool steel)	3	5400	<b>739 23</b>

**TYPE CHISEL NV**for tooling direction M4 and M3  
(carbide)

for type FSPV / FSPBV / SPV	D1	D2	D3	l	l1	W	number of chisels	S	F <sub>R</sub> (N)	cat. no.
<b>3</b>	22	24	60	57	9	30°	5 (carbide)	4	6000	<b>739 24</b>
	26	28	60	53	9	30°	5 (carbide)	4	6000	<b>739 25</b>
	31	33	60	48	9	30°	6 (carbide)	4	7200	<b>739 26</b>
	36	37	60	48	9	30°	5 (carbide)	6	9000	<b>739 27</b>
	39	40	60	48	9	30°	5 (carbide)	6	9000	<b>739 28</b>
	44	45	60	48	9	30°	6 (carbide)	6	10800	<b>739 29</b>
	49	50	60	48	9	30°	6 (carbide)	6	10800	<b>739 30</b>
	59	60	60	48	-	-	6 (carbide)	6	10800	<b>739 31</b>
<b>4</b>	31	33	75	50	9	45°	6 (carbide)	4	7200	<b>739 40</b>
	36	38	75	50	9	38°	6 (carbide)	4	7200	<b>739 41</b>
	39	41	75	45	9	45°	6 (carbide)	4	7200	<b>739 42</b>
	44	45	75	45	9	38°	6 (carbide)	6	10800	<b>739 43</b>
	49	50	75	45	9	30°	6 (carbide)	6	10800	<b>739 44</b>
	59	60	75	45	9	30°	6 (carbide)	6	10800	<b>739 45</b>
	69	70	75	45	9	30°	6 (carbide)	6	10800	<b>739 46</b>
	84	85	75	45	-	-	6 (carbide)	6	10800	<b>739 47</b>
	99	100	75	45	-	-	6 (carbide)	6	10800	<b>739 48</b>
	110	111	75	45	-	-	7 (carbide)	6	12600	<b>739 49</b>
	125	126	75	45	-	-	7 (carbide)	6	12600	<b>739 50</b>
<b>55</b>	84	85	160	69	9	45°	6 (carbide)	6	10800	<b>739 60</b>
	99	100	160	69	9	38°	6 (carbide)	6	10800	<b>739 61</b>
	110	111	160	69	9	30°	7 (carbide)	6	12600	<b>739 62</b>
	125	126	160	69	9	30°	7 (carbide)	6	12600	<b>739 63</b>
	140	141	160	69	9	30°	8 (carbide)	6	14400	<b>739 64</b>
	155	156	160	69	9	30°	8 (carbide)	6	14400	<b>739 65</b>
	170	171	160	69	-	-	8 (carbide)	6	14400	<b>739 66</b>
	195	196	160	69	-	-	8 (carbide)	6	14400	<b>739 67</b>
	230	231	160	69	-	-	7 (carbide)	10	21000	<b>739 68</b>
	260	261	160	69	-	-	8 (carbide)	10	24000	<b>739 69</b>
	290	291	160	69	-	-	8 (carbide)	10	24000	<b>739 70</b>

■ Additional clamping diameters of drive disks upon request.

## Changeable inserts for drive disks **FSP(V) / FSPB(V) / SP(V)**

### Technical data - changeable inserts · drive disks **FSPV / FSPBV / SPV**



### CARBIDE INSERTS

for type FSPV / FSPBV / SPV	machining direction	S	cat. no.
3	NV	4	736 558
4			
3	NV	6	736 560
4			
55			
55	NV	10	736 562

### SET SCREW



for fixing carbide inserts

for carbide inserts with S =	thread	cat. no.
4	M4	736 549
6	M5	736 551
10	M5	

## Removal lever for drive disks **FSP(V) / FSPB(V) / SP(V)**

In order to easily and quickly change the drive disks, the removal lever shown at right may be used.

### Technical data - removal lever



The removal lever is placed laterally and easily inserted. Thus the drive disk can be loosened through a tilting movement.

for type FSPV / FSPBV / SPV	D1	D2	l1	cat. no.
1	33	60	260	632 19
3	44.5	80	262	632 20
4	58.5	96	272	632 21
55	130.5	190	310	632 22

### INFORMATION FOR CHANGING THE DRIVE DISKS

In order to exclude the risk of injury, we recommend to use suitable gloves for changing drive disks. We can provide a mounting aid upon request.

The drive disks can be pulled off head side. We recommend the use of a removal lever in order to reduce the force required and provide increased safety.


## Center Pins FSP(V) / FSPB(V) / SP(V)

for face drivers **FSP(V) / FSPB(V) / SP(V)** with movable center pin

### Type FSP(V) / FSPB(V) / SP(V) · center pin



### Technical data - type FSP(V) / FSPB(V) / SP(V) · center pin



for type FSP(V) / FSPB(V) / SP(V)	d1	center Ø	clamping Ø	d2	l	cat. no.
<b>1</b>	8	2 - 4.5	9	4.5	44.5	<b>735 25</b>
		2 - 5.5	11	5.5	44.5	<b>735 26</b>
		3 - 8	14 - 18	-	49	<b>735 27</b>
		3 - 8	22 - 31	-	46	<b>735 28</b>
<b>3</b>	14	3 - 7	14	7	81.5	<b>735 52</b>
		3 - 10	18	10	84.5	<b>735 53</b>
		3 - 11	22	11	85.5	<b>735 54</b>
		3 - 10	26	-	81	<b>735 55</b>
		3 - 10	31 - 59	-	76	<b>735 56</b>
		7 - 14	31 - 59	-	78.5	<b>735 57</b>
<b>4</b>	20	3 - 13	31 - 36	-	80.5	<b>735 70</b>
		3 - 13	39 - 125	-	75.5	<b>735 71</b>
		10 - 20	39 - 125	-	80	<b>735 72</b>
<b>55</b>	35	10 - 20	84 - 290	28	113	<b>735 80</b>
		18 - 28	84 - 290	-	118	<b>735 81</b>
		25 - 35	84 - 290	-	123	<b>735 82</b>

■ Further center pins for other center holes upon request.

## Face Drivers FFP



### with drive disk and fixed center pin for high true run accuracy

The entire surface of the workpiece can be tooled and finished by clamping with a maximum of torque transmission.

NEIDLEIN face drivers of type FFP with drive disks are mechanical clamping systems which are suited **for turning as well as for hard turning operations and can also be used for grinding operations.**

Face drivers of the type FFP are power operated on the side of the machine spindle as well as the side of the tailstock. The workpieces are clamped centrally by the fixed center pin. This operation results in high true run accuracy.

#### Type FFP with flange retainer for screw connection

The face driver FFP is designed for a direct mounting onto a spindle nose. **DIN 702-1 (55028)**



#### NEIDLEIN face drivers FFP ensure:

- a maximum of torque transmission, thus achieving a high cutting performance
- datum-point location in the center of the workpiece ensures constant measures of length
- compensating drive disk for uneven face sides
- high flexibility in the application, wide range of clamping diameters
- run-out deviation in the process 0.005 - 0.015 mm
- low setup costs due to fast change of drive disks and center pins
- cost efficient exchange of parts that are in contact with the workpiece (changeable carbide inserts)
- suitable changeable parts depending on the hardness of the workpiece

## Clamping principle


The center pin located on the side of the tailstock pushes the workpiece against the fixed center pin of the face driver. The motion of the drive disk against the workpiece face side is initiated by the clamping cylinder mounted into the machine. The drive disk is "floatingly" suspended, thus balancing out possible planarity defects of the contact surface of the workpiece. The datum-point of workpieces on the machine is determined by the size of the center hole.


The entire surface of the workpiece can now be tooled in one single clamping. See page 61 for data of cutting performance and the clamping forces requested.

You will find various sizes of face drivers with appropriate standard drive disks and center pins on the following pages.

In case you need special dimensions, we will be glad to design clamping devices suitable for your workpiece.

### Type FFP with flange retainer



**Technical data – type FFP face driver - for screw connection**


l\* lengths of drive disk see  
page 62 - 63, 65

type	D	D1	d3	d4	d6	L1	fixing screws		short taper size	max. workpiece weight [kg] *	cat. no.
							type	pcs			
3	80	14 - 59	130	82.563	104.8	31	M12	3	5	90	<b>632 30</b>
	90	14 - 59	160	106.375	133.4	31	M12	3	6	90	<b>632 31</b>
4	90	31 - 125	160	106.375	133.4	31	M12	3	6	250	<b>632 32</b>
	100	31 - 125	220	139.719	171.4	39	M16	3	8	250	<b>632 33</b>


\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7

■ All face drivers are provided without drive disk and without center pin. (changeable parts see page 62 - 67)

## Face Drivers FFP · Calculations

### max. chip cross section of metal removing

**PRINCIPLE:** The tailstock force pushes the workpiece against the fixed center pin of the face driver. The drive disk is actuated by the clamping cylinder mounted into the machine.



#### ■ maximum chip cross section $q_{max}$ :

At a given force of clamping cylinder, the maximum chip cross section is calculated as follows:

$$q_{max} = \frac{\frac{F_S}{m} - 1300}{1100 \times \frac{D}{d}}$$

#### ■ depth of cut $a$ :

$$a = \frac{q_{max}}{f}$$

$F_S$	[N]	force of clamping cylinder
$q_{max}$	[mm <sup>2</sup> ]	maximum of chip cross section for metal removing
$D$	[mm]	cutting diameter
$d$	[mm]	clamping diameter
$m$	[-]	material factor (see adjustment-chart below)
$a$	[mm]	depth of cut
$f$	[mm/1]	feed rate

#### ■ tailstock force $F_R$ :

In case of tooling against the face driver the tailstock force has to be approx. 20% higher than the force of the clamping cylinder  $F_S$ .

In case of tooling against the tailstock, the tailstock should be approx. 40-50% higher than the force of the clamping cylinder, if not, then the chip cross section should be reduced by approx. 30%. (as there is an addition of force of clamping cylinder and cutting force)

**EXPLANATORY NOTES:** The first chip, however should always be machined towards the face driver, in order to achieve an ideal penetration of the carbide inserts. The ratio  $D/d$  should not exceed 2, otherwise it would work inefficiently.

#### Material factor $m$ adjustment chart:

material factor $m$	1.4	1.2	1.1	1.0	0.8
<b>Rm [N/mm<sup>2</sup>]</b>	1000	800	700	600	400
<b>examples</b>	42CrMo4	16MnCr5	C 15E (Ck 15)	S355J0	S235J0
		25CrMo4	C 45E (Ck 45)	35S20	

### Chisel load of carbide inserts

Keep the chisel load within the following range: 250 - 350 N per mm chisel length

#### ■ the chisel load is calculated as follows:

$$BS = \frac{F_S}{n \times s}$$

**EXEMPLIFICATION:** turning with FFP 3 face driver, 5 carbide inserts respective length of chisel 4 mm, clamping cylinder force 6000 N

$$BS = \frac{6000 \text{ N}}{5 \times 4 \text{ mm}} = 300 \frac{\text{N}}{\text{mm}}$$

$BS$  [N/mm] chisel load  
 $F_S$  [N] clamping cylinder force

$n$  [-] number of carbide inserts  
 $s$  [mm] chisel length




## Drive Disks FFP · Chisel NV / SL / SR

with changeable carbide inserts or made of tool steel  
for torque transmission onto the workpiece for the purpose  
of soft / green tooling

Type FFP · chisel NV / SL / SR




view from tailstock onto the face driver



SL (carbide)




NV (tool steel)



SR (carbide)

Technical data - type FFP · chisel NV / SL / SR



**TYPE CHISEL NV**

for tooling  
direction M4 and M3

for type FFP	D1	D2	D3	l	l1	W	number of chisels	S	F <sub>s</sub> (N)	cat. no.
<b>3</b>	14	14	60	59	5	35°	6 (tool steel)	2.5	4500	<b>740 02</b>
	18	18	60	59	5	30°	6 (tool steel)	2.5	4500	<b>740 03</b>

**TYPE CHISEL SL**

for tooling  
direction M4

**TYPE CHISEL SR**

for tooling  
direction M3

for type FFP	D1	D2	D3	l	l1	W	number of chisels	S	F <sub>s</sub> (N)	cat. no.	cat. no.
<b>3</b>	22	24	60	59	9	30°	4 carbide	4	4800	<b>740 04</b>	<b>740 20</b>
	26	28	60	53	9	30°	4 carbide	4	4800	<b>740 05</b>	<b>740 21</b>
	31	33	60	53	9	30°	5 carbide	4	6000	<b>740 06</b>	<b>740 22</b>
	36	37	60	45	9	30°	4 carbide	6	7200	<b>740 07</b>	<b>740 23</b>
	39	40	60	45	9	30°	4 carbide	6	7200	<b>740 08</b>	<b>740 24</b>
	44	45	60	45	9	30°	4 carbide	6	7200	<b>740 09</b>	<b>740 25</b>
	49	50	60	45	9	30°	5 carbide	6	9000	<b>740 10</b>	<b>740 26</b>
	59	60	60	45	-	-	5 carbide	6	9000	<b>740 11</b>	<b>740 27</b>
<b>4</b>	31	33	80	57	9	38°	5 carbide	4	6000	<b>740 40</b>	<b>740 60</b>
	36	38	80	57	9	35°	5 carbide	4	6000	<b>740 41</b>	<b>740 61</b>
	39	41	80	50	9	38°	6 carbide	4	7200	<b>740 42</b>	<b>740 62</b>
	44	45	80	45	9	38°	6 carbide	4	7200	<b>740 43</b>	<b>740 63</b>
	49	50	80	45	9	35°	5 carbide	6	9000	<b>740 44</b>	<b>740 64</b>
	59	60	80	45	9	30°	5 carbide	6	9000	<b>740 45</b>	<b>740 65</b>
	69	70	80	45	9	30°	6 carbide	6	10800	<b>740 46</b>	<b>740 66</b>
	84	85	80	45	9	-	6 carbide	6	10800	<b>740 47</b>	<b>740 67</b>
	99	100	80	45	-	-	6 carbide	6	10800	<b>740 48</b>	<b>740 68</b>
	110	111	80	45	-	-	7 carbide	6	12600	<b>740 49</b>	<b>740 69</b>
125	126	80	45	-	-	7 carbide	6	12600	<b>740 50</b>	<b>740 70</b>	

- All drive disks of type carbide will be provided with the respective carbide inserts.
- Additional clamping diameters of drive disks upon request.

## Changeable inserts for drive disks FFP

### Technical data - changeable inserts · drive disks FFP



### CARBIDE INSERTS

for type FFP	machining direction	S	cat. no.
3	SL/SR	4	736 548
4			
3	SL/SR	6	736 550
4			

### SET SCREW



for fixing carbide inserts

for carbide inserts with S =	thread	cat. no.
4	M4	736 549
6	M5	736 551

## Removal lever for drive disks FFP

In order to easily and quickly change the drive disks, the removal lever shown at right may be used.

### Technical data - removal lever



The removal lever is placed laterally inserted. By a tilting movement the drive disk can be loosened.

for type FFP	D1	D2	l1	cat. no.
3	51	80	275	632 40
4	71	100	285	632 41

### INFORMATION FOR CHANGING THE DRIVE DISKS

In order to exclude the risk of injury, we recommend to use suitable gloves for changing drive disks. We can provide a mounting aid upon request.

The drive disks can be pulled off head side. We recommend the use of a removal lever in order to reduce the force required and provide increased safety.


# Drive Disks FFP · KV Diamond




**cross serrated and diamond embedded for torque transmission onto the workpiece at hard turning and grinding operations**

This drive disks have a very high friction coefficient and can be used for both directions of rotation.


## Type FFP · KV diamond



## Technical data - type FFP · KV diamond



■ A [mm<sup>2</sup>]



for type FFP	D1	D2	D3	l	l1	W	A [mm <sup>2</sup> ]	cat. no.
3	14	9	60	59	5	35°	90	<b>740 82</b>
	18	13	60	59	5	30°	120	<b>740 83</b>
	22	13	60	59	9	30°	250	<b>740 84</b>
	26	17	60	53	9	30°	300	<b>740 85</b>
	31	22	60	53	9	30°	370	<b>740 86</b>
	36	24	60	45	9	30°	450	<b>740 87</b>
	39	30	60	45	9	30°	490	<b>740 88</b>
	44	35	60	45	9	30°	560	<b>740 89</b>
	49	39	60	45	9	30°	690	<b>740 90</b>
	59	47	60	45	9		1000	<b>740 91</b>
4	31	22	80	57	9	38°	370	<b>741 00</b>
	36	27	80	57	9	35°	450	<b>741 01</b>
	39	30	80	50	9	38°	490	<b>741 02</b>
	44	35	80	45	9	38°	560	<b>741 03</b>
	49	39	80	45	9	35°	690	<b>741 04</b>
	59	47	80	45	9	30°	1000	<b>741 05</b>
	69	57	80	45	9	30°	1190	<b>741 06</b>
	84	72	80	45	9	-	1470	<b>741 07</b>
	99	87	80	45	-	-	1750	<b>741 08</b>
	110	98	80	45	-	-	1960	<b>741 09</b>
125	113	80	45	-	-	2240	<b>741 10</b>	

■ Additional clamping diameters of drive disks upon request.

### ■ F<sub>S</sub> - clamping cylinder force:

The clamping cylinder force F<sub>S</sub> is dependent on the the diamond coated surface (A) of the drive disks.

**PLEASE NOTE:** surface load max. 150 N / mm<sup>2</sup>

**EXAMPLE:** If A = 55 mm<sup>2</sup>, the max. clamping cylinder force is F<sub>S</sub> = 8250 N

## Center Pins FFP


for face drivers FFP with taper shank dead center

Type FFP · tool steel or carbide



with carbide insert

Technical data – type FFP · tool steel or carbide



TYPE  
TOOL STEEL




TYPE  
CARBIDE

for type FFP	d1	d2	center Ø	clamping Ø	d3	l	cat. no.
3	14	M16 x 1.5	3.35	14	7	55	<b>734 52</b>
	14	M16 x 1.5	4.25	18 - 22	11	56	<b>734 53</b>
	14	M16 x 1.5	5.3	26 - 31	14	50.5	<b>734 54</b>
	14	M16 x 1.5	6.7	36 - 59	11.3	44	<b>734 55</b>
	14	M16 x 1.5	8.5	36 - 59	13.2	45	<b>734 56</b>
	14	M16 x 1.5	10.6	36 - 59	14	46	<b>734 57</b>
4	20	M22 x 1.5	5.3	31 - 36	20	59	<b>734 70</b>
	20	M22 x 1.5	6.7	39	17.1	53	<b>734 71</b>
	20	M22 x 1.5	8.5	44 - 125	13.2	50	<b>734 72</b>
	20	M22 x 1.5	10.6	44 - 125	15.2	51	<b>734 73</b>
	20	M22 x 1.5	13.2	44 - 125	17.8	53	<b>734 74</b>

cat. no.
<b>734 62</b>
<b>734 63</b>
<b>734 64</b>
<b>734 65</b>
<b>734 66</b>
<b>734 67</b>
<b>734 80</b>
<b>734 81</b>
<b>734 82</b>
<b>734 83</b>
<b>734 84</b>

■ Further center pins for other center holes upon request.

**Extracting nuts for center pin FFP****Type FFP** · extracting nuts**Technical data – type FFP** · extracting nuts

for type FFP	d2	d1	s	h	cat. no.
<b>3</b>	M16 x 1.5	20	22	10	<b>930 05</b>
<b>4</b>	M22 x 1.5	30	30	10	<b>930 06</b>



## Face Drivers FFPV

### with drive disk and fixed center pin for high true run accuracy

The entire surface of the workpiece can be tooled and finished by clamping with a maximum of torque transmission.

NEIDLEIN face drivers of type FFPV with drive disks are mechanical clamping systems which are suited for **turn-milling** as well as for hard turn-milling processes.

Face drivers of the type FFPV are power operated on the side of the machine spindle as well as the side of the tailstock. The workpieces are clamped centrally by the fixed center pin. This operation results in high true run accuracy.

#### Type FFPV with flange retainer for screw connection

The face driver FFPV is designed for a direct mounting onto a spindle nose, DIN 702-1 (55028)



#### NEIDLEIN face drivers FFPV ensure:

- radial, almost backlash-free driving
- datum-point location in the center of the workpiece ensures constant measures of length
- compensating drive disk for uneven face sides
- high flexibility in the application, wide range of clamping diameters
- run-out deviation in the process 0.005 - 0.015 mm
- low setup costs due to fast change of drive disks and center pins
- cost efficient exchange of parts that are in contact with the workpiece (changeable carbide inserts)
- suitable changeable parts depending on the hardness of the workpiece

## Clamping principle


The center pin located on the side of the tailstock pushes the workpiece against the fixed center pin of the face driver. The motion of the drive disk against the workpiece face side is initiated by the clamping cylinder mounted into the machine. The drive disk is "floatingly" suspended, thus balancing out possible planarity defects of the contact surface of the workpiece. The datum-point of workpieces on the machine is determined by the size of the center hole.


The entire surface of the workpiece can now be tooled in one single clamping. See page 71 for data of cutting performance and the clamping forces requested.

You will find various sizes of face drivers with appropriate standard drive disks and center pins on the following pages.

In case you need special dimensions, we will be glad to design clamping devices suitable for your workpiece.

### Type FFPV with flange retainer



**Technical data – type FFPV face driver · for screw connection**


l\* length of drive disks at  
page 72 - 73

type	D	D1	d3	d4	d6	L1	fixing screws		short taper size	max. workpiece weight [kg] *	cat. no.
							type	pcs			
3	80	14 - 59	130	82.563	104.8	31	M12	3	5	90	<b>632 50</b>
	90	14 - 59	160	106.375	133.4	31	M12	3	6	90	<b>632 51</b>
4	90	31 - 125	160	106.375	133.4	31	M12	3	6	250	<b>632 52</b>
	100	31 - 125	220	139.719	171.4	39	M16	3	8	250	<b>632 53</b>


\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7

- All face drivers are provided without drive disk and without center pin.  
(changable parts see page 72 - 76)

## Face Drivers FFPV · Calculations

### max. chip cross section of metal removing

**PRINCIPLE:** The tailstock force pushes the workpiece against the fixed center pin of the face driver. The drive disk is actuated by the clamping cylinder mounted into the machine.



#### ■ maximum chip cross section $q_{max}$ :

At a given force of clamping cylinder, the maximum chip cross section is calculated as follows:

$$q_{max} = \frac{\frac{F_s}{m} - 1300}{1100 \times \frac{D}{d}}$$

#### NOTE FFPV:

When using the face driver type FFPV, the calculated machining chip cross section  $q_{max}$  must be reduced by 20%.

#### ■ depth of cut $a$ :

$$a = \frac{q_{max}}{f}$$

$F_s$	[N]	force of clamping cylinder
$q_{max}$	[mm <sup>2</sup> ]	maximum of chip cross section for metal removing
D	[mm]	cutting diameter
d	[mm]	clamping diameter
m	[-]	material factor (see adjustment-chart below)
a	[mm]	depth of cut
f	[mm/1]	feed rate

#### ■ tailstock force $F_R$ :

In case of tooling against the face driver the tailstock force has to be approx. 20% higher than the force of the clamping cylinder  $F_s$ . In case of tooling against the tailstock, the tailstock should be approx. 40-50% higher than the force of the clamping cylinder, if not, then the chip cross section should be reduced by approx. 30%. (as there is an addition of force of clamping cylinder and cutting force)

**EXPLANATORY NOTES:** The first chip, however should always be machined towards the face driver, in order to achieve an ideal penetration of the carbide inserts. The ratio  $D/d$  should not exceed 2, otherwise it would work inefficiently.

#### Material factor $m$ adjustment chart:

material factor $m$	1.4	1.2	1.1	1.0	0.8
<b>Rm [N/mm<sup>2</sup>]</b>	1000	800	700	600	400
<b>examples</b>	42CrMo4	16MnCr5	C 15E (Ck 15)	S355J0	S235J0
		25CrMo4	C 45E (Ck 45)	35S20	

### Chisel load of carbide inserts

Keep the chisel load within the following range: 250 - 350 N per mm chisel length

#### ■ the chisel load is calculated as follows:

$$BS = \frac{F_s}{n \times s}$$

**EXEMPLIFICATION:** turning with FFPV 3 face driver, 5 carbide inserts respective length of chisel 4 mm, clamping cylinder force 6000 N

$$BS = \frac{6000 \text{ N}}{5 \times 4 \text{ mm}} = 300 \frac{\text{N}}{\text{mm}}$$

BS [N/mm] chisel load  
 $F_s$  [N] clamping cylinder force

n [-] number of carbide inserts  
 s [mm] chisel length


## Drive disks FFPV · Chisel NV

with changeable carbide inserts or made of tool steel for torque transmission onto the workpiece for the purpose of soft / green tooling

### Type FFPV · chisel NV



view from tailstock onto the face driver




NV (tool steel)

D1 = 14 - 18 · type 3



NV (carbide)

### Technical data - type FFPV · chisel NV



**TYPE CHISEL NV**for tooling direction M4 and M3  
(tool steel)

for type FFPV	D1	D2	D3	l	l1	W	number of chisels	S	F <sub>s</sub> (N)	cat. no.
<b>3</b>	14	14	60	59	5	35°	6 (tool steel)	2.5	4500	<b>741 22</b>
	18	18	60	59	5	30°	6 (tool steel)	2.5	4500	<b>741 23</b>

**TYPE CHISEL NV**for tooling direction M4 and M3  
(carbide)

for type FFPV	D1	D2	D3	l	l1	W	number of chisels	S	F <sub>s</sub> (N)	cat. no.
<b>3</b>	22	24	60	59	9	30°	4 (carbide)	4	4800	<b>741 24</b>
	26	28	60	53	9	30°	4 (carbide)	4	4800	<b>741 25</b>
	31	33	60	53	9	30°	5 (carbide)	4	6000	<b>741 26</b>
	36	37	60	45	9	30°	4 (carbide)	6	7200	<b>741 27</b>
	39	40	60	45	9	30°	4 (carbide)	6	7200	<b>741 28</b>
	44	45	60	45	9	30°	4 (carbide)	6	7200	<b>741 29</b>
	49	50	60	45	9	30°	5 (carbide)	6	9000	<b>741 30</b>
	59	60	60	45	-	-	5 (carbide)	6	9000	<b>741 31</b>
<b>4</b>	31	33	80	57	9	38°	5 (carbide)	4	6000	<b>741 40</b>
	36	38	80	57	9	35°	5 (carbide)	4	6000	<b>741 41</b>
	39	41	80	50	9	38°	6 (carbide)	4	7200	<b>741 42</b>
	44	45	80	45	9	38°	6 (carbide)	4	7200	<b>741 43</b>
	49	50	80	45	9	35°	5 (carbide)	6	9000	<b>741 44</b>
	59	60	80	45	9	30°	5 (carbide)	6	9000	<b>741 45</b>
	69	70	80	45	9	30°	6 (carbide)	6	10800	<b>741 46</b>
	84	85	80	45	9	-	6 (carbide)	6	10800	<b>741 47</b>
	99	100	80	45	-	-	6 (carbide)	6	10800	<b>741 48</b>
	110	111	80	45	-	-	7 (carbide)	6	12600	<b>741 49</b>
125	126	80	45	-	-	7 (carbide)	6	12600	<b>741 50</b>	

■ Additional clamping diameters of drive disks upon request.

## Changeable inserts for drive disks FFP / FFP(V)

### Technical data - changeable inserts · drive disks FFPV



### CARBIDE INSERTS

for type FFP / FFPV	machining direction	S	cat. no.
3	NV	4	736 558
4			
3	NV	6	736 560
4			

### SET SCREW



for fixing carbide inserts

for carbide inserts with S =	thread	cat. no.
4	M4	736 549
6	M5	736 551

## Removal lever for drive disks FFP(V)

In order to easily and quickly change the drive disks, the removal lever shown at right may be used.

### Technical data - removal lever



The removal lever is placed laterally inserted. By a tilting movement the drive disk can be loosened.

for type FFP / FFPV	D1	D2	l1	cat. no.
3	51	80	275	632 40
4	71	100	285	632 41

### INFORMATION FOR CHANGING THE DRIVE DISKS

In order to exclude the risk of injury, we recommend to use suitable gloves for changing drive disks. We can provide a mounting aid upon request.

The drive disks can be pulled off head side. We recommend the use of a removal lever in order to reduce the force required and provide increased safety.

# Center Pins FFP / FFP(V)


for face drivers FFP / FFP(V) with taper shank dead center

Type FFP / FFP(V) · tool steel or carbide

Technical data – type FFP / FFP(V) · tool steel or carbide



**HM** with carbide insert



TYPE  
TOOL STEEL

**HM** TYPE  
CARBIDE

for type	d1	d2	center Ø	clamping Ø	d3	l	cat. no.	
FFP / FFP(V)	14	M16 x 1.5	3.35	14	7	55	<b>734 52</b>	
	14	M16 x 1.5	4.25	18 - 22	11	56	<b>734 53</b>	
	<b>3</b>	14	M16 x 1.5	5.3	26 - 31	14	50.5	<b>734 54</b>
		14	M16 x 1.5	6.7	36 - 59	11.3	44	<b>734 55</b>
		14	M16 x 1.5	8.5	36 - 59	13.2	45	<b>734 56</b>
		14	M16 x 1.5	10.6	36 - 59	14	46	<b>734 57</b>
<b>4</b>	20	M22 x 1.5	5.3	31 - 36	20	59	<b>734 70</b>	
	20	M22 x 1.5	6.7	39	17.1	53	<b>734 71</b>	
	20	M22 x 1.5	8.5	44 - 125	13.2	50	<b>734 72</b>	
	20	M22 x 1.5	10.6	44 - 125	15.2	51	<b>734 73</b>	
	20	M22 x 1.5	13.2	44 - 125	17.8	53	<b>734 74</b>	

cat. no.
<b>734 62</b>
<b>734 63</b>
<b>734 64</b>
<b>734 65</b>
<b>734 66</b>
<b>734 67</b>
<b>734 80</b>
<b>734 81</b>
<b>734 82</b>
<b>734 83</b>
<b>734 84</b>


■ Further center pins for other center holes upon request.

## Extracting nuts for center pin FFP / FFPV


### Type FFP / FFPV · extracting nuts



### Technical data - type FFP / FFPV · extracting nuts



for type FFP / FFPV	d2	d1	s	h	cat. no.
<b>3</b>	M16 x 1.5	20	22	10	<b>930 05</b>
<b>4</b>	M22 x 1.5	30	30	10	<b>930 06</b>





## Face Drivers FFBR / FBSR

### with drive pins and fixed center pin

The complete surface of both, hardened and soft workpieces, can be finish-ground with one single clamping.

Face drivers types FFBR/FBSR are power-operated on the side of the spindle. The workpieces are clamped centrally using a dead center pin, this way a high true running accuracy is achieved.

#### Type FFBR with flange retainer

There are two retainer designs for adapting the face drivers onto the machine spindle – either for adaption onto a flange adapter with 140 in diameter or for direct mounting onto a spindle nose DIN 702-1 size 6 (DIN 55026/28).



#### Type FBSR with morse taper retainer

Like face driver FFBR, but including morse taper shank and extracting nut. Adjustment true by using set screws inside shank for highest true running accuracy.



#### NEIDLEIN face drivers FFBR / FBSR ensure:


- datum-point located in the center of the workpiece
- run-out deviation in the process 0.002 - 0.005 mm
- compensating drive components
- retractable drive pins for secure loading and unloading of the workpiece
- adjustment true at face drivers for highest run-out requirements
- **Attention:** Not suitable for profile grinding of gears. For generating gear grinding, please contact our technical sales department.

## Clamping principle

The center pin located on the side of the tailstock pushes the workpiece against the fixed center pin of the face driver. The motion of the drive pins against the surface of the workpiece is initiated by the clamping cylinder mounted into the machine. The drive pins are "floatingly" suspended, thus compensating

irregularities with regard to possible unevenness of the surface of workpieces. The datum-point of workpieces on the machines is determined by the size of the center hole. The entire surface of workpiece can now be tooled in one single clamping.


### Typ FFBR with flange retainer



**Technical data – type FFBR face driver**

type cylindrical retainer  $\varnothing 140$  mm  
on flange adapter

type short taper retainer DIN 702-1 size 6  
directly onto the machine spindle

**TYPE CYLINDRICAL  
RETAINER  $\varnothing 140$  mm****TYPE SHORT TAPER  
RETAINER SIZE 6**


type FFBR	d	center $\varnothing$	d5	d7	d8	d9	clamping $\varnothing$			max. workpiece weight [kg] *	cat. no.
							D1	D2	D3		
<b>0</b>	65	1 - 3	18	16	1.5	48	6	9	15	8	<b>726 31</b>
<b>01</b>	65	1 - 5	18	18	3	48	8	11	17	6	<b>726 32</b>
<b>11</b>	65	2 - 6.5	18	21	4.25	48	11	14	20	12	<b>726 33</b>
<b>1</b>	65	4 - 8.5	18	25	6.25	48	15	18	24	25	<b>726 34</b>
<b>2</b>	77	4 - 9	25	38	6.5	60	27	30	36	50	<b>726 35</b>
<b>3</b>	85	6 - 11	25	46	8.5	68	35	38	44	80	<b>726 36</b>
<b>4</b>	110	10 - 15	25	62	12.5	83	50	53	59	150	<b>726 37</b>

cat. no.
<b>726 01</b>
<b>726 02</b>
<b>726 03</b>
<b>726 04</b>
<b>726 05</b>
<b>726 06</b>
<b>726 07</b>

\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7

- Face drivers without changeable parts (types 0 / 01 include center body). Center pins, center bodies and drive pins see page 82 - 83.
- All face drivers for grinding are designed for 3 drive pins only.
- Diameter d8 refers to standard center pins. (see page 83)
- Further center pins for other center holes upon request.

### Technical data – type FBSR face driver



type FBSR	MK	d	A	center Ø	d3	d5	d7	d8	d9	L	l2	l3	clamping Ø			max. workpiece weight [kg] *	cat. no.	
													D1	D2	D3			
0	4	65	110	1 - 3	M35 x 1.5	11.5	16	1.5	48	183	73	16	6	9	15	8	<b>726 51</b>	
01	4	65	110	1 - 5	M35 x 1.5	11.5	18	3	48	183	73	16	8	11	17	6	<b>726 52</b>	
11	4	65	110	2 - 6.5	M35 x 1.5	11.5	21	4.25	48	183	73	16	11	14	20	12	<b>726 53</b>	
1	4	65	110	4 - 8.5	M35 x 1.5	11.5	25	6.25	48	183	73	16	15	18	24	25	<b>726 54</b>	
	5	65	110	4 - 8.5	M48 x 1.5	17.5	25	6.25	48	207	97	19	15	18	24	25	<b>726 55</b>	
2	4	77	110	4 - 9	M35 x 1.5	11.5	38	6.5	60	183	73	16	27	30	36	50	<b>726 56</b>	
	5	77	110	4 - 9	M48 x 1.5	17.5	38	6.5	60	207	97	19	27	30	36	50	<b>726 57</b>	
3	4	85	110	6 - 11	M35 x 1.5	11.5	46	8.5	68	183	73	16	35	38	44	80	<b>726 58</b>	
	5	85	110	6 - 11	M48 x 1.5	17.5	46	8.5	68	207	97	19	35	38	44	80	<b>726 59</b>	
4	4	100	120	10 - 15	M35 x 1.5	11.5	62	12.5	83	193	73	16	50	53	59	150	<b>726 60</b>	
	5	100	120	10 - 15	M48 x 1.5	17.5	62	12.5	83	207	97	19	50	53	59	150	<b>726 61</b>	

\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7

- Face drivers without changeable parts (types 0/01 include center body). Center pins, center bodies and drive pins see page 82 - 83.
- All face drivers for grinding are designed for 3 drive pins only.
- Diameter d8 refers to standard center pins. (see page 83)
- Further center pins for other center holes upon request.




## Drive Pins FFBR / FBSR · Chisel SR · Diamond

**for torque transmission onto the workpiece by grinding soft and hardened workpieces**

**For soft workpieces** we apply drive pins made of hardened HSS comprising a chisel. They are characterized by high wear-resistance as well as maximum torque transmission.

**For hardened workpieces** we apply drive pins that are diamond coated. They are characterized by a high friction-coefficient.

### Type FFBR / FBSR · chisel SR · diamond



### Technical data – type FFBR / FBSR · chisel SR · diamond

model A




model B



model C



view from tailstock onto the face driver



#### TYPE CHISEL SR

for type	for clamping	model	l	cat. no.
FFBR FBSR	D1	C	1.5	<b>736 651</b>
FFBR FBSR	D2	B	2	<b>736 652</b>
FFBR FBSR	D3	A	2	<b>736 653</b>

#### TYPE DIAMOND COATING

l	cat. no.
1.5	<b>736 654</b>
3	<b>736 655</b>
3	<b>736 656</b>

- Clamping diameter D1, D2, D3 see pages 80 - 81.
- Further clamping  $\varnothing$  of drive pins upon request.

# Center Pins FFBR / FBSR

## for face drivers FFBR / FBSR with fixed center pin

For maximum stability and run-out requirements the center pins are produced with narrow tolerances and are fixed safely via set screw and plane surface inside the face driver.

Due to the accurate assembly between center pin and head of face driver we ensure highly accurate replacement.



For a large batch of hardened workpieces we recommend the construction comprising carbide insert. Center heads of type 0 / 01 consist of 60°-taper tip that are carbide coated.

### Type FFBR / FBSR · tool steel or carbide

### Technical data – type FFBR / FBSR · tool steel or carbide



with carbide insert



A overhang dimension of face driver to centre d8 (see page 80 - 81)

TYPE  
TOOL STEEL

HM TYPE  
CARBIDE

for type FFBR / FBSR	d1	d4	center Ø	d7	d8	d9	cat. no.
<b>0</b>	3	-	1 - 3	16	1.5	48	<b>734 15</b>
<b>01</b>	5	-	1 - 5	18	3	48	<b>734 16</b>
<b>11</b>	7.8	6	2 - 6.5	-	4.25	-	<b>734 11</b>
<b>1</b>	9.8	8	4 - 8.5	-	6.25	-	<b>734 02</b>
<b>2</b>	10	14	4 - 9	-	6.5	-	<b>734 03</b>
<b>3</b>	12	18	6 - 11	-	8.5	-	<b>734 04</b>
<b>4</b>	16	20	10 - 15	-	12.5	-	<b>734 05</b>

cat. no.
<b>734 31</b>
<b>734 32</b>
<b>734 33</b>
<b>734 34</b>
<b>734 35</b>
<b>734 36</b>
<b>734 38</b>

- Further center pins for other center holes upon request.
- At type FFBR/FBSR 0/01 (type carbide) the 60° tip is carbide coated.



## Face Drivers FFB / FFBH

### with drive pins and fixed center pin

The entire surface of the workpiece can be finished with one single clamping and with a maximum of torque transmission. NEIDLEIN face drivers are clamping systems, which are equally suitable **for grinding soft and hard workpieces**.

Face drivers of types FFB / FFBH are power-operated on the side of the spindle.

Originally conceived for turning, face drivers of type FFB / FFBH provide a multitude of possible applications for grinding. Without retraction of drive pins and with NEIDLEIN retainer  $\varnothing 100$  type FFB / FFBH provides an alternative to face drivers of type FFBH / FBSR, especially when machining large-size workpieces.

When FFBH is used, the compensation of drive pins is implemented hydraulically, thus achieving excellent true runout results.

#### Type FFB with flange retainer

Type FFB is adapted onto the machine spindle using an adjustable flange adapter.



#### Type FFBH with flange retainer


Type FFBH is adapted onto the machine spindle using an adjustable flange adapter.



#### NEIDLEIN face drivers FFB / FFBH ensure:

- datum-point located in the center of the workpiece
- run-out deviation in the process
  - type FFB: 0.005 - 0.01 mm
  - type FFBH: 0.002 - 0.005 mm
- adjustment true via adjustable flange adapter for highest run-out requirements
- easy handling
- compensating drive components / optimal clamping of the workpiece
- face driver type FFBH comprises a hydraulic unit which is exchangeable as a cartridge
- **Attention:** Not suitable for profile grinding of gears. For generating gear grinding, please contact our technical sales department.

### Technical data – type FFB face driver



type FFB 01/0

type FFB	d	center Ø	d2	d3	d5	d6	d8	A	l2	drive pins	fixing screws type	fixing screws pcs	clamping Ø			max. workpiece weight [kg]*	cat. no.
													D1	D2	D3		
<b>01</b>	60	1-5	6	160	18	133.4	3.5	115	38	3	M12	3	8	11	17	6	<b>731 01</b>
<b>0</b>	60	1-3	8	160	18	133.4	3	115	38	3	M12	3	6	11	19	8	<b>731 12</b>
<b>11</b>	42	2-6.5	6	160	12	133.4	4.25	115	38	3	M12	3	11	14	20	12	<b>731 11</b>
<b>1</b>	48	4-8.5	8	160	18	133.4	6.25	115	38	3	M12	3	13	18	26	25	<b>731 02</b>
<b>2</b>	70	4-9	10	160	22	133.4	6.5	115	38	3	M12	3	26	31	36	50	<b>731 03</b>
<b>3</b>	70	6-11	10	160	22	133.4	8.5	115	38	3	M12	3	34	39	44	90	<b>731 04</b>
<b>35</b>	80	4-9	15	160	22	133.4	6.5	115	38	3	M12	3	29	39	49	130	<b>731 13</b>
<b>4</b>	90	10-15	15	160	25	133.4	12.5	115	38	5	M12	3	39	49	59	250	<b>731 05</b>
<b>45</b>	100	10-15	15	160	25	133.4	12.5	115	54	5	M12	3	49	59	69	400	<b>731 06</b>
<b>5</b>	132	10-15	20	160	25	133.4	12.5	115	54	5	M12	3	69	84	99	1000	<b>731 07</b>
<b>55</b>	182	10-15	20	220	40	171.4	12.5	155	54	5	M16	3	110	125	140	1600	<b>731 08</b>
<b>6</b>	220	10-15	20	250	40	210	12.5	171	54	5	M20	3	140	155	170	2500	<b>731 09</b>

\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7


- All face drivers are supplied without drive pins. (drive pins see page 88-89)
- Types FFB 01/0 are supplied with center body, all other types without center pin. (center pin see page 87)
- Diameter d8 refers to standard center pins. (see page 87)
- Further center pins for other center holes upon request.
- Mounting elements for face drivers see page 104-109.

A stable assembly on the machine spindle is implemented using an adjustable flange adapter. We supply these flange adapters for various sizes of spindle heads in standardized size (DIN ISO 702-1 / DIN 55028) or for vendor-specific spindle heads in particular. Thus face drivers of range FFB can be assembled universally on various machines. Driving components and center pin are easily exchanged from the front part of the machine.

As required, the face driver can be equipped with either drive pins comprising a chisel for machining soft workpieces, or with diamond coated drive pins for machining hardened workpieces.

Apart from the clamping diameters listed above D1, D2, D3, we can also provide alternative sizes upon request. We are also able to manufacture larger center pins or mushroom centers for oversize centering.

### Technical data – type FFBH face driver




type	d	center Ø	d2	d3	SW	d5	d6	d8	A	l2	drive pins	fixing screws		clamping Ø			max. workpiece weight [kg] *	cat. no.
												type	pcs	D1	D2	D3		
FFBH																		
<b>1</b>	70	4-8.5	8	160	24	12	133.4	6.25	115	35	3	M12	3	13	18	26	25	<b>631 02</b>
<b>2</b>	70	4-9	10	160	24	12	133.4	6.5	115	35	3	M12	3	26	31	36	50	<b>631 03</b>
<b>3</b>	70	6-11	10	160	24	12	133.4	8.5	115	35	3	M12	3	34	39	44	90	<b>631 04</b>
<b>4</b>	90	10-15	15	160	34	12	133.4	12.5	132	35	5	M12	3	39	49	59	250	<b>631 06</b>
<b>45</b>	100	10-15	15	160	34	12	133.4	12.5	132	35	5	M12	3	49	59	69	400	<b>631 07</b>
<b>5</b>	132	10-15	20	160	34	12	133.4	12.5	149	35	5	M12	3	69	84	99	1000	<b>631 08</b>

\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7

- All face drivers are supplied without drive pins and without center pins. (changeable parts see page 87 - 89)
- The diameter d8 refers to the standard center pins. (see page 87)
- Further center pins for other center holes upon request.
- Mounting elements for face drivers see page 104 - 109.

### Technical data – type FFBH hydraulic unit



type	SW1	d5	L	d1	SW2	D	cat. no.
FFBH							
<b>1</b>	24	12	70.5	47	41	75	
<b>2</b>	24	12	70.5	47	41	75	<b>631 02 HE</b>
<b>3</b>	24	12	70.5	47	41	75	
<b>4</b>	34	12	70.5	65	59	93	<b>631 06 HE</b>
<b>45</b>	34	12	70.5	65	59	93	
<b>5</b>	34	12	70.5	87	81	131	<b>631 08 HE</b>

The general explanatory notes for this face driver FFBH can be obtained from the sheet "technical data – type FFB". For safe and smooth operation of face driver we recommend exchange of hydraulic unit after 1500 operating hours.

Furthermore, we offer the option for professional maintenance of the exchanged hydraulic units in our production plant.

# Center Pins FFB / FFBH

## for face drivers FFB / FFBH with fixed center pin

For maximum stability and run-out requirements the center pins are produced with narrow tolerances and are fixed safely via set screw and plane surface inside the face driver.

Due to the accurate assembly between center pin and head of face driver we ensure highly accurate replacement.


For a large batch of hardened workpieces we recommend the construction comprising carbide insert. Center heads of type 0 / 01 consist of 60°-taper tip that are carbide coated.

### Type FFB / FFBH · tool steel or carbide


### Technical data – type FFB / FFBH · tool steel or carbide



with carbide insert



center body type FFB / FFBH 01 / 0



A overhang dimension of face driver to centre d8 (see page 85 - 86)

#### TYPE TOOL STEEL

#### TYPE CARBIDE

for type FFB / FFBH	d1	d2	d4	center Ø	d8	cat. no.
<b>01</b>	5	6	48	1 - 5	3.5	<b>734 01</b>
<b>0</b>	3	8	48	1 - 3	3	<b>734 101</b>
<b>11</b>	7.8	-	6	2 - 6.5	4.25	<b>734 11</b>
<b>1</b>	9.8	-	8	4 - 8.5	6.25	<b>734 02</b>
<b>2</b>	10	-	14	4 - 9	6.5	<b>734 03</b>
<b>3</b>	12	-	18	6 - 11	8.5	<b>734 04</b>
<b>35</b>	10	-	14	4 - 9	6.5	<b>734 12</b>
<b>4</b>	16	-	20	10 - 15	12.5	<b>734 05</b>
<b>45</b>	16	-	28	10 - 15	12.5	<b>734 06</b>
<b>5</b>	16	-	35	10 - 15	12.5	<b>734 07</b>
<b>55</b>	16	-	35	10 - 15	12.5	<b>734 08</b>
<b>6</b>	16	-	35	10 - 15	12.5	<b>734 09</b>

cat. no.
<b>734 43</b>
<b>734 44</b>
<b>734 33</b>
<b>734 34</b>
<b>734 35</b>
<b>734 36</b>
<b>734 37</b>
<b>734 38</b>
<b>734 39</b>
<b>734 40</b>
<b>734 41</b>
<b>734 42</b>

■ Further center pins for other center holes upon request.




## Drive Pins FFB / FFBH · Chisel SR · Diamond

### for torque transmission onto the workpiece when grinding soft and hardened workpieces




Drive pins made of hardened HSS with chisel are used **for grinding soft workpieces**. These are characterized by a high resistance to wear and tear and a maximum torque transmission.

Diamond coated drive pins are applied **for grinding hardened workpieces**. These are characterized by a high resistance to wear and tear, a maximum of torque transmission and by a high friction-coefficient.


#### Type FFB / FFBH · chisel SR · diamond



#### Technical data – type FFB / FFBH · chisel SR · diamond



view from tailstock  
onto the face driver



**TYPE  
CHISEL SR**

for type FFB/FFBH	d	clamping Ø			chisel length			cat. no.
		D1	D2	D3	l1	l2	l3	
<b>01</b>	6	8			1.5			<b>736 600</b>
	6		11			2		<b>736 601</b>
	6			17			2	<b>736 602</b>
<b>0</b>	8	6			1.5			<b>736 603</b>
	8		11			2		<b>736 604</b>
	8			19			2	<b>736 605</b>
<b>11</b>	6	11			1.5			<b>736 606</b>
	6		14			2		<b>736 607</b>
	6			20			2	<b>736 608</b>
<b>1</b>	8	13			1.5			<b>736 609</b>
	8		18			2		<b>736 610</b>
	8			26			2	<b>736 611</b>
<b>2</b>	10	26			3			<b>736 612</b>
	10		31			3		<b>736 613</b>
	10			36			3	<b>736 614</b>
<b>3</b>	10	34			3			<b>736 615</b>
	10		39			3		<b>736 616</b>
	10			44			3	<b>736 617</b>
<b>35</b>	15	29			3			<b>736 618</b>
	15		39			3		<b>736 619</b>
	15			49			3	<b>736 620</b>
<b>4</b>	15	39			3			<b>736 621</b>
	15		49			3		<b>736 622</b>
	15			59			3	<b>736 623</b>
<b>45</b>	15	49			3			<b>736 624</b>
	15		59			3		<b>736 625</b>
	15			69			3	<b>736 626</b>
<b>5</b>	20	69			4			<b>736 627</b>
	20		84			4		<b>736 628</b>
	20			99			4	<b>736 629</b>
<b>55</b>	20	110			4			<b>736 630</b>
	20		125			4		<b>736 631</b>
	20			140			4	<b>736 632</b>
<b>6</b>	20	140			4			<b>736 633</b>
	20		155			4		<b>736 634</b>
	20			170			4	<b>736 635</b>

**TYPE  
DIAMOND COATING**

chisel length			cat. no.
l1	l2	l3	
1.5			<b>736 300</b>
	3		<b>736 301</b>
		3	<b>736 302</b>
1.5			<b>736 303</b>
	4		<b>736 304</b>
		4	<b>736 305</b>
1.5			<b>736 306</b>
	3		<b>736 307</b>
		3	<b>736 308</b>
1.5			<b>736 309</b>
	4		<b>736 310</b>
		4	<b>736 311</b>
5			<b>736 312</b>
	5		<b>736 313</b>
		5	<b>736 314</b>
5			<b>736 315</b>
	5		<b>736 316</b>
		5	<b>736 317</b>
5			<b>736 318</b>
	5		<b>736 319</b>
		5	<b>736 320</b>
5			<b>736 321</b>
	5		<b>736 322</b>
		5	<b>736 323</b>
5			<b>736 324</b>
	5		<b>736 325</b>
		5	<b>736 326</b>
5			<b>736 327</b>
	7.5		<b>736 328</b>
		7.5	<b>736 329</b>
5			<b>736 330</b>
	7.5		<b>736 331</b>
		7.5	<b>736 332</b>
5			<b>736 333</b>
	7.5		<b>736 334</b>
		7.5	<b>736 335</b>

■ Further clamping Ø of drive pins upon request.



## Face Drivers FDNC

### with drive heads and movable center pin

Face drivers for clamping workpieces **for milling** free from backlash for gear hobbing, keyway milling and other surfaces.

#### Type FDNC with flange retainer

Type FDNC is mounted onto the machine spindle nose using a flange adapter.





#### NEIDLEIN face drivers FDNC ensure:

- machining free from backlash due to fixed driving elements
- stability and mounting of high transverse thrust using adjustable, spring-loaded center pins
- constant datum point on the end face of the workpiece
- run-out deviation in the process 0.015 - 0.02 mm (a machined and rectangular face side of the workpiece is required)
- adjustment of dissimilar bore holes
- adjustment true at drive head for high true running accuracy
- tapered design for optimum tool path

## Clamping principle

The workpiece is pushed by the tailstock force against the moving center pin, which moves back until the workpiece face side is in contact with the drive head.



type	D	d3	d5	l1	l2	l3	cat. no.
FDNC							
<b>11-4</b>	59	160	52	160	77	90	<b>732 01</b>

- All face drivers are supplied without drive heads and without center pins. (changeable parts see page 92 - 93)
- Mounting elements for face drivers see page 104 - 109.




## Drive Heads FDNC

### changeable drive heads for basic body FDNC

#### Type FDNC · drive head



#### Technical data - type FDNC · drive head



for type FDNC	D1	D2	d1	max. workpiece weight [kg] *	cat. no.
<b>11.11</b>	11	7	6	12	<b>737 01</b>
<b>11.14</b>	14	9	6	12	<b>737 02</b>
<b>11.18</b>	18	12	6	12	<b>737 03</b>
<b>1.22</b>	22	14	8	20	<b>737 04</b>
<b>1.26</b>	26	18	8	20	<b>737 05</b>
<b>2.30</b>	30	20	14	40	<b>737 06</b>
<b>2.36</b>	36	24	14	40	<b>737 07</b>
<b>3.39</b>	39	29	18	60	<b>737 08</b>
<b>3.44</b>	44	34	18	60	<b>737 09</b>
<b>4.49</b>	49	39	24	100	<b>737 10</b>
<b>4.59</b>	59	49	24	100	<b>737 11</b>

\* The max. workpiece weight also depends on the size of the workpiece center hole / DIN332 part 7

■ Additional dimensions for drive heads upon request.


## Center Pins FDNC

changeable center pins for basic body  
and drive heads FDNC

### Type FDNC · center pin



### Technical data - type FDNC · center pin



for type FDNC	d1	l	center Ø	cat. no.
<b>11</b>	6	78	1 - 6	<b>733 01</b>
<b>1</b>	8	80	1 - 8	<b>733 02</b>
<b>2</b>	14	86	1 - 14	<b>733 03</b>
<b>3</b>	18	89	3 - 18	<b>733 04</b>
<b>4.1</b>	24	89	3 - 18	<b>733 05</b>
<b>4.2</b>	24	96	16 - 24	<b>733 06</b>

■ Further center pins for other center holes upon request.



# Pipe Drivers & Drive Dog



NDG



DH

Pipe Drivers NDG / AND

96

Drive Dog DH

98



## Pipe Drivers NDG / AND


The entire outside surface of a tubular workpiece can be tooled with one single clamping and high torque transmission.

By means of a pipe driver, large clamping areas can be covered.

### Type NDG pipe driver



### Clamping principle




#### NEIDLEIN pipe drivers NDG and AND ensure:

- high torque transmission, thus achieving a high rate of metal removing
- extended service life of driving chisels
- a large clamping area of tubular workpieces 2 - 155 mm bore-diameter
- finishing of outer surface by clamping » saving of time
- easy handling


**Technical data - type NDG pipe driver**

type NDG	morse taper	D	d1	L	L1	L2	L3	a	chisel PCS	for bore-Ø from to	cat. no.
0/15	2	18	0	100	31	4	68	60°	6	2 17	750 01
0/30	3	31	0	135	50	5	85	60°	6	2 30	750 02
10/40	3	45	8	145	60	5	85	60°	6	9 43	750 03
20/60	3	63	18	147	62	5	85	60°	8	19 60	750 04
10/40	4	45	8	168	60	6	108	60°	6	9 43	750 05
20/60	4	63	18	170	62	6	108	60°	8	19 60	750 06




**Technical data - type NDG drive cone exchangeable**

type NDG	D	d1	d2	L	L1	a	chisel PCS	for bore-Ø from to	cat. no.
35/90	93	32.8	35	70	46	60°	10	33 90	751 01
90/155	158	88	35	75	46	60°	10	88 155	751 02



**Technical data - type AND arbor**

type AND	morse taper	D	d2	L1	L2	L3	L4	cat. no.
35/4	4	46	35	36	16	5	108	752 01
35/5	5	44.5	35	36	16	5	130	752 02
35/6	6	64	35	36	16	5	144	752 03



## Drive Dog DH



### driver for turning and grinding operations


NEIDLEIN drive dogs are used as a driver for turning and grinding operations. The drive dog's special design and the overlapping clamping ranges ensure a safe and reliable driving of all your workpieces. With 8 different sizes, you are able to clamp and drive shafts from  $\text{Ø}5$  mm to  $\text{Ø}100$  mm.

**Attention:** Only use the drive dogs in machines with guard doors!

#### Type DH drive dog




### Clamping principle



#### Consisting of the following features:

- high strength aluminium body
- clamping screw made of unhardened steel
- interchangeable drive pin made of hardened steel

### Technical data - type DH drive dog



type DH	clamping range Ø	D1	B1	L1	cat.-no.
<b>12</b>	5 - 12	26	5	15	<b>710 00</b>
<b>20.5</b>	10 - 20	36	5	20	<b>710 01</b>
<b>20</b>	10 - 20	36	10	20	<b>710 02</b>
<b>32</b>	18 - 32	52	10	25	<b>710 03</b>
<b>46</b>	30 - 46	72	10	30	<b>710 04</b>
<b>62</b>	44 - 62	95	10	35	<b>710 05</b>
<b>82</b>	60 - 82	122	14	40	<b>710 06</b>
<b>100</b>	80 - 100	150	14	45	<b>710 07</b>
<b>set</b>	5 - 100	complete assortment			<b>710 10</b>



# Mandrels



GSD



ISD

<b>Mandrels GSD</b>	<b>102</b>
<b>Mandrels ISD</b>	<b>102</b>

## Mandrels GSD / ISD



### with fixed centering and floating clamping elements

#### Mandrels of type GSD and ISD

The entire surface of the workpiece can be completely machined with one single clamping and with a maximum of torque transmission. NEIDLEIN mandrels are mechanical clamping systems, suitable for turning, hard turning and grinding operations likewise.

Mandrels of type GSD and ISD are power-operated on the side of the machine spindle as well as the side of the tailstock. The workpieces are clamped centrally by the fixed centering. This operation results in high true run-out accuracy.

#### Type GSD sliding jaw mandrel

Type GSD is mounted onto the machine spindle nose using flange-adapter, adjustable for true run-out.



#### Type ISD internal clamping mandrel

Type ISD is mounted onto the machine spindle nose using flange-adapter, adjustable for true run-out.



#### NEIDLEIN mandrels GSD / ISD with fixed centering ensure:

- maximum of torque transmission, thus achieving a high cutting performance
- datum-point location in the center of the workpiece ensures constant measures of length
- run-out deviation in the process 0.005 - 0.01mm
- fixed clamping location
- floating clamping elements
  - » compensating internal clamping
- sliding jaw mandrels GSD available for bore hole diameters starting from  $\varnothing$  18 mm
- internal clamping mandrel ISD available for bore hole diameters starting from  $\varnothing$  10 mm
- changeable centering unit


## Clamping principle

The center pin located on the side of the tailstock pushes the workpiece against the fixed centering of the mandrel. The actuation of the sliding jaws / clamping sleeve against the surface of the workpiece bore hole is initiated by the clamping cylinder mounted into the machine. The sliding jaws / clamping sleeve are "floatingly" suspended, thus compensating irregularities with regard to possible eccentricity of the workpiece bore hole. The datum-point of workpieces on the machines is determined by the size of the centering. The entire surface of the workpiece can now be tooled in one single clamping.

The data for achievable cutting performance and the thrust requested, you can find in the provided documentation or upon request from our technical sales department.

We will be glad to design clamping devices suitable for your workpieces.

### Type GSD / ISD



Sizes and prices of the mandrels and basic retainer upon request



ZF

# Mounting Elements

with appropriate accessories  
for mounting of clamping tools on machine tools



ZFE



RF



RH

<b>Flange Adapters ZF</b>	<b>106</b>
<b>Flange Adapters ZFE (adjustable)</b>	<b>108</b>
<b>Reducing Adapters RF</b>	<b>110</b>
<b>Reducing Sleeves RH / RHZ</b>	<b>112</b>

## Flange Adapters ZF

according to DIN ISO 702-1 (DIN 55028)

for mounting of face drivers type FSB / FSBR / FSP / FDNC


The flange adapter is used for direct mounting of **face drivers with movable center pin** on machine tool spindle noses DIN ISO 702-1 (DIN 55026).

Our flange adapters are made of non-hardened steel. This helps to protect the spindle nose and serves for a better damping property.

### Type ZF with short taper



### Technical data - type ZF with short taper



type ZF	spindle size	D1	D2	D3 for	L	for face drivers FSB / FSBR / FSP / FDNC	cat. no.
5	5	160	82.563	M10	25	01 - 5	742 02
6	6	165	106.375	M12	25	01 - 5	742 04
8	8	220	139.719	M16	60	01 - 55	742 062
11	11	280	196.869	M20	60	01 - 6	742 082

- Adapters are supplied with mounting screws to suit the machine tool spindle nose.
- Other sizes and special adapters are available upon request.
- Hardened flange adapters are available upon request.


## Clamping principle

Face drivers with movable center pin and all other face drivers with retainer  $\varnothing 100$  are mounted onto the machine tool spindle via flange adapter ZF.

Because of the exactly fitting of the mounting diameter  $\varnothing 100$  it is possible to adapt the face driver without adjusting the run out.

For increased run out requirements the face driver should be adjusted in the flange adapter.

### Type ZF with short taper



## Flange Adapters ZFE (adjustable)

according to DIN ISO 702-1 (DIN 55028)  
for mounting face drivers type FFB / FFBH  
und reducing sleeves type RF

The flange adapter is used for direct mounting of **face drivers type FFB and FFBH** with adjustment true. Adaption on machine tool spindle noses DIN ISO 702-1 (DIN 55026).


Our flange adapters are made of non-hardened steel. This helps to protect the spindle nose and serves for a better damping property.

### Type ZFE with short taper

for adjustment at high run out requirements



### Technical data – type ZFE with short taper




type ZFE	spindle size	D1	D2	D3 for	L	for face drivers FFB / FFBH	cat. no.
5	5	160	82.563	M10	40	01 - 5	<b>742 12</b>
6	6	165	106.375	M12	42	01 - 5	<b>742 14</b>
8	8	220	139.719	M16	42	01 - 55	<b>742 16</b>
11	11	280	196.869	M20	60	01 - 6	<b>742 18</b>

- Adapters are supplied with mounting screws to suit the machine tool spindle nose.
- Other sizes and special adapters are available upon request.
- Hardened flange adapters are available upon request.

## Clamping principle

Face drivers of the type FFB / FFBH and all other face drivers with retainer  $\text{D}100$  which need a very precise run out adjustment are mounted onto the machine tool spindle via flange adapter ZFE.

### Type ZFE with short taper




## Reducing Adapters RF

### for mounting clamping tools with morse taper shank

The reducing adapter is used for direct mounting of **face driver type SB**, **pipe driver type NDG** or of **various center pins with morse taper shank**.

#### Type RF with morse taper

#### Technical data – type RF with morse taper




type RF	MK	D1	D2	L	L1	d6	cat. no.
3	3	42	36	15	55	133.4	743 01
4	4	55	40	36	55	133.4	743 02
5	5	68	55	63	55	133.4	743 03
6	6	90	80	75	70	133.4	743 04

- Adapters are supplied with mounting screws to suit the machine tool spindle nose.
- Other sizes and special adapters are available upon request.

## Clamping principle

For mounting a clamping tool with morse taper shank onto a machine tool spindle DIN ISO 702-1, a reducing flange RF is used by mounting it onto the machine tool spindle via flange adapter ZFE (e. g. at a double spindle CNC lathe).

### Type RF with morse taper



## Reducing Sleeves RH / RHZ

### for reducing of morse cone retainers

The reducing sleeve is used for mounting of face driver type SB, pipe driver type NDG or of various center pins with morse taper shank.


#### Type RH with morse taper



#### Type RHZ with cyl. retainer




#### Technical data – type RH with morse taper



type	MK	MK	D	L	cat. no.
RF	outside	inside	screw thread		
4/3	4	3	M35 x 1.5	82	932 09
5/3	5	3	M48 x 1.5	91	932 10
5/4	5	4	M48 x 1.5	91	932 11
6/3	6	3	M70 x 1.5	128	932 12
6/4	6	4	M70 x 1.5	128	932 13
6/5	6	5	M70 x 1.5	128	932 14

■ Other sizes and special sleeves are available upon request.

#### Technical data – type RHZ with cyl. retainer



type	cyl. Ø	MK	D1	L	l	cat. no.
RHZ	D	inside	collar			
35/3	35	3	44	65	8	932 20
41/4	41	4	49	70	8	932 21
61/5	61	5	72	80	10	932 22
85/6	85	6	96	85	10	932 23


■ Other sizes and special sleeves are available upon request.

## Clamping principle


**Reducing sleeve RH** – For retaining a morse cone shank which is smaller than the available tailstock quill or machine tool spindle, a reducing sleeve with matching size is adapted.

**Reducing sleeve RHZ** – For retaining a morse cone shank in a collet chuck or a 3 jaw chuck, a reducing sleeve RHZ with cylindrical retainer is adapted.

### Type RH with morse taper



### Type RHZ with cyl. retainer




## Extracting nut DIN 1804 h - for reducing sleeve RH

### Type DIN 1804 h



### Technical data - type DIN 1804 h



D1	D2	D3	h	cat. no.
M35 x 1.5	47	55	11	<b>830 41</b>
M48 x 1.5	67	75	13	<b>830 43</b>
M70 x 1.5	90	100	14	<b>830 44</b>



RN

RNW and changeable inserts

RNCS with carbide tip

## LIVE CENTERS FOR TURNING AND GRINDING

<b>Ultra Live Centers RN / RNC / RNZ</b>	<b>116</b>
<b>Ultra Live Centers RNA</b>	<b>122</b>
<b>Bullnose Ultra Live Centers RK</b>	<b>124</b>
<b>Bullnose Ultra Live Centers RKA</b>	<b>126</b>
<b>Ultra Live Centers RNW</b>	<b>128</b>
<b>Ultra Live Centers RNF / RNCF</b>	<b>130</b>
<b>Ultra Live Centers RNF / RNCF VDI</b>	<b>132</b>
<b>Ultra Live Centers RNWF MK + VDI</b>	<b>134</b>

## LIVE CENTERS ESPECIALLY FOR GRINDING

<b>Ultra Live Centers RNS / RNCS</b>	<b>136</b>
<b>Load Charts for Live Centers</b>	<b>140</b>

# Live Centers & Dead Centers

with appropriate accessories



RNF VDI



carbide dead center DIN 807



FNA and changeable center cone

## DEAD CENTERS FOR TURNING, HARD TURNING AND GRINDING

<b>Dead Centers FN / FNC / FNZ</b>	<b>145</b>
<b>Dead Center Shanks FNA / FNW</b>	<b>148</b>
<b>Carbide Dead Centers DIN 806</b>	<b>150</b>
<b>Carbide Dead Centers DIN 807</b>	<b>152</b>
<b>Dead Centers FE / FEC – type taper 1:7.5 / Ø 28.33</b>	<b>154</b>
<b>Carbide Bull Nose Cones FNK</b>	<b>156</b>

## ACCESSORIES

<b>Changeable Center Cones for type RNA / FNA</b>	<b>158</b>
<b>Changeable Center Cones for type RKA</b>	<b>159</b>
<b>Changeable Inserts for type RNW / FNW</b>	<b>160</b>

## Ultra Live Centers RN / RNC / RNZ



### for general use

NEIDLEIN ultra live centers are designed for employment in **turning, grinding and other production machine tools.**

Owing to the application of bearing and the stable design high axial and radial load can be absorbed accurately. Therefore our live centers are outstanding for any application, especially for tooling with face drivers.

#### Type RN with morse taper



↑ 0.005

↑ 0.003



with full carbide tip

with half carbide tip

#### NEIDLEIN revolving ultra live centers type RN / RNC ensure:

- application of live centers in case of high thrust and loading
- run-out deviation max.  
0.005 mm · type turning  
0.003 mm · type grinding
- enhanced true running accuracy HQ upon request
- maintenance-free, due to gasket system and life-time lubrication of bearings; gasket system comprising variable seal and steel protection cover
- excellent demounting by means of extracting nut and extracting disk, which ensures safe and easy removal of the live center from the tailstock spindle sleeve

**Type RNC with morse taper**

» **extended tooling clearance**  
for better access of machining tools

↗ **0.005** 

↗ **0.003** 



 with carbide tip

**Type RNZ with morse taper**

» **extended tooling clearance**  
extended version for more tool clearance


↗ **0.005** 

↗ **0.003** 




 **TYPE TURNING**

- with contact-free labyrinth seal
- true running accuracy max. 0.005 guaranteed




 **TYPE GRINDING**

- with contact spindle seal
- true running accuracy max. 0.003 guaranteed



**Technical data – type RN with morse taper**

type tool steel tip


**WITH TOOL STEEL TIP**TYPE  
TURNINGTYPE  
GRINDING

type RN	MK	D1	D2	D4	D5	L1	L2	L3	L4	rpm max. [1/min]	cat. no.	cat. no.
3	3	55	22	M58 x 1.5	23.83	26	102	183	5	6000	<b>812 01</b>	<b>812 0102</b>
	4	55	22	M58 x 1.5	31.27	26	103.5	206	6.5	6000	<b>812 02</b>	<b>812 0202</b>
	5	55	22	M58 x 1.5	44.4	26	103.5	233	6.5	6000	<b>812 03</b>	<b>812 0302</b>
4	4	70	32	M75 x 1.5	31.27	45	131.2	233.7	6.5	5000	<b>812 04</b>	<b>812 0402</b>
	5	70	32	M75 x 1.5	44.4	45	131.2	260.7	6.5	5000	<b>812 05</b>	<b>812 0502</b>
5	5	92	45	M95 x 2	44.4	60	156.2	285.7	6.5	4000	<b>812 06</b>	<b>812 0602</b>
	6	92	45	M95 x 2	63.35	60	157.7	339.7	8	4000	<b>812 07</b>	<b>812 0702</b>
6	6	107	55	M110 x 2	63.35	60	169.7	351.7	8	3000	<b>812 08</b>	<b>812 0802</b>

- Run-out deviation max.: type turning 0.005 mm · type grinding 0.003 mm.
- Extracting nuts and extracting disks see page 172 - 173 for accessories.
- Load chart see page 140.



type full carbide tip


**WITH FULL CARBIDE TIP**TYPE  
TURNINGTYPE  
GRINDING

type RN	MK	D1	D2	D4	D5	L1	L2	L3	L4	rpm max. [1/min]	cat. no.	cat. no.
3	3	55	22	M58 x 1.5	23.83	26	102	183	5	6000	<b>812 0104</b>	<b>812 0106</b>
	4	55	22	M58 x 1.5	31.27	26	103.5	206	6.5	6000	<b>812 0204</b>	<b>812 0206</b>
	5	55	22	M58 x 1.5	44.4	26	103.5	233	6.5	6000	<b>812 0304</b>	<b>812 0306</b>
4	4	70	32	M75 x 1.5	31.27	45	131.2	233.7	6.5	5000	<b>812 0404</b>	<b>812 0406</b>
	5	70	32	M75 x 1.5	44.4	45	131.2	260.7	6.5	5000	<b>812 0504</b>	<b>812 0506</b>
5	5	92	45	M95 x 2	44.4	60	156.2	285.7	6.5	4000	<b>812 0604</b>	<b>812 0606</b>
	6	92	45	M95 x 2	63.35	60	157.7	339.7	8	4000	<b>812 0704</b>	<b>812 0706</b>
6	6	107	55	M110 x 2	63.35	60	169.7	351.7	8	3000	<b>812 0804</b>	<b>812 0806</b>

- Run-out deviation max.: type turning 0.005 mm · type grinding 0.003 mm.
- Extracting nuts and extracting disks see page 172 - 173 for accessories.
- Load chart see page 140.

**Technical data - type RN with morse taper**

**HM** type half carbide tip



**TYPE TURNING**

**TYPE GRINDING**


**WITH HALF CARBIDE TIP**

type RN	MK	D1	D2	D3	D4	D5	L1	L2	L3	L4	rpm max. [1/min]	cat. no.	cat.no
<b>3</b>	<b>3</b>	55	22	11	M58 x 1.5	23.83	26	102	183	5	6000	<b>812 0103</b>	<b>812 0105</b>
	<b>4</b>	55	22	11	M58 x 1.5	31.27	26	103.5	206	6.5	6000	<b>812 0203</b>	<b>812 0205</b>
	<b>5</b>	55	22	11	M58 x 1.5	44.4	26	103.5	233	6.5	6000	<b>812 0303</b>	<b>812 0305</b>
<b>4</b>	<b>4</b>	70	32	14	M75 x 1.5	31.27	45	131.2	233.7	6.5	5000	<b>812 0403</b>	<b>812 0405</b>
	<b>5</b>	70	32	14	M75 x 1.5	44.4	45	131.2	260.7	6.5	5000	<b>812 0503</b>	<b>812 0505</b>
<b>5</b>	<b>5</b>	92	45	22	M95 x 2	44.4	60	156.2	285.7	6.5	4000	<b>812 0603</b>	<b>812 0605</b>
	<b>6</b>	92	45	22	M95 x 2	63.35	60	157.7	339.7	8	4000	<b>812 0703</b>	<b>812 0705</b>
<b>6</b>	<b>6</b>	107	55	28	M110 x 2	63.35	60	169.7	351.7	8	3000	<b>812 0803</b>	<b>812 0805</b>

- Run-out deviation max.: type turning 0.005 mm · type grinding 0.003 mm.
- Extracting nuts and extracting disks see page 172 - 173 for accessories.
- Load chart see page 140.

**Technical data – type RNC with morse taper**

type tool steel tip


TYPE  
TURNINGTYPE  
GRINDING**WITH TOOL STEEL TIP**

type RNC	MK	D1	D2	D3	D4	D5	L1	L2	L3	L4	rpm max. [1/min]	cat. no.	cat. no.
3	3	55	22	10	M58 x 1.5	23.83	32	108	189	5	6000	813 01	813 0102
	4	55	22	10	M58 x 1.5	31.27	32	109.5	212	6.5	6000	813 02	813 0202
	5	55	22	10	M58 x 1.5	44.4	32	109.5	239	6.5	6000	813 03	813 0302
4	4	70	32	16	M75 x 1.5	31.27	45	131.2	233.7	6.5	5000	813 04	813 0402
	5	70	32	16	M75 x 1.5	44.4	45	131.2	260.7	6.5	5000	813 05	813 0502
5	5	92	45	22	M95 x 2	44.4	62	158.2	287.7	6.5	4000	813 06	813 0602
	6	92	45	22	M95 x 2	63.35	62	159.7	341.7	8	4000	813 07	813 0702
6	6	107	55	28	M110 x 2	63.35	72	181.7	363.7	8	3000	813 08	813 0802

- Run-out deviation max.: type turning 0.005 mm · type grinding 0.003 mm.
- Extracting nuts and extracting disks see page 172 - 173 for accessories.
- Load chart see page 140.



type full carbide tip


TYPE  
TURNINGTYPE  
GRINDING**WITH CARBIDE TIP**

type RNC	MK	D1	D2	D3	D4	D5	L1	L2	L3	L4	rpm max. [1/min]	cat. no.	cat. no.
3	3	55	22	10	M58 x 1.5	23.83	32	108	189	5	6000	813 0104	813 0106
	4	55	22	10	M58 x 1.5	31.27	32	109.5	212	6.5	6000	813 0204	813 0206
	5	55	22	10	M58 x 1.5	44.4	32	109.5	239	6.5	6000	813 0304	813 0306
4	4	70	32	16	M75 x 1.5	31.27	45	131.2	233.7	6.5	5000	813 0404	813 0406
	5	70	32	16	M75 x 1.5	44.4	45	131.2	260.7	6.5	5000	813 0504	813 0506
5	5	92	45	22	M95 x 2	44.4	62	158.2	287.7	6.5	4000	813 0604	813 0606
	6	92	45	22	M95 x 2	63.35	62	159.7	341.7	8	4000	813 0704	813 0706
6	6	107	55	28	M110 x 2	63.35	72	181.7	363.7	8	3000	813 0804	813 0806

- Run-out deviation max.: type turning 0.005 mm · type grinding 0.003 mm.
- Extracting nuts and extracting disks see page 172 - 173 for accessories.
- Load chart see page 140.

**Technical data – type RNZ with morse taper**

type tool steel tip



type RNZ	MK	D1	D2	D3	L5	D4	D5	L1	L2	L3	L4	rpm max. [1/min]	cat. no.	cat. no.
3	3	55	22	10	21	M58 x 1.5	23.83	48	124	205	5.0	6000	<b>812 51</b>	<b>812 5102</b>
	4	55	22	10	21	M58 x 1.5	31.27	48	125.5	228	6.5	6000	<b>812 52</b>	<b>812 5202</b>
4	4	70	32	12	26	M75 x 1.5	31.27	54	140.2	242.7	6.5	5000	<b>812 54</b>	<b>812 5402</b>
	5	70	32	12	26	M75 x 1.5	44.4	54	140.2	269.7	6.5	5000	<b>812 55</b>	<b>812 5502</b>
5	5	92	45	14	31	M95 x 1.5	44.4	65	161.2	290.7	6.5	4000	<b>812 56</b>	<b>812 5602</b>
	6	92	45	14	31	M95 x 1.5	63.35	65	162.7	344.7	8.0	4000	<b>812 57</b>	<b>812 5702</b>

- Run-out deviation max.: type turning 0.005 mm - type grinding 0.003 mm.
- Extracting nuts and extracting disks see page 172-173 for accessories.
- Load chart see page 141.

## Ultra Live Centers RNA



### high flexibility at large workpiece center holes

NEIDLEIN ultra live centers type RNA are designed for employment in **turning, grinding and other production machines**.

#### Type RNA with morse taper

high degree of flexibility for clamping of workpieces with large centers



**0.01**

incl. center cone



changeable center cone  
see page 158


#### NEIDLEIN revolving ultra live centers type RNA ensure:

- application of live centers in case of high thrust and loading
- run-out deviation max.: 0.01 mm incl. center cone
- easy exchange of center cones using SK30 short taper interface and cylinder screw
- maintenance-free, due to gasket system and life-time lubrication of bearings; gasket system comprising variable seal and steel comprehensive protection cover
- excellent demounting by means of extracting nut and extracting disk, which ensures safe and easy removal of the live center from the tailstock spindle sleeve




#### TYPE TURNING

- with contact-free labyrinth seal




#### TYPE GRINDING

- with contact spindle seal



### Technical data - type RNA with morse taper



TYPE  
TURNING



TYPE  
GRINDING

type RNA	MK	D1	D4	D5	L1	L2	L3	L4	rpm max. [1 / min]	cat. no.	cat. no.
4	4	70	M75 x 1.5	31.27	41	127	229.5	6.5	6000	<b>814 04</b>	<b>814 0402</b>
	5	70	M75 x 1.5	44.4	41	127	256.5	6.5	6000	<b>814 05</b>	<b>814 0502</b>
5	5	92	M95 x 2	44.4	41	137.2	266.7	6.5	5000	<b>814 06</b>	<b>814 0602</b>
	6	92	M95 x 2	63.35	41	138.7	320.7	8	5000	<b>814 07</b>	<b>814 0702</b>
6	6	107	M110 x 2	63.35	41	151.7	333.7	8	3000	<b>814 08</b>	<b>814 0802</b>

- Run-out deviation max.: 0.01 mm incl. center cone.
- Variety of center cones ranging from Ø 25 to Ø 315, see page 158.
- Special cones up to Ø 400 available upon customer's request.
- Extracting nuts and extracting disks see page 172 - 173 for accessories.
- Speed-dependent load see page 140.

## Bullnose ultra live centers RK



### for work pieces with large center holes

NEIDLEIN bullnose ultra live centers type RK are characterized by a large clamping range and therefore they can cover large work piece center holes.

The clamping system allows for a high degree of flexibility. It enables clamping of work pieces with center hole sizes from  $\varnothing 6$  to  $\varnothing 340$ . Due to the heavy duty bearing system, work pieces up to 5000 kg can be clamped.

#### Type RK with morse taper




↑ **0.005**  
type RK3 + RK4

↑ **0.007**  
type RK5

↑ **0.01 - 0.02**  
type RK6

#### NEIDLEIN bullnose ultra live centers type RK ensure:

- high flexibility due to the large diameter range
- run-out deviation max.: 0.005 - 0.02 (depending onto type)
- high true run accuracy even when using low axial forces
- use in case of high thrust and loads
- maintenance free due to gasket system and life-time lubrication of the bearings; gasket system by use of a shaft seal ring
- excellent demounting by means of extracting nut, which ensures safe and easy removal of the bull nose live center from the tailstock spindle sleeve

**Technical data - type RK with morse taper**


type RK	MK	D1	D2	D3	D4	L1	L2	L3	rpm. max (1/min.)	cat. no.
<b>3</b>	<b>2</b>	70	2	M22 x 1.5	17.78	93	157	15.5	3000	<b>820 00</b>
	<b>3</b>	70	2	M28 x 1.5	23.83	93.5	174.5	16	3000	<b>820 01</b>
	<b>4</b>	70	2	M35 x 1.5	31.27	95	197.5	17.5	3000	<b>820 02</b>
<b>4</b>	<b>4</b>	100	30	M35 x 1.5	31.27	103	205.5	17.5	2500	<b>820 03</b>
	<b>5</b>	100	30	M48 x 1.5	44.4	105	234.5	19.5	2500	<b>820 04</b>
<b>5</b>	<b>4</b>	160	90	M35 x 1.5	31.27	135.5	238	17.5	2000	<b>820 05</b>
	<b>5</b>	160	90	M48 x 1.5	44.4	137.5	267	19.5	2000	<b>820 06</b>
	<b>6</b>	160	90	M70 x 1.5	63.35	140	322	22	2000	<b>820 07</b>
<b>6</b>	<b>5</b>	220	150	M48 x 1.5	44.4	157.5	287	19.5	1500	<b>820 08</b>
	<b>6</b>	220	150	M70 x 1.5	63.35	160	342	22	1500	<b>820 09</b>
	<b>6</b>	280	210	M70 x 1.5	63.35	160	342	22	1500	<b>820 10</b>

- load chart see page 141.
- At speeds lower than 500 rpm and high loads, upon request it's possible to use a heavy duty grease for lubrication of the bearings
- The extraction nut is included.



## Bullnose ultra live centers RKA

### for heavy workpieces with large centers

NEIDLEIN bullnose ultra live centers type RKA are designed for heavy workpieces with large centers.

The modular clamping system allows for a high degree of flexibility. It enables clamping of workpieces with centers from  $\varnothing 50$  to  $\varnothing 460$ .

#### Type RKA basic retainer with morse taper



 **0.005**


without center cone

 **0.02**

incl. center cone



changeable center cones  
see page 159

**Technical data - type RKA basic retainer with morse taper**


type	MK	D4	D5	L2	L3	L4	rpm max. [1 / min]	cat. no.
RKA								
6	5	M48 x 1.5	44.4	159.5	289	19.5	2500	<b>814 09</b>
	6	M70 x 1.5	63.35	162.5	344.5	22	2500	<b>814 10</b>

- Run-out deviation max.: 0.005 mm without center cone - 0.02 mm incl. center cone.
- Workpieces with centers between Ø50 and Ø115 can be clamped using the basic retainer. In this case the max. radial loads (see page 142) must be reduced by 50%.
- Special basic retainer available upon customer's request.
- Basic retainer including extraction nut.
- Accessories on page 159.
- Load chart see page 142.

## Ultra Live Centers RNW



### high flexibility by using different changable inserts

NEIDLEIN ultra live centers type RNW are designed for employment **in turning, grinding and other production machines.**

#### Type RNW with morse taper

the adaptation of various changeable inserts ensures a high degree of flexibility and saving of costs

 **0.01**  
incl. insert



changeable inserts  
see page 160 - 161


#### NEIDLEIN revolving ultra live centers type RNW ensure:

- application of live centers in case of high thrust and loading
- run-out deviation max.: 0.01 mm incl. insert
- easy exchange of changeable inserts using spanner flat and open-end wrench or Tommy bar
- maintenance-free, due to gasket system and life-time lubrication of bearings; gasket system comprising variable seal and steel comprehensive protection cover
- excellent demounting by means of extracting nut and extracting disk, which ensures safe and easy removal of the live center from the tailstock spindle sleeve




#### TYPE TURNING


- with contact-free labyrinth seal



#### TYPE GRINDING

- with contact spindle seal



**Technical data - type RNW with morse taper**

**TYPE  
TURNING**

**TYPE  
GRINDING**

type RNW	MK	D1	D2	D3	D4	D5	L1	L2	L3	L4	rpm max. [1/min]	cat. no.	cat. no.
<b>3</b>	<b>3</b>	55	22	16	M58 x 1.5	23.83	6.3	82	163	5	6000	<b>815 01</b>	<b>815 0102</b>
	<b>4</b>	55	22	16	M58 x 1.5	31.27	6.3	83.5	186	6.5	6000	<b>815 02</b>	<b>815 0202</b>
	<b>5</b>	55	22	16	M58 x 1.5	44.4	6.3	83.5	213	6.5	6000	<b>815 03</b>	<b>815 0302</b>
<b>4</b>	<b>4</b>	70	32	16	M75 x 1.5	31.27	8.3	94.5	197	6.5	5000	<b>815 04</b>	<b>815 0402</b>
	<b>5</b>	70	32	16	M75 x 1.5	44.4	8.3	94.5	224	6.5	5000	<b>815 05</b>	<b>815 0502</b>
<b>5</b>	<b>5</b>	92	45	22	M95 x 2	44.4	10.3	106.5	236	6.5	4000	<b>815 06</b>	<b>815 0602</b>
	<b>6</b>	92	45	22	M95 x 2	63.35	10.3	108	290	8	4000	<b>815 07</b>	<b>815 0702</b>
<b>6</b>	<b>6</b>	107	55	22	M110 x 2	63.35	10.3	120	302	8	3000	<b>815 08</b>	<b>815 0802</b>

- Run-out deviation max.: 0.01 mm incl. insert.
- Various changeable inserts of different designs, see page 160 - 161.
- Special inserts available upon customer's request.
- Extracting nuts and extracting disks see page 172 - 173 for accessories.
- Speed-dependent load see page 142.



## Ultra Live Centers RNF / RNCF

### spring loaded live center

NEIDLEIN ultra live centers type RNF are especially suitable for **employment in turrets, in manual tailstocks and in case of linear thermal extension of workpieces.**

The spring loaded, moving spindle and the engraved scale rings enable the adjustment and/or programming of various axial forces.

#### Type RNF with morse taper

↑ 0.003



#### Type RNCF with morse taper

» extended tooling clearance  
for better access of machining tools

↑ 0.003




#### NEIDLEIN ultra live centers type RNF / RNCF ensure:

- employment of live centers in turrets and manual tailstocks when hydraulic systems cannot guarantee any repositioning
- compensation if there is a linear thermal extension of workpieces or if the extension is caused by the process of machining
- run-out deviation max.: 0.003 mm
- maintenance free, due to the gasket system and the lifetime lubrication filling of the bearing
- obtaining of the axial forces applied via scale rings as well as clarification of the force ranges on the outside of the housing



Example type RNF 4 MK4


**Technical data - type RNF with morse taper**



type RNF	MK	D1	D2	D3	D5	L1	L2	L3	L4	rpm max. [1/min]	cat. no.
3	3	55	25	-	23.83	28.5	84.5	165	5	4500	817 01
	4	55	25	-	31.27	28.5	86	185.5	6.5	4500	817 02
	5	55	25	-	44.4	28.5	86	215.5	6.5	4500	817 03
4	4	68	35	-	31.27	40	109.5	210.3	6.5	4000	817 04
	5	68	35	-	44.4	40	109.5	239	6.5	4000	817 05
5	5	92	50	-	44.4	53	138.5	268	6.5	3500	817 09

- Run-out deviation max.: 0.003 mm.
- Models with extraction thread or with special spindles are available upon customer's request.
- Load chart see page 143.

**Technical data - type RNCF with morse taper**



type RNCF	MK	D1	D2	D3	D5	L1	L2	L3	L4	rpm max. [1/min]	cat. no.
3	3	55	25	12	23.83	37	93	173.5	5	4500	818 01
	4	55	25	12	31.27	37	94.5	194	6.5	4500	818 02
	5	55	25	12	44.4	37	94.5	224	6.5	4500	818 03
4	4	68	35	14	31.27	49	118.5	219.3	6.5	4000	818 04
	5	68	35	14	44.4	49	118.5	248	6.5	4000	818 05
5	5	92	50	22	44.4	65	150.5	280	6.5	3500	818 09

- Run-out deviation max.: 0.003 mm.
- Models with extraction thread or with special spindles are available upon customer's request.
- Load chart see page 143.



## Ultra Live Centers RNF / RNCF VDI

### spring loaded live center with VDI retainer

NEIDLEIN ultra live centers type RNF/RNCF VDI are adapted in the tool turret and are **especially suited for CNC machines without tailstock or with sub spindle.**

The spring loaded, moving spindle and the engraved scale rings enable the adjustment and/or programming of various axial forces.

#### Type RNF with VDI retainer

↑ 0.003



#### Type RNCF with VDI retainer

» extended tooling clearance  
for better access of machining tools

↑ 0.003



#### NEIDLEIN ultra live centers type RNF / RNCF VDI ensure:


- employment of live centers in turrets when hydraulic systems cannot guarantee any repositioning
- compensation if there is a linear thermal extension of workpieces or if the extension is caused by the process of machining
- run-out deviation max.: 0.003 mm
- maintenance free, due to the gasket system and the lifetime lubrication filling of the bearing
- obtaining of the axial forces applied via scale rings as well as clarification of the force ranges on the outside of the housing



Example type RNF 4 VDI 40

**Technical data - type RNF with VDI retainer**

DIN ISO 10889-1




type RNF	VDI	D1	D2	D3	D4	L1	L2	L3	rpm max. [1/min]	cat. no.
3	30	55	25	-	68	28.5	84.5	139.5	4500	817 06
	40	55	25	-	83	28.5	84.5	147.5	4500	817 07
4	40	68	35	-	83	40	108	171	4000	817 08

- Run-out deviation max.: 0.003 mm.
- Load chart see page 143.

**Technical data - type RNCF with VDI retainer**

DIN ISO 10889-1



type RNCF	VDI	D1	D2	D3	D4	L1	L2	L3	rpm max. [1/min]	cat. no.
3	30	55	25	12	68	37	93	148	4500	818 06
	40	55	25	12	83	37	93	156	4500	818 07
4	40	68	35	14	83	49	117	180	4000	818 08

- Run-out deviation max.: 0.003 mm.
- Load chart see page 143.



## Ultra Live Centers RNWF MK + VDI

### spring loaded live center with morse taper and VDI retainer

NEIDLEIN ultra live centers type RNWF are especially suitable for **employment in turrets, in manual tailstocks and in case of linear thermal extension of workpieces.**

The spring loaded, moving spindle and the engraved scale rings enable the adjustment and/or programming of various axial forces.

#### Type RNWF with morse taper

the adaptation of various changeable inserts ensures a high degree of flexibility and saving of costs

↑ **0.01**  
incl. insert



#### Type RNWF with VDI retainer

↑ **0.01**  
incl. insert




changeable inserts  
see page 160-161

#### NEIDLEIN ultra live centers type RNWF ensure:

- employment of live centers in turrets and manual tailstocks when hydraulic systems cannot guarantee any repositioning
- compensation if there is a linear thermal extension of workpieces or if the extension is caused by the process of machining
- run-out deviation max.: 0.01 mm incl. insert
- easy exchange of changeable inserts using spanner flat and open-end wrench or Tommy bar
- maintenance free, due to the gasket system and the lifetime lubrication filling of the bearing
- obtaining of the axial forces applied via scale rings as well as clarification of the force ranges on the outside of the housing



**Technical data - type RNWF with morse taper**




type RNWF	MK	D1	D2	D3	D5	L1	L2	L3	L4	rpm max. [1/min]	cat. no.
3	3	55	25	16	23.83	6	62	142.5	5	4500	<b>818 15</b>
	4	55	25	16	31.27	6	63.5	163	6.5	4500	<b>818 16</b>
	5	55	25	16	44.4	6	63	193	6.5	4500	<b>818 17</b>
4	4	68	35	16	31.27	8	77.5	178.3	6.5	4000	<b>818 18</b>
	5	68	35	16	44.4	8	77.5	207	6.5	4000	<b>818 19</b>
5	5	92	50	22	44.4	10	95.5	225	6.5	3500	<b>818 20</b>

- Run-out deviation max.: 0.01 mm with insert.
- Models with extraction thread or with special spindles are available upon customer's request.
- Load chart see page 143.
- Various changeable inserts of different designs, see page 160 - 161.

**Technical data - type RNWF with VDI retainer**

DIN ISO 10889-1



type RNWF	VDI	D1	D2	D3	D4	L1	L2	L3	rpm max. [1/min]	cat. no.
3	30	55	25	16	68	6	62	117	4500	<b>818 21</b>
	40	55	25	16	83	6	62	125	4500	<b>818 22</b>
4	40	68	35	16	83	8	76	139	4000	<b>818 23</b>

- Run-out deviation max.: 0.01 mm with insert.
- Load chart see page 143.
- Various changeable inserts of different designs, see page 160 - 161.



## Ultre Live Centers RNS / RNCS

### especially for grinding operations

NEIDLEIN ultra live centers type RNS / RNCS are **especially suited for the use in grinding and other production machine tools.**

By the specific arrangement of the bearings, the design of the live centers is very short and also the live centers can be

used for precise clamping of heavy workpieces with high axial forces. Therefore they are ideal for every use, especially in combination with face drivers.

#### Type RNS with morse taper

 0.003



with carbide tip  
for hardened workpieces  
and high production quantities

#### NEIDLEIN ultra live centers RNS / RNCS ensure:


- short projection length
- run-out deviation max.: 0.003 mm
- high true run accuracy even when using low axial forces
- application of live centers in case of high axial and radial loads
- maintenance free, due to the gasket system and the lifetime lubrication of the bearings
- easy and safe removal by means of extracting nut and extracting disk

**Type RNCS with morse taper**

» **extended tooling clearance**  
for better access of machining tools

**0.003**

with carbide tip  
for hardened workpieces  
and high production quantities

**Technical data – type RNS with morse taper**


type caride tip


**TYPE  
TOOL STEEL**


**TYPE  
CARBIDE**

type RNS	MK	D1	D2	D4	D5	L1	L2	L3	L4	rpm max. [1/min]	cat. no.
<b>1</b>	<b>2</b>	34	18	M36 x 1.5	17.78	20	61	125	5	6000	<b>818 97</b>
	<b>3</b>	34	18	M36 x 1.5	23.83	20	61	142	5	6000	<b>818 98</b>
<b>2</b>	<b>3</b>	42	22	M48 x 1.5	23.83	25	72	152.5	5	5500	<b>818 99</b>
	<b>4</b>	42	22	M48 x 1.5	31.27	25	73.5	173	6.5	5500	<b>819 00</b>
<b>3</b>	<b>3</b>	55	25	M58 x 1.5	23.83	28	74.5	155	5	4500	<b>819 01</b>
	<b>4</b>	55	25	M58 x 1.5	31.27	28	76	175.5	6.5	4500	<b>819 02</b>
	<b>5</b>	55	25	M58 x 1.5	44.4	28	76	205.5	6.5	4500	<b>819 03</b>
<b>4</b>	<b>4</b>	68	35	M75 x 1.5	31.27	40	96	197	6.5	4000	<b>819 04</b>
	<b>5</b>	68	35	M75 x 1.5	44.4	40	96	225.5	6.5	4000	<b>819 05</b>
<b>5</b>	<b>5</b>	92	50	M95 x 2	44.4	53	119	248.5	6.5	3600	<b>819 06</b>

**cat. no.**
**818 9706****818 9806****818 9906****819 0006****819 0106****819 0206****819 0306****819 0406****819 0506****819 0606**

- Run-out deviation max.: 0.003 mm.
- Extracting nuts and extracting disks see page 172 - 173 for accessories.
- Load chart see page 144.

**Technical data - type RNCS with morse taper**



**HM** type caride tip



**TYPE TOOL STEEL**

**HM TYPE CARBIDE**

type RNCS	MK	D1	D2	D3	D4	D5	L1	L2	L3	L4	rpm max. [1/min]	cat. no.
1	2	34	18	6	M36 x 1.5	17.78	26	67	131	5	6000	819 17
	3	34	18	6	M36 x 1.5	23.83	26	67	148	5	6000	819 18
2	3	42	22	10	M48 x 1.5	23.83	29	76	156.5	5	5000	819 19
	4	42	22	10	M48 x 1.5	31.27	29	77.5	177	6.5	5000	819 20
3	3	55	25	12	M58 x 1.5	23.83	37	83.5	164	5	4500	819 21
	4	55	25	12	M58 x 1.5	31.27	37	85	186.5	6.5	4500	819 22
	5	55	25	12	M58 x 1.5	44.4	37	85	214.5	6.5	4500	819 23
4	4	68	35	14	M75 x 1.5	31.27	49	105.5	206	6.5	4000	819 24
	5	68	35	14	M75 x 1.5	44.4	49	105	234.5	6.5	4000	819 25
5	5	92	50	22	M95 x 2	44.4	65	131	260.5	6.5	3600	819 26

cat. no.
819 1706
819 1806
819 1906
819 2006
819 2106
819 2206
819 2306
819 2406
819 2506
819 2606

- Run-out deviation max.: 0.003 mm.
- Extracting nuts and extracting disks see page 172 - 173 for accessories.
- Load chart see page 144.

## Load Charts for Live Centers

**TYPE RN** tool steel and with full carbide tip

**TYPE RNC / RNZ / RNA** tool steel

type	rpm [1/min]	typ of load	load [daN]	max. load [daN]	max. workpiece weight [daN]
3	250	radial	110	110	220
	500		90		
	1000		70		
	2000		50		
	4000		30		
	6000		10		
	250	axial	600	600	
	500		600		
	1000		600		
	2000		500		
4000	400				
6000	350				
4	250	radial	250	250	500
	500		210		
	1000		170		
	2000		120		
	3500		70		
	5000		20		
	250	axial	900	900	
	500		900		
	1000		700		
	2000		600		
3500	500				
5000	500				
5	250	radial	600	600	1200
	500		520		
	1000		420		
	2000		310		
	3000		200		
	4000		50		
	250	axial	1500	1500	
	500		1400		
	1000		1300		
	2000		1100		
3000	900				
4000	700				
6	250	radial	750	750	1500
	500		650		
	1000		520		
	2000		360		
	3000		200		
	250		axial		
	500	2000			
	1000	1600			
	2000	1400			
	3000	1200			

- The max. load is based on a bearing service life of min. 2000 operating hours.
- Higher loads are possible for short periods.

**TYPE RN** with half carbide tip

**TYPE RNC** with carbide tip

type	rpm [1/min]	typ of load	load [daN]	max. load [daN]	max. workpiece weight [daN]
3	250	radial	75	75	150
	500		65		
	1000		55		
	2000		40		
	4000		25		
	6000		10		
	250	axial	600	600	
	500		600		
	1000		600		
	2000		500		
4000	400				
6000	350				
4	250	radial	150	150	300
	500		130		
	1000		110		
	2000		85		
	3500		60		
	5000		20		
	250	axial	900	900	
	500		900		
	1000		700		
	2000		600		
3500	500				
5000	500				
5	250	radial	300	300	600
	500		250		
	1000		200		
	2000		150		
	3000		100		
	4000		40		
	250	axial	1500	1500	
	500		1400		
	1000		1300		
	2000		1100		
3000	900				
4000	700				
6	250	radial	450	450	900
	500		380		
	1000		300		
	2000		220		
	3000		120		
	250		axial		
	500	2000			
	1000	1600			
	2000	1400			
	3000	1200			

- The max. load is based on a bearing service life of min. 2000 operating hours.
- Higher loads are possible for short periods.

## TYPE RNZ tool steel

type	rpm [1/min]	typ of load	load [daN]	max. load [daN]	max. workpiece weight [daN]
3	250	radial	30	30	60
	500		25		
	1000		20		
	2000		15		
	4000		10		
	6000		5		
	250	axial	500	500	
	500		500		
	1000		450		
	2000		400		
4000	350				
6000	300				
4	250	radial	45	45	90
	500		40		
	1000		35		
	2000		30		
	3500		20		
	5000		10		
	250	axial	700	700	
	500		700		
	1000		650		
	2000		600		
3500	500				
5000	450				
5	250	radial	75	75	150
	500		70		
	1000		60		
	2000		50		
	3000		40		
	4000		25		
	250	axial	1200	1200	
	500		1200		
	1000		1200		
	2000		1100		
3000	900				
4000	700				

- The max. load is based on a bearing service life of min. 2000 operating hours.
- Higher loads are possible for short periods.

## TYPE RK

type	rpm [1/min]	typ of load	load [daN]	max. load [daN]	max. workpiece weight [daN]			
3	500	radial	150	150	300			
	1000		110					
	2000		70					
	3000		30					
	500		600			600		
	1000		550					
	2000	400						
	3000	300						
	4	500	radial	400			400	800
		1000		300				
1800		200						
2500		100						
500		1000		1000				
1000		800						
1800		700						
2500		600						
5		250	radial		1500*	1500*	3000*	
		500			1000*			
	1000	600*						
	1500	300						
	250	2500		2500				
	500	2500						
	1000	2000						
	1500	1500						
	6	250	radial		2500**	2500**		5000**
		500			2000**			
800		1500**						
1200		1000						
250		3500		3500				
500		3000						
800		2500						
1200		2000						

- The max. load is based on a bearing service life of min. 2000 operating hours.
- Higher loads are possible for short periods.
- \* In version MK4 the max. radial load is 400daN (=work piece weight 800daN) and in version MK5 the max. radial load is 1000daN (=work piece weight 2000daN)
- \*\* in version MK5 the max. radial load is 1000daN (=work piece weight 2000daN)

## Load Charts for Live Centers

### TYPE RKA

type	rpm [1/min]	typ of load	load [daN]	max. load [daN]	max. workpiece weight [daN]
<b>6</b>	250	radial	1000*	1000	2000
	500		850*		
	1000		700*		
	1500		500*		
	2000		300*		
<b>MK5</b>	250	axial	2000	2000	2000
	500		2000		
	1000		1600		
	1500		1400		
	2000		1000		
<b>6</b>	250	radial	1250*	1250	2500
	500		1100*		
	1000		900*		
	1500		650*		
	2000		350*		
<b>MK6</b>	250	axial	2000	2000	2500
	500		2000		
	1000		1600		
	1500		1400		
	2000		1000		

- The max. load is based on a bearing service life of min. 2000 operating hours.
- Higher loads are possible for short periods.
- \* When just using the basic retainer for work piece clamping (up to  $\sigma$  115) the declared loads must be reduced by 50%.

### TYPE RNW tool steel

type	rpm [1/min]	typ of load	load [daN]	max. load [daN]	max. workpiece weight [daN]
<b>3</b>	250	radial	110	110	220
	500		90		
	1000		70		
	2000		50		
	4000		30		
<b>3</b>	6000	axial	10	600	220
	250		600		
	500		600		
	1000		600		
	2000		500		
<b>4</b>	4000	radial	400	150	300
	6000		350		
	250		150		
	500		130		
	1000		110		
<b>4</b>	2000	axial	90	900	300
	3500		70		
	5000		20		
	250		900		
	500		900		
<b>5</b>	1000	radial	700	325	650
	2000		600		
	3500		500		
	5000		500		
	250		325		
<b>5</b>	500	axial	280	1200	650
	1000		250		
	2000		200		
	3000		160		
	4000		50		
<b>6</b>	250	radial	1200	325	650
	500		1200		
	1000		1200		
	2000		1100		
	3000		900		
<b>6</b>	4000	axial	700	1200	650
	250		325		
	500		280		
	1000		250		
	2000		200		
<b>6</b>	3000	radial	160	325	650
	250		1200		
	500		1200		
	1000		1200		
	2000		1200		
<b>6</b>	3000	axial	1200	1200	650
	250		325		
	500		280		
	1000		250		
	2000		200		

- The max. load is based on a bearing service life of min. 2000 operating hours.
- Higher loads are possible for short periods.

**TYPE RNF / RNCF**

type	rpm [1/min]	typ of load	load [daN]	max. load [daN]	max. workpiece weight [daN]		
<b>3</b>	250	radial	150	150	300		
	500		130				
	1000		105				
	1800		80				
	3000		50				
	4500	15					
	<b>4</b>	250	axial	650		650	700
		500		550			
		1000		450			
		1800		400			
3000		330					
4500		250					
<b>5</b>		250	radial	350	350	1300	
		500		300			
		1000		250			
		1800		190			
	2800	110					
	4000	40					
	<b>6</b>	250	axial	800	800		1350
		500		700			
		1000		600			
		1800		500			
2800		400					
4000		300					
<b>7</b>		250	radial	650	650	650	
		500		540			
		900		420			
		1600		290			
	2400	160					
	3500	60					
	<b>8</b>	250	axial	1350	1350		650
		500		1200			
		900		1000			
		1600		800			
2400		700					
3500		600					

- The max. load is based on a bearing service life of min. 2000 operating hours.
- Higher loads are possible for short periods.

**TYPE RNWF**

type	rpm [1/min]	typ of load	load [daN]	max. load [daN]	max. workpiece weight [daN]		
<b>3</b>	250	radial	75	75	150		
	500		65				
	1000		50				
	1800		40				
	3000		30				
	4500	15					
	<b>4</b>	250	axial	650		650	350
		500		550			
		1000		450			
		1800		400			
3000		330					
4500		250					
<b>5</b>		250	radial	175	175	650	
		500		150			
		1000		130			
		1800		110			
	2800	85					
	4000	40					
	<b>6</b>	250	axial	800	800		650
		500		700			
		1000		600			
		1800		500			
2800		400					
4000		300					
<b>7</b>		250	radial	325	325	650	
		500		280			
		900		250			
		1600		200			
	2400	160					
	3500	60					
	<b>8</b>	250	axial	1350	1350		650
		500		1200			
		900		1000			
		1600		800			
2400		700					
3500		600					

- The max. load is based on a bearing service life of min. 2000 operating hours.
- Higher loads are possible for short periods.

## TYPE RNS tool steel and with carbide tip

## TYPE RNCS tool steel

type	rpm [1/min]	typ of load	load [daN]	max. load [daN]	max. workpiece weight [daN]
1	250	radial	50	50	100
	500		40		
	1000		30		
	2000		20		
	3900		10		
	6000	5			
	250	axial	250	250	
	500		200		
	1000		180		
	2000		160		
3900	130				
6000	120				
2	250	radial	125	125	250
	500		105		
	1000		85		
	2000		60		
	3500		35		
	5500	10			
	250	axial	380	380	
	500		320		
	1000		280		
	2000		260		
3500	190				
5500	100				
3	250	radial	150	150	300
	500		130		
	1000		105		
	2000		80		
	3200		50		
	4500	15			
	250	axial	550	550	
	500		450		
	1000		400		
	2000		330		
3200	250				
4500	200				
4	250	radial	350	350	700
	500		300		
	1000		250		
	1800		190		
	2800		110		
	4000	40			
	250	axial	800	800	
	500		700		
	1000		600		
	1800		500		
2800	400				
4000	300				
5	250	radial	650	650	1300
	500		540		
	1000		420		
	1700		290		
	2500		160		
	3600	60			
	250	axial	1400	1400	
	500		1350		
	1000		1100		
	1700		900		
2500	700				
3600	600				

- The max. load is based on a bearing service life of Min. 2000 operating hours.
- Higher loads are possible for short periods.

## TYPE RNCS with carbide tip

type	rpm [1/min]	typ of load	load [daN]	max. load [daN]	max. workpiece weight [daN]
1	250	radial	25	25	50
	500		22		
	1000		18		
	2000		15		
	3900		10		
	6000	5			
	250	axial	250	250	
	500		200		
	1000		180		
	2000		160		
3900	130				
6000	120				
2	250	radial	50	50	100
	500		45		
	1000		40		
	2000		30		
	3900		20		
	6000	8			
	250	axial	380	380	
	500		320		
	1000		280		
	2000		260		
3500	190				
5500	100				
3	250	radial	100	100	200
	500		90		
	1000		75		
	2000		60		
	3200		40		
	4500	12			
	250	axial	550	550	
	500		450		
	1000		400		
	2000		330		
3200	250				
4500	200				
4	250	radial	150	150	300
	500		130		
	1000		110		
	1800		80		
	2800		50		
	4000	15			
	250	axial	800	800	
	500		700		
	1000		600		
	1800		500		
2800	400				
4000	300				
5	250	radial	300	300	600
	500		260		
	1000		210		
	1700		150		
	2500		90		
	3600	30			
	250	axial	1500	1500	
	500		1350		
	1000		1100		
	1700		900		
2500	700				
3600	600				

- The max. load is based on a bearing service life of Min. 2000 operating hours.
- Higher loads are possible for short periods.

## Dead Centers FN / FNC / FNZ



### for general use

For rotating and fixed tailstock spindle sleeve. Designed for employment **in turning, grinding and other production machines.**

#### Type FN with morse taper

» can be reground



0.002



#### Type FNC with morse taper

» extended tooling clearance  
for better access of machining tools



0.002



- Run-out deviation max.: 0.002 mm.
- Made of fully hardened tool-steel.
- All types with extracting thread to prevent spindle ball bearings or solid spindle sleeves from damage.
- Extracting nuts DIN 807, see page 173.
- Max. load of the dead centers upon request.
- Special design upon request.

#### Type FNZ with morse taper

» can be reground


for general use with extended length for better tool clearance




0.002




- Run-out deviation max.: 0.002 mm.
- Made of fully hardened tool-steel.
- With cylindrical set down and extended length for better tool clearance
- All types with extracting thread to prevent spindle ball bearings or solid spindle sleeves from damage.
- Extracting nuts DIN 807, see page 173.
- Max. load of the dead centers upon request.
- Special design upon request.

**Technical data – type FN with morse taper**

**TYPE FN**

MK	D1	D2	D3	L1	L2	cat. no.
<b>3</b>	24	M27 x 1.5	-	138	57	<b>920 01</b>
<b>4</b>	31.6	M36 x 1.5	-	175	72	<b>920 02</b>
<b>5</b>	44.7	M48 x 1.5	-	217	87	<b>920 03</b>
<b>6</b>	63.8	M68 x 1.5	-	290	108	<b>920 04</b>

**Technical data – type FNC with morse taper**

**TYPE FNC**

MK	D1	D2	D3	L1	L2	cat. no.
<b>3</b>	24	M27 x 1.5	10	148	67	<b>921 01</b>
<b>4</b>	31.6	M36 x 1.5	14	187	84	<b>921 02</b>
<b>5</b>	44.7	M48 x 1.5	16	242	112	<b>921 03</b>
<b>6</b>	63.8	M68 x 1.5	20	330	148	<b>921 04</b>

**Technical data – type FNZ with morse taper**

**TYPE FNZ**

MK	D1	D2	D3	L1	L2	L3	β	cat. no.
<b>2</b>	18	M22x1.5	9	120	56	17	40	<b>921 10</b>
	18	M22x1.5	11	120	56	21	40	<b>921 11</b>
<b>3</b>	24	M27x1.5	9	150	69	17	40	<b>921 12</b>
	24	M27x1.5	13	150	69	25	40	<b>921 13</b>
<b>4</b>	31.6	M36x1.5	9	190	87.5	17	40	<b>921 14</b>
	31.6	M36x1.5	13	190	87.5	27	40	<b>921 15</b>
	31.6	M36x1.5	19	190	87.5	53	90	<b>921 16</b>
<b>5</b>	44.7	M48x1.5	19	245	115	53	40	<b>921 17</b>
	44.7	M48x1.5	28	245	115	65	60	<b>921 18</b>



## Dead Center Shanks FNA / FNW

### high flexibility at different workpiece center holes

#### Type FNA with morse taper

##### » for large workpiece centers

high degree of flexibility for clamping of workpieces with large centers



0.01

incl. center cone



changeable center cones  
see page 158

- Run-out deviation max.: 0.01 mm incl. center cone.
- Different types of center cones from Ø 25 to Ø 315, see page 158.
- Special center cones up to Ø 400 available upon customer's request.
- Extracting nuts DIN 807, see page 173.
- Max. load of the dead centers upon request.

#### Type FNW with morse taper

##### » maximum flexibility

the adaptation of various changeable inserts ensures a high degree of flexibility and saving of costs



0.01


incl. insert



changeable inserts  
see page 160 - 161

- Run-out deviation max.: 0.01 mm incl. insert.
- Various changeable inserts of different designs, see page 160 - 161.
- Special inserts available upon customer's request.
- Extracting nuts, see page 173 for accessories.
- Max. load of the dead centers upon request.


**Technical data - type FNA with morse taper**



**TYPE FNA**

MK	D1	D2	D3	L1	L2	cat. no.
3	32	M27 x 1.5	-	149	68	<b>922 01</b>
4	32	M36 x 1.5	-	173.5	71	<b>922 02</b>
5	45	M48 x 1.5	-	202.5	73	<b>922 03</b>
6	64	M68 x 1.5	-	263.5	81.5	<b>922 04</b>

**Technical data - type FNW with morse taper**



**TYPE FNW**

MK	D1	D2	D3	L1	L2	cat. no.
3	24	M27 x 1.5	16	121	40	<b>923 01</b>
4	32	M36 x 1.5	16	154.5	52	<b>923 02</b>
5	45	M48 x 1.5	22	190	60	<b>923 03</b>
6	64	M68 x 1.5	22	252	70	<b>923 04</b>

## Carbide Dead Centers DIN 806



### for hardened workpieces

To be applied with hardened workpieces. For headstocks and fixed tailstock spindle sleeves. Designed for employment in grinding and other production machines.

#### Type DIN 806 · model E



with full carbide tip



0.002



#### Type DIN 806 · model HE



flattened with half carbide tip



0.002



with half carbide tip




- Run-out deviation max.: 0.002 mm.
- With carbide insert.
- Max. load of the dead centers upon request.
- Special design upon request.


**Technical data - type DIN 806 · model E/HE**




similar to DIN 806 · model E  
with full carbide tip



model E  
with half carbide tip



model HE  
flattened with  
half carbide tip



**MODEL E**



**MODEL HE**



MK	D1	L1	L2
1	12.2	80	26.5
2	18	100	36
3	24.1	125	44
4	31.6	160	57.5
5	44.7	200	70.5
6	63.8	270	88

cat. no.
<b>910 02</b>
<b>910 05</b>
<b>910 08</b>
<b>910 11</b>
<b>910 14</b>
<b>910 18</b>

D3	cat. no.
7	<b>910 01</b>
7	<b>910 03</b>
11	<b>910 06</b>
14	<b>910 09</b>
18	<b>910 12</b>
18	<b>910 15</b>

D3	h	L3	cat. no.
7	1.5	22	<b>911 01</b>
7	2	30	<b>911 02</b>
11	3	38	<b>911 04</b>
14	5	50	<b>911 06</b>
18	7	63	<b>911 08</b>
18	10	79	<b>911 10</b>

## Carbide Dead Centers DIN 807



### type with extraction screw thread for hardened workpieces

#### With extraction screw thread

Dead centers according to DIN 807 are designed with an extraction thread. This serves to protect the spindle bearings and is necessary for use in non-drilled sleeves.

#### Type DIN 807 · model E



with full carbide tip



0.002



#### Type DIN 807 · model HE



flattened with half carbide tip



0.002



with half carbide tip




- Run-out deviation max.: 0.002 mm.
- With carbide insert.
- Max. load of the dead centers upon request.
- Special design upon request.
- For demounting and for preventing the spindle bearing from damage of for spindle sleeves which have no through bore the center pins come with an extracting screw thread.
- Extracting nuts DIN 807, see page 173.


**Technical data - type DIN 807 · model E/HE**




similar to DIN 807 · model E  
with full carbide tip



model E  
with half carbide tip



model HE  
flattened with  
half carbide tip



**MODEL E**



**MODEL HE**



MK	D1	D2	L1	L2
1	12.2	M16 x 1.5	90	36.5
2	18	M22 x 1.5	112	48
3	24.1	M27 x 1.5	138	57
4	31.6	M36 x 1.5	175	72.5
5	44.7	M48 x 1.5	217	87.5
6	63.8	M68 x 1.5	290	108

cat. no.

**912 02**

**912 05**

**912 08**

**912 11**

**912 14**

**912 18**

D3

cat. no.

7

**912 01**

7

**912 03**

11

**912 06**

14

**912 09**

18

**912 12**

18

**912 15**

D3

h

L3

cat. no.

7

1.5

22

**913 01**

7

2

30

**913 03**

11

3

38

**913 06**

14

5

50

**913 09**

18

7

63

**913 12**

18

10

79

**913 15**

## Dead centers FE / FEC



### Type taper 1:7.5 / Ø 28.33

For use in **EMAG turning-, grinding- and other production machines**

#### Type FE taper 1:7.5

» can be reground

↑ 0.002



#### Type FEC taper 1:7.5

» extending tool clearance  
for better access of the machining tool

↑ 0.002



- Run- out deviation max.: 0.002mm
- Made of through hardened tool steel
- All types with extracting thread to prevent spindle bearings and solid spindle sleeves from damage
- Extracting nuts see page 173 for accessories
- Max. load of the dead centers upon request
- Special design upon request

#### Type FE carbide taper 1:7.5

HM with full carbide tip

↑ 0.002



#### Type FEC carbide taper 1:7.5

» extending tooling clearance  
for better access of machining tool


↑ 0.002

HM with half carbide tip



- Run- out deviation max.: 0.002mm
- With carbide insert
- Max. load of the dead centers upon request
- Special design upon request
- All types with extracting thread to prevent spindle bearings and solid spindle sleeves from damage
- Extracting nuts see page 173 for accessories


**Technical data - type FE / FE HM taper 1:7.5**



type	D1	D2	D3	L1	L2	cat. no.
FE	28	M32x1.5	-	115	60	<b>914 03</b>

type	cat. no.
FE carbide	
<b>FE carbide</b>	<b>914 13</b>

**Technische Daten - type FEC / FEC HM taper 1:7.5**



type	D1	D2	D3	L1	L2	cat. no.
FEC	28	M32x1.5	8	105	50	<b>914 01</b>
FEC	28	M32x1.5	14	105	50	<b>914 02</b>

type	cat. no.
FEC carbide	
<b>FEC carbide</b>	<b>914 11</b>
<b>FEC carbide</b>	<b>914 12</b>



## Carbide Bull Nose Cones FNK

### for hardened workpieces

Our carbide bull nose cones FNK are made for hardened workpieces, with big center holes, for grinding and other manufacturing machines. For headstocks and fixed tailstock spindle sleeves.

#### Type FNK



mushroom carbide bull nose



0.002



- Run-out deviation max.: 0.002mm.
- With carbide insert.

Upon request:

- Max. load of the bull nose cone.
- Special designs.

### with extraction screw thread for hardened workpieces

FNK bull nose cones are made with extraction screw thread. This serves to protect the spindle bearings and is used for sleeves that are non-drilled.

#### Type FNK with extraction screw thread



mushroom carbide bull nose



0.002




- Run-out deviation max.: 0.002mm.
- With carbide insert.
- With spanner flat.
- All types with extraction screw threads for protecting the spindle bearings or for non-drilled sleeves.
- Extracting nuts see page 173 for accessories.

Upon request:


- Max. load of the bull nose cone.
- Special design.

### Technical data - type FNK



MK	D1	D2	D3	L1	L2	cat. no.
2	30	10	-	100.5	36.5	<b>915 01</b>
2	40	20	-	103.5	39.5	<b>915 03</b>
2	50	30	-	108.5	44.5	<b>915 05</b>
3	30	10	-	118.5	37.5	<b>915 06</b>
3	35	15	-	121.5	40.5	<b>915 07</b>
3	40	20	-	121.5	40.5	<b>915 08</b>
3	45	25	-	121.5	40.5	<b>915 09</b>
3	55	35	-	126.5	45.5	<b>915 11</b>
3	70	50	-	131.5	49.5	<b>915 13</b>
4	40	20	-	145.5	43	<b>915 17</b>
4	50	30	-	150.5	48	<b>915 19</b>
4	60	40	-	155.5	53	<b>915 21</b>
4	70	50	-	155.5	53	<b>915 22</b>
4	80	60	-	155.5	53	<b>915 23</b>
5	55	35	-	175	48	<b>915 29</b>
5	60	40	-	180	53	<b>915 30</b>
5	70	50	-	180	53	<b>915 31</b>
5	80	60	-	180	53	<b>915 32</b>

### Technical data - type FNK with extraction screw thread



MK	D1	D2	D3	L1	L2	cat. no.
3	35	15	M27 x 1.5	134.5	57	<b>915 071</b>
3	50	30	M27 x 1.5	138.5	61	<b>915 101</b>
4	45	25	M36 x 1.5	167	64.5	<b>915 181</b>
4	60	40	M36 x 1.5	168	65.5	<b>915 211</b>
5	55	35	M48 x 1.5	197	67.5	<b>915 291</b>
5	70	50	M48 x 1.5	199	69.5	<b>915 311</b>

## Changeable Center Cones for type RNA / FNA


### center cones for large workpiece centers

High degree of flexibility for clamping of workpieces with large centers.

For type RNA / FNA with SK30 interface



Technical data - for type RNA / FNA with SK30 interface



- Suitable for live centers type RNA on page 122 - 123 and for dead centers type FNA on page 148 - 149.
- Special cones up to  $\varnothing$  400 available upon customer's request.
- The center cones are fastened with a screw M8 DIN 912 onto the base body.
- The center cones can be drawn off with a screw M10.

#### FOR TYPE RNA / FNA

W1	D1	D2	L	cat. no.
60	20	85	60	<b>814 50</b>
60	70	135	60	<b>814 51</b>
60	120	185	60	<b>814 52</b>
60	170	235	60	<b>814 53</b>
60	220	285	60	<b>814 54</b>
75	20	105	60	<b>814 55</b>
75	90	175	60	<b>814 56</b>
75	160	245	60	<b>814 57</b>
75	230	315	60	<b>814 58</b>
90	20	130	60	<b>814 59</b>
90	100	210	60	<b>814 60</b>
90	180	290	60	<b>814 61</b>

## Changeable Center Cones for type RKA


### center cones for large workpiece centers

Workpieces with large center holes from  $\varnothing 120$  to  $\varnothing 460$  are clamped with a basic retainer and a changeable center cone.

#### for type RKA · centering taper



#### Technical data - for type RKA · centering taper



- Suitable for live center type RKA on page 126 - 127.
- Special changeable center cones ( $90^\circ / 75^\circ$  / various diameters) available upon customer's request.
- True run-out accuracy max 0.02 at changeable center cone is guaranteed.

#### FOR TYPE RKA

D1	D2	L	cat. no.
113	220	98.5	<b>814 80</b>
195	275	75	<b>814 81</b>
270	350	75	<b>814 82</b>
345	425	75	<b>814 83</b>
380	460	75	<b>814 84</b>

## Changeable Inserts for type RNW / FNW

### Changeable inserts for a maximum of flexibility

The adaptation of various changeable inserts ensures a high degree of flexibility and saving of costs.

#### For type RNW / FNW with taper interface

model B



model G



- Suitable for live centers type RNW on page 128-129, for the live centers type RNWF on page 134-135 and for the dead centers type FNW on page 148-149.
- Special inserts available upon customer's request.
- For quick demounting all changeable inserts come with spanner flat or cross hole.








#### FOR TYPE RNW3 / 4 FNW MK3 / MK4

model	D1	D2	D3	D4	L	cat. no.
<b>A</b>	22	-	-	16	30	<b>815 50</b>
<b>B</b>	22	10	-	16	40	<b>815 51</b>
<b>C</b>	22	7	10	16	30	<b>815 52</b>
<b>D</b>	22	11	-	16	30	<b>815 53</b>
<b>E</b>	55	21	-	16	35	<b>815 54</b>
<b>F</b>	55	50	16	16	30	<b>815 55</b>
<b>G</b>	22	10	-	16	40	<b>815 56</b>

#### FOR TYPE RNW5 / 6 FNW MK5 / MK6

model	D1	D2	D3	D4	L	cat. no.
<b>A</b>	34	-	-	22	35	<b>815 60</b>
<b>B</b>	34	16	-	22	54	<b>815 61</b>
<b>C</b>	34	7	10	22	29	<b>815 62</b>
<b>D</b>	34	18	-	22	35	<b>815 63</b>
<b>E</b>	70	33	-	22	38	<b>815 64</b>
<b>F</b>	70	64	24	22	34	<b>815 65</b>
<b>G</b>	34	16	-	22	54	<b>815 66</b>

**Technical data - for type RNW / FNW with taper interface**





positive driver

**In addition to our standard portfolio, we manufacture a large number of special applications according to customer requirements.**

Based on your processes, specifications and drawings we will prepare an appropriate offer for you. Our aim is to develop a suitable clamping tool for you and to manufacture it to the highest quality standards.

From your inquiry to the practical use of the new clamping tool directly on site, we guarantee expert advice and seamless support.

Developing new clamping tools or improving existing processes is part of our daily business and we look forward to supporting you, on your way to finding the clamping tool that is suitable for you.

# Special Applications



dead center with carbide ball



RNS with air purge



friction taper


<b>Special Face Drivers</b>	<b>164</b>
Face Driver FFB	164
Positive Driver	164
Face Driver FSB	165
Face Driver FDNC	165
<b>Special Live Centers</b>	<b>166</b>
Live Center RNS with speed monitoring	166
Live Center RN adjustable	166
Live Center RNS with air purge	167
Live Center RN with 3-spot contact	167
<b>Special Dead Centers</b>	<b>168</b>
Dead Center with carbide ball	168
Female Dead Center flattened	168
Dead Center with HSK-C50 retainer	168
Dead Center with carbide bars	169
Dead Center with flange retainer	169
Friction Taper with carbide ring	169



## Face Driver FFB

**cylindrical set down and extended in length**

Type FFB · special design



Thanks to the cylindrical set down and extended design of the face driver, the outer and inner contours of the workpiece can be completely machined in one single clamping.

- clearance for the cutting tool
- torque transmission along a radius by using angled drive pin chisels



## Positive Driver

**with changeable drive head**

Type positive driver · special design



Torque transmission by special adapted drive heads, according to the work piece shape.

- changeable drive heads
- robust torque transmission by positive driving

## Face Driver FSB



with big centering and internal clamping diameter

Type FSB · special design



The reduced weight by cylindrical set down of the short taper flange and the special mushroom type center pin with recesses for the drive pins, are the features of this face driver.

- extended deflection
- special center pin with recesses

## Face Driver FDNC



with customer specific retainer

Type FDNC · special design



FDNC face driver with customized retainer, for direct mounting in a gear hobbing machine.

- customized quick change retainer



## Live Center RNS with speed monitoring

### integrated speed monitoring sensor with plug-in connection

#### Type RNS · special design

HM with carbide tip



Used to monitor the workpiece rotation during the manufacturing process. If the workpiece rotation is stopped by a collision, the speed monitoring sensor of the live center detects this and stops the machine spindle immediately.

- integrated speed monitoring sensor
- minimizing the damage caused by a collision
- easy integration to the machine control

## Live Center RN adjustable

### eccentric adjustable center pin



#### Type RN · special design



This live center was designed to adjust the center pin radially. On the one hand, eccentric workpieces can be adjusted to  $\pm 1$  mm from the center and on the other hand, the center pin can be adjusted to approx. 1  $\mu$  run out accuracy.

- radial adjustable center pin

## Live Center RNS with air purge



### air purge connection and flange retainer

#### Type RNS · special design

HM with carbide tip



This live center was designed according to customer specifications and is characterized by an air purge connection, flange mount and speed monitoring using a wrench flat.

- air purge connector
- flange retainer
- half carbide tip
- spindle for speed monitoring

## Live Center RN with 3-spot contact



### 3-spot contact made of carbide

#### Type RN · special design

HM with carbide tip



This live center is characterized by a special manufactured, mushroom type spindle with carbide tip, which ensures a 3-spot contact of the workpieces.

- segmented 3-spot contact made of carbide
- for rough work piece center holes

## Dead Center with carbide ball

### Special design

HM with carbide ball



For grinding operations with fixed tailstock spindle sleeves or alternatively for hard turning operation with live tailstock sleeves. When used with fixed tailstocks, the spherical shape reduces friction in the center hole.

- morse taper size 4 retainer
- with carbide ball  $\varnothing 18$
- extracting thread M30x1.5

## Female Dead Center flattened

### Special design

HM with carbide insert



For grinding operations with fixed tailstock spindle sleeves. The flattening of the centering area provides clearance for the grinding wheel.

- morse taper size 2 retainer
- with carbide insert  $\varnothing 15$
- female centering  $\varnothing 12 / 90^\circ$
- flattened  $h = 6.9 \text{ mm}$

## Dead Center with HSK-C50 retainer

### Special design

HM with carbide tip



For use in grinding and milling machines.

- HSK-C50 retainer
- with carbide insert  $\varnothing 40$

## Dead Center with carbide bars

### Special design



with carbide bars



The 3-spot contact is used for grinding and other hard manufacturing operations with not perfectly round center holes.

- flange retainer
- with carbide bars

## Dead Center with flange retainer

### Special design



with carbide tip



For use in manufacturing machines, like grinding and other hard manufacturing operations.

- flange retainer  $\varnothing 100$
- with carbide tip  $\varnothing 55$

## Friction Taper with carbide ring

### Special design



with carbide insert



For use in manufacturing machines, like grinding and other hard manufacturing operations. Torque transmission to the work piece via high-precision female taper, by using axial force.

- friction taper
- with carbide ring  $\varnothing 40.6 \times 14^\circ$
- retainer  $\varnothing 50$

# General accessories



Extracting nut DIN 1804 h



thrust indicator KMD

## GENERAL ACCESSORIES

### Extracting Disks and Extracting Nuts

Extracting disk	172
Extracting nut DIN 1804 h	173
Extracting nut DIN 807	173

### Hook Wrench and Open-End Wrench

Hook wrench DIN 1810 A (for extracting nut DIN 1804 h)	174
Open-end wrench DIN 894 (for extracting nut DIN 807)	174

<b>Puller Set</b>	<b>175</b>
-------------------	------------

<b>Pliers</b>	<b>175</b>
---------------	------------

<b>Thrust Measuring System</b>	<b>176</b>
--------------------------------	------------

<b>Taper Cleaner / Cone Wiper</b>	<b>178</b>
-----------------------------------	------------

<b>Installation- / Removal Paste</b>	<b>178</b>
--------------------------------------	------------

# Service & Training



Repair service



Training


## SERVICE & TRAINING

<b>Repair service</b>	<b>179</b>
<b>Training</b>	<b>179</b>

## Extracting Disks and Extracting Nuts

### Accessories for demounting

Accessories for safe and quick demounting of our ultra live centers, dead centers, center pins and face drivers.




### Extracting disk

#### Extracting disk




#### Technical data - extracting disk



for ultra live centers **type RN/RNC/RNA/RNW/RNS**


for type	MK	D1	D2	h	cat. no.
<b>1</b>	<b>2</b>	22	60	4	<b>830 30</b>
	<b>3</b>	28	80	4	<b>830 31</b>
<b>3</b>	<b>4</b>	38	80	5	<b>830 32</b>
	<b>5</b>	49	80	5	<b>830 33</b>
<b>4</b>	<b>4</b>	38	100	5	<b>830 34</b>
	<b>5</b>	49	100	5	<b>830 35</b>
<b>5</b>	<b>5</b>	49	120	5	<b>830 36</b>
	<b>6</b>	70	120	6	<b>830 37</b>
<b>6</b>	<b>6</b>	70	140	6	<b>830 38</b>

**Extracting nut DIN 1804 h****Type DIN 1804 h****Technical data - type DIN 1804 h**

for ultra live centers, center pins and face drivers

D1	D2	D3	h	cat. no.
M28 x 1.5	43	50	10	<b>830 39</b>
M32 x 1.5	45	52	11	<b>830 40</b>
M35 x 1.5	47	55	11	<b>830 41</b>
M36 x 1.5	48	55	11	<b>830 42</b>
M48 x 1.5	67	75	13	<b>830 43</b>

D1	D2	D3	h	cat. no.
M58 x 1.5	80	90	13	<b>830 22</b>
M70 x 1.5	90	100	14	<b>830 44</b>
M75 x 1.5	100	110	14	<b>830 23</b>
M95 x 2	120	135	16	<b>830 24</b>
M110 x 2	140	155	16	<b>830 25</b>

**Extracting nut DIN 807****Type DIN 807****Technical data - type DIN 807**

for dead centers and center pins

MK	D1	D2	h	s	cat. no.
<b>1</b>	M16 x 1.5	23	12	24	<b>929 99</b>
<b>2</b>	M22 x 1.5	30	15.5	32	<b>930 00</b>
<b>3</b>	M27 x 1.5	39	17.5	41	<b>930 01</b>
<b>4</b>	M36 x 1.5	53	21	55	<b>930 02</b>
<b>5</b>	M48 x 1.5	67	23	75	<b>930 03</b>
<b>6</b>	M68 x 1.5	90	25.5	100	<b>930 04</b>

## Hook Wrench and Open-End Wrench

### Hook Wrench DIN 1810 A

#### Hook wrench DIN 1810 A

for extracting nut DIN 1804 h



	cat. no.
<b>M28 x 1.5</b>	<b>830 50</b>
<b>M32 x 1.5</b>	<b>830 51</b>
<b>M35 x 1.5</b>	<b>830 51</b>
<b>M36 x 1.5</b>	<b>830 51</b>
<b>M48 x 1.5</b>	<b>830 52</b>
<b>M58 x 1.5</b>	<b>830 53</b>
<b>M70 x 1.5</b>	<b>830 54</b>
<b>M75 x 1.5</b>	<b>830 55</b>
<b>M95 x 1.5</b>	<b>830 56</b>
<b>M110 x 1.5</b>	<b>830 57</b>

### Open-End Wrench DIN 894

#### Open-end wrench DIN 894

for extracting nut DIN 807



SW		cat. no.
<b>24</b>	<b>M16 x 1.5</b>	<b>830 70</b>
<b>32</b>	<b>M22 x 1.5</b>	<b>830 71</b>
<b>41</b>	<b>M27 x 1.5</b>	<b>830 72</b>
<b>55</b>	<b>M36 x 1.5</b>	<b>830 73</b>
<b>75</b>	<b>M48 x 1.5</b>	<b>830 74</b>
<b>100</b>	<b>M68 x 1.5</b>	<b>830 75</b>

## Puller Set

### complete with case

#### Puller set with slide hammer in plastic case

Stable extractor (galvanised) with ergonomically shaped slide hammer.

In conjunction with the appropriate adapter, the centre pin is removed by means of vigorous strikes with the slide hammer.

#### Use:

For removing centre pins with internal thread

#### Puller set with slide hammer in plastic case

Pin extractor in plastic case (275 x 230 x 80 mm) with thread inserts (M3 - M12)



type	cat. no.
M3 - M12	500 20


## Pliers

#### Use:

For gripping and dismantling drive pins Ø6 - 10 mm

#### Pliers

type	cat. no.
46-10	500 50



## Thrust Measuring System

### Hydraulic measuring of clamping thrust for face drivers and live centers for measuring the ideal clamping thrust on machine tools

For setting up and checking the clamping thrust required, it is necessary to have a thrust indicator. A pressure gauge on the machine without tabulation or conversion is insufficient.

The hydraulic thrust measuring system is perfectly suitable for safe adjusting and checking of the clamping thrust within the machine.


#### Type KMD - thrust indicator including centered tailstock piece and case



### Clamping principle

#### Type KMD and type AP

The thrust measuring system is set up between face driver and tailstock center.




## Thrust indicator

### Device for measuring clamping thrust in machine tools

All thrust indicators are equipped with a differential thrust indicator as well as a centered tailstock piece.

In order to ensure a perfect torque transmission of the face drivers onto the work piece, it is essential to determine the chisel load of the drive pins accurately.

#### Technical data - type KMD



type KMD	D1	D2	D3	L1	L2	L3	D4	L4	measuring range [KN]	scale division [daN]	application	cat. no.	
<b>250</b>	63	45	70	75	16	50	44	20	0 - 2.5	0 - 250	0.1	grinding	<b>500 01</b>
<b>1600</b>	63	45	70	75	16	50	44	20	0 - 16	0 - 1600	0.5	turning	<b>500 02</b>
<b>2500</b>	63	45	70	75	16	50	44	20	0 - 25	0 - 2500	1	turning	<b>500 03</b>


## Thrust piece

### interim plate on face driver

In order to measure the impact of thrust onto the face driver, it is essential to have an adapter plate for parallel and even contact of the drive pins.

#### Technical data - type AP


type AP	D5	D6	L5	for face driver sizes	cat. no.
<b>50</b>	50	5	12	0 - 35	<b>500 10</b>
<b>102</b>	102	15	18	4 - 5	<b>500 11</b>
<b>175</b>	175	20	28	55 - 6	<b>500 12</b>



## Taper Cleaner / Cone Wiper

**for cleaning an inner Morse taper**  
(e. g. work spindle or tailstock)

### Taper cleaner / cone wiper



MK	cat. no.
1	500 31
2	500 32
3	500 33
4	500 34
5	500 35
6	500 36

## Installation / Removal Paste

**Universal use as installation paste and for preventing fretting corrosion**

Castrol Optimol Paste White T is ideal for all installation work as well as for base-film and thin-film lubrication. The paste prevents fretting rust as well as facilitating installation and removal of our clamping tools.

It is resilient to hot and cold water and provides anti-corrosion protection.

### Installation- / removal paste

white, virtually colourless when applied as a thin film

### cat. no.

500 40



## Repair Service

### Our service for sustainable machining

Our clamping tools boast a long service life. After continuous use over lengthy periods of time or if damage occurs during production, we get the tools back into perfect shape with the necessary maintenance or repair. This investment is generally worthwhile since you then have a tool that is fully functional and virtually as good as new.



We will be pleased to compile a cost estimate for repair and maintenance, including delivery period.



## Training

We provide free product training so as to enable you to put our products to effective use in line with requirements.

Whether on our premises or yours, we give you an overview of our product range and as well a detailed specialist knowledge in terms of cost efficiency, quality and safety.

Training is provided in German and English.

If you wish to take advantage of our training programmes, please get in touch with our Technical Sales department and our staff will take care of everything else.

[www.neidlein.de](http://www.neidlein.de)

» Contact » Contact person » technical sales



You will find our GTB at

[www.neidlein.de](http://www.neidlein.de)





**NEIDLEIN-SPANNZEUGE GmbH** · Erlenbrunnenstraße 3 · 72411 Bodelshausen · Germany  
Phone +49 7471 9608-0 · Fax +49 7471 9608-14 · [info@neidlein.de](mailto:info@neidlein.de)

[www.neidlein.de](http://www.neidlein.de)

No. 01.08.24